[INCH-POUND]
A-A-50691A
28 DECEMBER 1998
SUPERSEDING
A-A-50691
INT.AMEMDMENT - 1
17 JUNE 1993
A-A-50691
2 NOVEMBER 1990

.

COMMERCIAL ITEM DESCRIPTION

TRUCK, AIRCRAFT BAGGAGE LOADING-UNLOADING

The General Services Administration has authorized the use of this commercial item description, for all federal agencies.

1. SCOPE. This commercial item description covers the general requirements for a self-contained, self-propelled, operator driven vehicle mounted belt conveyor for use to load and unload aircraft baggage and cargo, and for the movement of material handling ground support equipment.

2. SALIENT CHARACTERISTICS.

2.1 Dimensions. The fully operational vehicle shall have a wheelbase of not less than 94 inches, with overall dimensions for length of the vehicle not to exceed 300 inches, width 84 inches, and height 56 inches. Conveyor dimensions shall not exceed the length 300 inches, overall conveyor width 36 inches, and a minimum belt width of 24 inches.

2.2 Conveyor. The conveyor belt shall be a minimum 2-ply, non-slip rubber with only one lace joint. The conveyor shall have a reversible motor with infinite variable speed control from 40 feet per minute (fpm) to 100 fpm in each direction under full load of 1000 pounds. The conveyor belt shall have an over-center valve to prevent belt runaway under load. Automatic belt aligners and non-slip pulleys shall be provided, these shall be surface treated to prevent corrosion. Conveyor belt stop sensors shall be furnished to stop the belt if the operator is between the belt conveyor and aircraft. A permanently mounted control station shall be mounted at the left rear, and a removable remote control, with minimum 10 foot length extension cable, shall be located at the left front. Both control stations shall be continually active at any conveyor position. The conveyor elevating mechanism shall be capable of raising and lowering the conveyor at rated capacity from 39 to 132 inches at the front and 22 to 52 inches at the rear. Minimum seven inch outside diameter weather resistant rubber bumpers, located at the front and rear of the conveyor, shall be provided. Positive locking maintenance stands and guide rails shall also be provided.

2.3 Neutral start switch and starter lockout. The vehicle electrical system shall be designed to prevent engaging the starter while the engine is operating, and when the transmission is in any position except neutral.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data which may improve this document should be sent to: WR-ALC/LEG, 225 OCMULGEE CT, ROBINS AFB GA 31098-5609.

AMSC N/A FSC 3930

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:45Z
Check the source to verify that this is the current version before use.

2.4 Electrical system. A 12 volt vehicle electrical system shall be furnished and have sufficient capacity to operate all electrical components simultaneously without battery discharge. The electrical system shall consist of all electrical components necessary for operation of the vehicle and conveyor. There shall be sufficient electrical grounding to prevent static discharge. All circuits shall be protected by circuit breakers and guarded from environmental conditions. Each circuit breaker shall be labeled and readily accessible. At least one maintenance free battery shall be provided and mounted in a readily accessible and protected area.

2.5 Hydraulic system. The hydraulic system shall consists of all hydraulic components necessary for operation of the vehicle, including filter(s), drier(s) and strainer(s). The vehicle shall be designed so that hydraulic fluid does not exceed 100°F above the ambient temperature during all operations, or temperature recommended by the manufacturer. All hydraulic lift cylinders shall incorporate safety check valves.

2.6 Vehicle lighting. Headlights, running lights, brake lights, backup lights, and rear work light shall be provided. All lighting and control switches shall be designed for all weather operation. All lighting and reflectors mounted on vertical surfaces shall be flush or recessed to preclude damage.

2.7 Backup alarm. An audible backup alarm shall be furnished.

2.8 Electromagnetic interference (EMI). If applicable, the vehicle shall comply with the EMI requirements of SAE J551.

2.9 Operator's compartment. The operator's compartment shall be large enough to permit comfortable operation by a minimum 250 pound driver without hampering movement. A seatbelt shall be furnished. In addition to the instruments supplied on the standard commercial vehicle, the following instruments and gauges shall be furnished: speedometer, odometer, hourmeter, oil pressure gauge, battery voltage indicator, water temperature gauge, hydraulic fluid pressure gauge, and fuel gauge. All instruments and gauges, except the hourmeter, shall be lighted and shall illuminate when the headlights are turned on. All controls and switches shall be clearly marked, identified, and shall be accessible by the operator while seated and seatbelt secured. Two adjustable side mounted mirrors shall be provided, positioned and mounted so that they do not obstruct the forward or side line-of-sight of the driver.

2.10 Engine. The vehicle shall be powered by a standard commercial liquid cooled diesel engine. Horsepower and torque shall be sufficient to provide the performance specified herein. The engine shall operate on diesel fuel in accordance with A-A-52557 without detrimental effects to the engine or its performance. A fuel tank shall be provided of sufficient capacity to allow eight hours of continuous operation without refueling. The fuel system shall incorporate a water separator that is readily accessible and easily replaced. The engine shall be protected from the environment by a hinged engine cover. Engine exhaust shall not be directed toward the ground.

2.11 Transmission. A minimum of three forward and one reverse geared automatic transmission shall be furnished complete with a hydraulic torque converter that has a capacity of least 105 percent of the maximum net engine torque. The transmission shall be provided with a transmission oil cooler or a fluid heat exchanger in the radiator.

2.12 Brakes, wheels and tires. The vehicle shall be equipped with four-wheel power assisted brakes capable of withstanding 250 pounds of brake force without component failure. Service brakes shall be capable of stopping the vehicle, at rated capacity, in a smooth controlled manner. Parking brake and service brakes shall be capable of independently holding the vehicle, at rated capacity, on a 21 percent incline in both ascending and descending slope directions. The brake pedal shall have a nonskid metal surface or replaceable rubber cap. Tire and wheel assemblies shall be commercial items suitable for the vehicles intended usage.

2.13 Steering. The vehicle shall be furnished with power assisted steering.

2.14 Turn radius. The maximum turn radius of the vehicle, measured from outside of the tires, shall be 30 feet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:45Z
Check the source to verify that this is the current version before use.

2.15 Travel speed. The maximum vehicle travel speed, forward at rated capacity, shall be 20 mph.

2.16 Environment. The vehicle shall be designed for operation in all weather conditions, such as: wind, rain, sleet, snow, etc. The vehicle shall be designed for operation in ambient temperatures ranging from -25°F to +125°F. Adequate winterization shall be furnished as necessary to protect the engine, battery(s), and other components for operation and storage at -25°F.

2.17 Towing lugs. Two towing lugs at the front and two at the rear of the vehicle shall be provided. The lugs shall be capable of sustaining a horizontal force of two times that of the gross vehicle weight (GVW) without material deformation. Tow lugs shall have a minimum 3 inch inside diameter opening.

2.18 Finish. The outer surfaces of the vehicle and interior surfaces of compartments shall be primed and painted with the manufacturer's standard commercial primer and paint. Finish color shall be equivalent to FED-STD-595, forest green, color number 24052.

2.19 Data plates, identification and markings.

2.19.1 Schematics. Separate wiring and hydraulic schematic data plates of corrosion and weather resistant material shall be furnished. Each schematic shall be permanently installed in an area where normal usage will not cause damage. Schematic plates may be located behind a panel, which can be opened by hand without the need for tools.

2.19.2 Transportation data plate. A transportation data plate shall be permanently installed in a readily accessible location. The following information shall be provided on the data plate for the vehicle in transportation configuration:

a. SIDE AND REAR SILHOUETTE VIEWS OF THE VEHICLE
b. HORIZONTAL AND VERTICAL LOCATION OF CENTER OF GRAVITY
c. LOADING CUBAGE
d. GROSS SHIPPING WEIGHT
e. OVERALL LENGTH, WIDTH AND HEIGHT OF VEHICLE
f. TIE DOWN LOCATIONS AND CAPACITY

2.19.3 Vehicle identification plate. A vehicle identification plate shall be permanently installed in the operator's compartment. The data plate shall include the following information:

a. DoD AGENCY
b. REGISTRATION NUMBER
c. NOMENCLATURE
d. NATIONAL STOCK NUMBER (NSN)
e. MANUFACTURER'S NAME, ADDRESS AND SERVICE PHONE NUMBER
f. MANUFACTURER'S MAKE AND MODEL NUMBER
g. MANUFACTURER'S SERIAL NUMBER
h. VEHICLE CURB WEIGHT
i. GROSS VEHICLE WEIGHT (GVW)
j. CONTRACT NUMBER
k. DATE OF DELIVERY (MONTH AND YEAR)
l. WARRANTY PERIOD

2.19.4 Instruction plates. All warning and instruction plates normally installed by the manufacturer, describing procedures and safety, shall be supplied and mounted on the vehicle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:45Z
Check the source to verify that this is the current version before use.

2.19.5 Marking. A license plate bracket or holder shall be provided and mounted at the rear of the vehicle. All tiedown locations with their capacity, the fuel type, and tire pressures shall be stenciled in black at their immediate areas.

3. REGULATORY REQUIREMENTS.

3.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent possible, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).
3.1.1 Materials. For the purpose of this requirement, recovered materials are those materials that have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the vehicle may be newly fabricated from recovered materials to the maximum extent practicable, provided the vehicle produced meets all other requirements of this CID. Used, rebuilt or re-manufactured components, pieces and parts shall not be incorporated.

4. QUALITY ASSURANCE PROVISIONS.

4.1 Product conformance. The product provided shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

5. PACKAGING.

5.1 Preservation, packing, labeling and marking. Unless otherwise specified in the contract, the items shall be packaged according to normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipment, handling and storage. Shipping containers shall be properly marked and in compliance with both national and uniform motor freight classifications

6. NOTES.

6.1 Intended use. The vehicle is intended for use to transfer baggage or cargo between military and civilian configured aircraft, and for the movement of material handling ground support equipment. The vehicle will be used in all environmental conditions. During non-loading hours, the vehicle will be used to clear aircraft areas of material handling ground support equipment.

6.2 Source of documents.

6.2.1 The Federal Publications may be obtained from Standardization Document Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 1911-5094

6.2.2 The Society of Automotive Engineers (SAE) documents may be obtained from SAE, 400 Commonwealth Drive, Warrendale, PA 15096-0001.

MILITARY INTEREST:

CUSTODIAN:
Air Force - 99

AGENT:
Air Force – 99

CIVIL AGENCY and
COORDINATING ACTIVITY:
GSA – 7FXE

PREPARING ACTIVITY:
Air Force - 84

(Project Number: 3930-0014)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:45Z
Check the source to verify that this is the current version before use.