INCH – POUND

A-A-50691B
December 2, 2004
SUPERSEDING
A-A-50691A
December 28, 1998

COMMERCIAL ITEM DESCRIPTION

TRUCK, AIRCRAFT BAGGAGE LOADING-UNLOADING

The General Services Administration has authorized the use of this Commercial Item Description (CID) for all federal agencies.

1. SCOPE.

1.1 Scope. This commercial item description covers the general requirements for a self-contained, self-propelled, operator driven vehicle mounted belt conveyor for use to load and unload aircraft baggage and cargo, and for the movement of material handling ground support equipment.

2. CLASSIFICATION.

2.1 Classification. The operator driven vehicle covered by this CID shall be commercially available and may be modified to the extent necessary to meet this description.

3. SALIENT CHARACTERISTICS.

The operator driven vehicle shall be capable of operation within the accuracies, limits, and specifications herein.

3.1. Dimensions. The fully operational vehicle shall have a wheelbase of not less than 94 inches, with overall dimensions for length of the vehicle not to exceed 300 inches, width 84 inches, and height 59 inches. Conveyor dimensions shall not exceed the length 300 inches, overall width 36 inches, and a minimum belt width of 24 inches.

Comments, suggestions, or questions on this document should be addressed to WR-ALC/LEEV, 295 Byron St., Warner Robins AFB, GA 31098-1611. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://assist.daps.dla.mil .

FSC 3930

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:45Z
Check the source to verify that this is the current version before use.

3.2 Conveyor. The conveyor belt shall be a minimum 2-ply, non-slip rubber with only one lace joint. The conveyor shall have a reversible motor with infinite variable speed control from 40 feet per minute (fpm) to 90 (fpm) in each direction under full load of 1000 pounds. The conveyor belt shall have an over-center valve to prevent belt runaway under load. Automatic belt aligners and non-slip pulleys shall be provided, these shall be surface treated to prevent corrosion. A permanently mounted control station shall be mounted at the left rear, and a removable remote control, with minimum 10 foot length extension cable, shall be located at the left front. Both control stations shall be continually active at any conveyor position. The conveyor elevating mechanism shall be capable of raising and lowering the conveyor at rated capacity from 39 to 132 inches at the front and 22 to 52 inches at the rear. Minimum seven inch outside diameter weather resistant rubber bumpers, located at the front and rear of the conveyor, shall be provided. Positive locking maintenance stands and guide rails shall also be provided.

3.3 Neutral start switch and starter lockout. The vehicle electrical system shall be designed to prevent engaging the starter while the engine is operating, and when the transmission is in any position except neutral.

3.4 Electrical system. A 12 volt vehicle electrical system shall be furnished and have sufficient capacity to operate all electrical components simultaneously without battery discharge. The electrical system shall consist of all electrical components necessary for operation of the vehicle and conveyor. There shall be sufficient electrical grounding to prevent static discharge. All circuits shall be protected by circuit breakers and guarded from environmental conditions. Each circuit breaker shall be labeled and readily accessible. At least one maintenance free battery shall be provided and mounted in a readily accessible and protected area.

3.5 Hydraulic system. The hydraulic system shall consist of all hydraulic components necessary for operation of the vehicle, including filter(s), drier(s) and strainer(s). The vehicle shall be designed so that hydraulic fluid does not exceed 100° F above the ambient temperature during all operations, or temperature recommended by the manufacturer. All hydraulic lift cylinders shall incorporate safety check valves.

3.6 Vehicle lighting. Headlights, brake lights, backup lights, and rear work light shall be provided. All lighting and control switches shall be designed for all weather operation. All lighting and reflectors mounted on vertical surfaces shall be flush or recessed to preclude damage.

3.7 Backup alarm. An audible backup alarm shall be furnished.

3.8 Electromagnetic interference (EMI). The vehicle shall comply with the EMI requirements of SAE J551.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:45Z
Check the source to verify that this is the current version before use.

3.9 Operator's compartment. The operator's compartment shall be large enough to permit comfortable operation by a minimum 250 pound driver without hampering movement. A handrail located adjacent to the seat shall be furnished to safely assist the operator with entering or exiting the compartment. A seatbelt shall be furnished. In addition to the instruments supplied on the standard commercial vehicle, the following instruments and gauges shall be furnished: speedometer, hour-meter, oil pressure gauge, battery voltage indicator, water temperature gauge, hydraulic fluid pressure gauge, and fuel gauge. All instruments and gauges, except the hour-meter, shall be lighted and shall illuminate when the headlights are turned on. All controls and switches shall be clearly marked, identified, and shall be accessible by the operator while seated and seatbelt secured. Two adjustable sides mounted mirrors shall be provided, positioned, and mounted so that they do not obstruct the forward or side line-of-sight of the driver. When specified (see 7.3), a Falling Object Protective Structure (FOPS) shall be provided. When specified (see 7.3), an enclosed cab incorporating FOPS shall be provided.

3.10 Engine. The vehicle shall be powered by a standard commercial liquid cooled diesel engine. Horsepower and torque shall be sufficient to provide the performance specified herein. The engine shall operate on diesel fuel in accordance with A-A-52557 without detrimental effects to the engine or its performance. A fuel tank shall be provided of sufficient capacity to allow eight hours of continuous operation without refueling. The fuel system shall incorporate a water separator that is readily accessible and easily replaced. The engine shall be protected from the environment by a hinged engine cover. Engine exhaust shall not be directed toward the ground.

3.11 Transmission. A minimum of three forward and one reverse geared automatic transmission shall be furnished complete with a hydraulic torque converter that has a capacity of least 105 percent of the maximum net engine torque. The transmission shall be equipped with an interlock system to prevent inadvertent engagement. The shifter interlock shall not permit engagement of the transmission in forward or reverse direction without application of the service brakes. The transmission shall be provided with transmission oil cooler or a fluid heat exchanger in the radiator.

3.12 Brakes, wheels and tires. The vehicle shall be equipped with four-wheel power assisted brakes capable of withstanding 250 pounds of brake force without component failure. Service brakes shall be capable of stopping the vehicle, at rated capacity, in a smooth controlled manner. Parking brake and service brakes shall be capable of independently holding the vehicle, at rated capacity, on a 21 percent incline in both ascending and descending slope directions. The brake pedal shall have a nonskid metal surface or replaceable rubber cap. The parking brake system shall be furnished with an illuminated warning light to indicate engagement. Tire and wheel assemblies shall be commercial items suitable for the vehicles intended usage.

3.13 Steering. The vehicle shall be furnished with power assisted steering.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:45Z
Check the source to verify that this is the current version before use.

3.14 Turn radius. The maximum turn radius of the vehicle, measured from outside of the tires, shall be 30 feet.

3.15 Travel speed. The maximum vehicle travel speed, forward at rated capacity, shall be 20 mph.

3.16 Environment. The vehicle shall be designed for operation in all weather conditions, such as: wind, rain, sleet, snow, etc. The vehicle shall be designed for operation in ambient temperatures ranging from -25° F to +125° F. Adequate winterization shall be furnished as necessary to protect the engine, battery(s), and other components for operation and storage at -25° F.

3.17 Towing lugs. Two towing lugs at the front and two at the rear of the vehicle shall be provided. The lugs shall be capable of sustaining a horizontal force of two times that of the gross vehicle weight (GVW) without material deformation. Two lugs shall have a minimum 3 inch inside diameter opening.

3.18 Finish. The outer surfaces of the vehicle and interior surfaces of compartments shall be primed and painted with the manufacturer's standard commercial primer and paint. Finish color shall be equivalent to FED-STD-595, forest green, Color number 24052, unless otherwise specified (see 7.3).

3.19 Data plates, identification and markings.

3.19.1 Schematics. Separate wiring and hydraulic schematic data plates of corrosion and weather resistant material shall be furnished. Each schematic shall be permanently installed in an area where normal usage will not cause damage. Schematic plates may be located behind a panel, which can be opened by hand without the need for tools.

3.19.2 Transportation data plate. A transportation data plate shall be permanently mounted in a readily accessible location. The following information shall be provided on the data plate for the vehicle in transportation configuration:

a. SIDE AND REAR SILHOUETTE VIEWS OF THE VEHICLE
b. HORIZONTAL AND VERTICAL LOCATION OF CENTER OF GRAVITY
c. LOADING CUBEAGE
d. GROSS SHIPPING WEIGHT
e. OVERALL LENGTH, WIDTH, AND HEIGHT OF VEHICLE
f. TIE-DOWN LOCATIONS AND CAPACITY

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:45Z
Check the source to verify that this is the current version before use.

3.19.3 Vehicle identification plate. A vehicle identification plate shall be permanently mounted to the operator's compartment. The data plate shall include the following:

a. DoD AGENCY
b. REGISTRATION NUMBER
c. NOMENCLATURE
d. NATIONAL STOCK NUMBER (NSN)
e. MANUFACTURER'S NAME, ADDRESS, AND SERVICE NUMBER
f. MANUFACTURER'S MAKE AND MODEL NUMBER
g. MANUFACTURER'S SERIAL NUMBER
h. VEHICLE CURB WEIGHT
i. GROSS VEHICLE WEIGHT (GVW)
j. CONTRACT NUMBER
k. DATE OF DELIVERY (MONTH AND YEAR)
l. WARRANTY PERIOD

3.19.4 Instruction plates. All warning and instruction plates normally installed by the manufacturer, describing procedures and safety, shall be supplied and mounted on the vehicle.

3.19.5 Marking. A license plate bracket or holder shall be provided and mounted at the rear of the vehicle. All tie-down locations with their capacity, the fuel type, and tire pressures shall be stenciled in black at their immediate areas.

3.20 Winterization. When specified (see 7.3), the truck shall be furnished with Type C winterization that shall consist of the following:

a. Protection to -25° F
b. Starting aid. Glow plug(s) or a measured-shot ether injection system shall be furnished.
c. Cab. The cab shall meet the requirements of paragraph 3.9, and shall also contain thermal insulation, to meet the heating requirements listed below in part (d).
d. Cab heater and defroster. The heater shall have sufficient capacity to maintain a temperature of at least +40° F (cab level) and an ambient temperature of -20° F.
e. Antifreeze. Engine coolant shall be protected to -25° F with antifreeze.

3.21 Tropical rust proofing. When specified (see 7.3), tropical rust-proofing shall be provided. This should be considered a premium rust-proofing package usually consisting of an additional coating. The truck shall be treated with a corrosion preventative compound complying with A-A-59295. A copy of A-A-59295 can be requested from WR-ALC/LESVG. Many of these vehicles are used in tropical/coastal environments and experience high humidity and salt spray. They usually exhibit high levels of corrosion in the areas listed below. At a minimum, these areas shall be coated: (1) cab interior, (2) cab exterior, (3) seams, (4) welds, (5) hidden recessed areas, (6) locations where dissimilar metals come in contact, (7) area above fuel tank(s), (8) engine oil pan & transmission oil pan, (9) radiator support structure, and (10) battery box.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:45Z
Check the source to verify that this is the current version before use.

3.22 Fire extinguisher. When specified (see 7.3), a commercial fire extinguisher shall be mounted on the truck in an easily accessible location. The fire extinguisher shall be a minimum 2 ½ pound capacity ABC type, or equivalent. The fire extinguisher shall be UL listed.

4. REGULATORY REQUIREMENTS

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the fullest maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4.1.2 Materials. For the purpose of this requirement, recovered materials are those materials that have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces, and parts incorporated in the vehicle may be newly fabricated from recovered materials to the maximum extent practicable, provided the vehicle produced meets all other requirements of this CID. Used, rebuilt, or re-manufactured components, pieces, and parts shall not be incorporated.

5. PRODUCT CONFORMANCE PROVISIONS

5.1 Product conformance. The product provided shall meet the salient characteristics of this CID, conform to the producer's own drawing, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance. Minor changes to the commercial product (with the respect to ruggedizing, environmental suitability, and protection) shall be permitted, subject to the approval of the procurement office, to satisfy these requirements.

6. PACKAGING.

6.1 Packaging. Preservation, packing, and marking shall be as specified in the contract. Unless otherwise specified in the contract, the items shall be packaged according to normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipment, handling, and storage. Shipping containers shall be properly marked and in compliance with both national and uniform motor freight classifications.

7. NOTES

7.1 Intended use. The vehicle is intended for use to transfer baggage or cargo between military and civilian configured aircraft, and for the movement of material handling ground support equipment. The vehicle will be used in all environmental conditions. During non-loading hours, the vehicle will be used to clear aircraft areas of material handling ground-support equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:45Z
Check the source to verify that this is the current version before use.

7.2 Source of documents.

Military Specifications, Standards, and Handbooks referenced herein may be obtained online at http://assist.daps.dla.mil/quicksearch/ or from the Standardization Document Order Desk, Building 4, Section D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

The Society of Automotive Engineers (SAE) documents may be obtained online at http://www.sae.org or from SAE, 400 Commonwealth Drive, Warrendale, PA 15096-0001.

NIST Handbook 44 may be obtained online at http://www.nist.gov/ or from NIST Public Inquiries, NIST, 100 Bureau Drive, Stop 3460, Gaithersburg, MD 20899-3640.

7.3 Ordering Data. Procurement documents must specify the title, number, and date of this CID, issue of DODISS to be cited in the solicitation, and preservation and packaging requirements.

Falling Object protective Structure (see 3.9)
Enclosed operator's compartment/cab (see 3.9)
Finish/Color (see 3.18)
Winterization (see 3.20)
Tropical rust proofing (see 3.21)
Fire extinguisher (see 3.22)

MILITARY INTERESTS:

Custodian:
Air Force – 99

Civil Agency and
Coordinating Activity:
GSA-7FXE

Preparing Activity:
Air Force – 84

Agent:
Air Force – 99

(Project 3930-0040)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:45Z
Check the source to verify that this is the current version before use.