A-A-50693
February 25, 1991

COMMERCIAL ITEM DESCRIPTION

TRUCK, AIRCRAFT CARGO LOADING - UNLOADING, WIDE BODY

"The General Services Administration has authorized the use of this commercial item description."

SCOPE. The new commercial Truck Aircraft Cargo Loader - Unloaders must be capable of servicing wide body aircraft main deck cargo doors of B747, DC10, and KC10 aircraft, the lower-lobe cargo door on the B747, and the front lower-lobe cargo door of the DC10 or any cargo door on the above listed aircraft that will accept 88" x 108" military 463L pallets. The intended use is for loading and unloading of cargo to and from the aircraft only, not for transportation of cargo.

SALIENT CHARACTERISTICS. The failure of the Truck, Aircraft Cargo Loader - Unloader to meet the following salient characteristics will require rejection of the offer. The loaders shall be free from faulty construction or any defect which affects appearance, serviceability and durability. The loaders shall be representative of the quality and workmanship found in loaders offered for new commercial sale.

a. Load capacity of a minimum of 40,000 pounds.

b. Capable of lifting three 88" x 108" military 463L pallets from a height of 20 inches to 216 inches.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: WR-ALC/LZMD, Robins AFB, GA 31098-5609, By using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3930

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:45Z
Check the source to verify that this is the current version before use.

c. Must have aircraft interface feature to prevent separation of vehicle and aircraft during on/off of driven vehicles.

d. Self propelled, diesel engine powered capable of a ground speed of 4mph minimum, with inching control for final positioning near aircraft. Engine shall be of common industrial design .

e. Single operator capability.

f. Mechanical, hydraulic, or electrical operated pallet stops to prevent accidental off-loading of pallets.

g. Ladder to allow access to operator's platform at any level. Platform located at aircraft end of loader.

h. Platform deck pallet transfer using electrical or hydraulic powered retractable belts, rollers or wheels.

i. Fuel tank capacity sufficient to support eight hours of continuous normal operation.

j. Integral check valves on all lift cylinders to protect against pressure loss related platform drops.

k. Emergency lowering systems and roll away feature if engine power is lost.

l. All controls and switches shall be weather proof or suitable for continuous outdoor use.

m. Power steering and dynamic braking shall be furnished.

n. Rear main platform capable of accepting over the crest wheeled axle loads of 15,000 pounds minimum.

o. Pallet side load capability from either side to be located on the rear portion of the platform.

p. Loader must have an established in commission rate of 90 plus or minus 5 percent and be of standard commercial design in service for at least three years.

q. The contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:45Z
Check the source to verify that this is the current version before use.

practicable. Used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the truck.

r. The contractor shall make available the following:

1. A minimum of eight hours training for five operators at each location.

2. A minimum of 24 hours in factory training for two mechanics for each loader acquired. Training must include hydraulic/electrical systems and schematic interpretation.

CONTRACTOR CERTIFICATION. The contractor shall certify that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product offered for sale in the commercial marketplace. Small businesses that cannot offer products with established commercial acceptability may compete by submission of bid samples. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

PACKAGING, PACKING, AND MARKING. The loader shall be packaged in accordance with the contractor's commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage while in transit.

The following shall be required by the contracting officer at time of procurement:

a. Transportation of loader to each location.

b. Assembly, operation and test at each site.

c. A list of recommended spare parts to include quantities and cost to support each loader for one year. the equipment manufacture shall sell spare parts to either base contracting/acquisition or the base contractor operated parts store (COPARS) at most favored customer price. Contractor agrees that parts will be readily available for a minimum of ten years from date of equipment delivery.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:45Z
Check the source to verify that this is the current version before use.

d. Technical manuals to include operation, maintenance and parts manuals. The parts manuals shall list the component manufacturer's part number and the equipment manufacturer's part number as applicable. one set of manuals to be supplied with each loader.

e. A list of any special tools and test equipment necessary, to include cost and sources.

f. Any required adapters or interface devices for lower lobe and main deck cargo doors.

CUSTODIAN:
AIR FORCE - 99

PREPARING ACTIVITY:
AIR FORCE - 84

Project Number:
3930-F023

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:45Z
Check the source to verify that this is the current version before use.