A-A-50748
6 May 1987

Commercial Item Description

HOLSTER, HIP, PISTOL, SEMI-AUTOMATIC, 9MM.

The General Service Administration has authorized the use of this commercial item description.

scope:

This commercial item description Covers left and right band hip holsters for use with the 9MM M9 semi-automatic PISTOL.

Applicable Documents:

Standards:

FED-STD-751	Stitches, Seams and Stitching
FED-STD-595	Color, Requirements for individual color chips, 3x5
MIL-STD-130	Identification marking of U.S. Military property

Drawings:

99A-RH-P, Holster, Hip, Pistol, 9MM.
99A-LH-P, Holster, Hip, Pistol, 9MM.
Drawings available from Warner Robins, ALC/CREMS
Robins AFB, GA 31096-5609

Salient Characteristics:

The holster shall be capable of interface and fit with the government furnished 9MM, M9 pistol.There shall not be excessive interference when insering and withdrawing the pistol, nor will they cause functioning of any of the pistol controls.

The holster shall comply with the requirements as defined in the drawings and as called out in the contract or order. The holster shall be manufactured from leather, thread, and required hardware (snaps/rivets). All stitching shall comply with the requirements set forth in FED-STD-751, stitch type 301, 5 to 7 stitches per inch.

Color:

Holsters shall be black and conform color number 27038 of FED-STD-595

Identification Marking:

Each holster shall be indelibly marked with the letters "US", part number, national stock number, manufacturer's name and FSCM code. Markings shall conform to TO MIL-STD-130 and be in the size and location indicated on the applicable drawing.

DISTRIBUTION STATEMENT A. Approved for public release: distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:46Z
Check the source to verify that this is the current version before use.

Workmanship:

Holsters shall be free of dust, grease, corrosion and other foreign matter. The finished holsters shall conform to the quality of product established by this document and as called called out in the contract or order.

Repairs of Type 301 Stitching:

Repairs of type 301 stitching shall be as follow:

a. When thread breaks or bobbins run-outs occur during stitching, the stitching shall be repaired by restarting the stitching a minimum of 2 stitches back of the end of stitching.

b. Thread breaks or one or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 2 stitches in back of the defective area, continue a minimum of 2 stitches beyond the defective area onto the existing stitching. Loose stitching shall be repaired by removing the defective stitching without damaging the materials and restitching in the required manner.

c. When making the above repairs, stitches shall enter and exit previously made neele holes.

Thread Ends:

All thread ends shall be trimmed to 1/8 inch maximum length.

Certification:

The contractor shall certify that the product offered-meets the salient characteristics of this description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same product offere for sale in the commercial marketplace. Small businesses that cannot offer products with established commercial market acceptability, may compete by submission of bid samples. (The Governament reserves the rights to require proof of such conformance before first delivery and thereafter as may be otherwise provided for under provisions of the contract.)

Packaging, Packing, and Markings:

The items shall be packaged in accordance with normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with national motor freight classification. Shipping container shall be markd as specified in the contract order.

Notes:

Type I - Right Hand
Type II - Left Hand

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:46Z
Check the source to verify that this is the current version before use.

Known, Acceptable Items:

The following products are known to meet the requirements of this CID:

FSCM	Manufacturer	Model	NSN
50905	BIANCHI	99A-RH-P	1095-01-211-7962
50905	BIANCHI	99A-LH-P	1095-01-212-9200

Military Interests:

Custodian

Air Force - 99

Army - AR

Navy - 0S

Preparing Acitivity

Air Force - 84

Agent

Air Force - 99

Project No. 1095-0230

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:46Z
Check the source to verify that this is the current version before use.