MIL-C-915/5B
1 August 1972
SUPERSEDING
MIL-C-00915/5A(SHIPS)
20 March 1972
MIL-C-915/5
15 March 1968

MILITARY SPECIFICATION SHEET

CABLE, ELECTRICAL, 300 VOLTS, TYPE DLT

(B) This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the cable described herein shall consist of this document and the latest issue of Specification MIL-C-915.

REQUIREMENTS:

Qualification required.

Construction

Insulated Steel Core Member

(B) First - One steel strength member conforming to MIL-W-5424, 7 X 19 stranding, 0.156-inch finished diameter (not preformed).

(B) Second - 60-percent natural rubber insulation (ASTM-D353). Minimum thickness 0.046 inch, to a nominal diameter of 0.262 inch. The insulation shall fill all outer interstices of the steel strands; this may be applied in one or two layers.

Insulated Conductors (Four)

(B) First - Copper conductor. Navy Standard Size 1-1/2(41), coated.

Second - Separator.

(B) Third - 30-percent natural rubber insulation, (ASTM-D353). Nominal thickness 0.031 inch. Standard Identification Code, applied by Method 3.

Assembly

(B) First - The four insulated conductors shall be cabled in a close helix about the steel strength member, with a lay of approximately 0.625-inch, partially embedded in the relatively soft partially vulcanized insulation of the steel core member.

(B) Second - Synthetic rubber filler, integral with an 0.031-inch nominal thickness for an insulating belt over the assembly.

(B) Third - Reinforcement under cable jacket.

(B) Fourth - Polychloroprene jacket (black) minimum thickness 0.078 inch, bonded to the insulating belt. The assembled cable shall be vulcanized into a compact unit. The insulating belt shall be removable from the conductors and the conductors shall be separable without damage to the insulation and without destroying the identity of the color code. Manufacturer's identification shall include molded markings on the jacket at intervals not greater than 25 feet, showing cable type, manufacturer's name or identification, and year of manufacture. Maximum overall diameter 0.710-inch.

(B) Denotes changes

FSC 6145

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:05Z
Check the source to verify that this is the current version before use.

EXAMINATION AND TESTS:

	Requirements:
Basic electrical:	
Conductor resistance - Ohms/1000 ft. at 25°C., maximum	17.0
Voltage withstand - Volts, rms, minimum	
Conductor to conductor.	2000
Conductor to ground (strength member and water bath).	2000
Insulation resistance - Megohms/1000 ft., minimum	200
Group A:	
Visual and dimensional	
Group B:	
Physicals (unaged)	
Insulation (conductor) (ASTM-D353)	
Tensile strength - psi, minimum	900
Elongation - Percent, minimum	300
Jacket (cable)	
Tensile strength - psi, minimum	1800
Elongation - Percent, minimum	300
Bending endurance - At 25°C., on 2-inch maximum diameter mandrel, cycles, minimum	1000
Group C:	
Flammability - Inches, maximum	2
(B) Steel strength member	MIL-W-5424
Physicals (aged)	
Insulation (conductor) (ASTM-353)	
Air oven	
Tensile strength - Percent of unaged, minimum	75
Elongation - Percent of unaged, minimum	75
Oxygen pressure	
Tensile strength - Percent of unaged, minimum	65
Elongation - Percent of unaged, minimum	65
Jacket (cable)	
Air pressure heat	
Tensile strength - Percent of unaged, minimum	50
Elongation - Percent of unaged, minimum	50

QUALIFICATION INSPECTION

Qualification inspection shall include basic electrical, all of Groups A, B and C plus stress endurance.

UNIT ORDERING LENGTHS:

The DLT cable shall be delivered in nominal lengths of not less than 600 feet and not more than 630 feet. Except where authorized by the contract or order, not more than 30 percent of the total footage of each lot offered for inspection may be accepted in random lengths of not less than 400 feet, and not more than 420 feet or in random lengths of not less than 200 feet and not more than 210 feet. Combinations thereof of random lengths will be permitted. Other lengths are not suitable for the purpose.

(B) Custodians:
Army - MI
Navy - SH
Air Force - 80

(B) Review activities:
Army - EL, MI, AV
Navy - EC
Air Force - 80

(B) User activities:
Army - ME, MU, WC
Navy - CG

Preparing activity:
Navy - SH
(Project 6145-0609-3)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:05Z
Check the source to verify that this is the current version before use.