MILITARY SPECIFICATION

CABLE AND CORD, ELECTRICAL,
FOR SHIPBOARD USE,
GENERAL SPECIFICATION FOR

This interim amendment is approved for use within the Naval Sea Systems Command, with Military Specification MIL-C-915F dated 18 June 1985.

PAGE 1

1.2.1: Delete and substitute:

"1.2.1 Watertight, nonflexing service. Cable and cord types for watertight, nonflexing service are as follows:

Unarmored	Armored		
Electronic, communication and instrumentation:			
Type MSPW	---	59 conductors (8 shielded pairs, 3 shielded triads, 34 shielded singles)	
TSP	TSPA	11 and 31 pairs	300 V "

AMSC N/A FSC 6145
DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:56Z
Check the source to verify that this is the current version before use.

1.2.3: Delete and substitute:

"1.2.3 Non-watertight, nonflexing service. Cable and cord types for non-watertight, non-flexing service are as follows:

	Unarmored	Armored	
Electronic, communication and instrumentation:			
Type MSP	---		59 conductors (8 shielded pairs, 3 shielded triads, 34 shielded singles)
1PR-A20E	---		One twisted pair
1PR-16	---		One twisted pair
7PR-16	---		Seven twisted pairs
2SPR-16	---		Two shielded twisted pairs
3PR-16	---		Three twisted pairs
1Q-16	---		Twisted quad
1TR-16	---		Twisted triad
7SPR-16S	---		Seven shielded twisted pairs with overall shield
1SPR-16	---		One shielded twisted pair "

Source: https://assist.dla.mil -- Downloaded: 202610-16T11:56Z
Check the source to verify that this is the current version before use.

PAGE 5

1.2.4: Delete and substitute:

"1.2.4 Non-watertight flexing service. Cable and cord types for non-watertight flexing service are as follows:

Power and lighting:

Unarmored	Armored		
Type CVSF	---	Four conductors (3-#3 and 1-#5 AWG)	600 V
DLT	---	Four conductors	300 V
JAS	---	Four conductors (2-#250 and 2-#6 AWG)	600 V
THOF	---	Three conductors, sizes 3 through 600 AWG	600 V
TRF	---	Single conductor	600 V
TRXF	---	Single conductor	125 V

Control:

Type MHOF		Seven through 61 conductors	600 V

Electronic, communication and instrumentation:

Type 5SS	---	Five conductors (4 singles and one shielded single) with overall shield	600 V
DLT	---	Four conductors	300 V "

PAGE 14

Table IV, footnote 1: Add:

"Other strand construction employing the same total number of wires are acceptable if approved by NAVSEA."

Source: https://assist.dla.mil -- Downloaded: 202640-16T11:56Z
Check the source to verify that this is the current version before use.

PAGES 31 and 32

TABLE XIII: Delete and substitute:

"TABLE XIII. Qualification samples and groups.

Qualification test		
Group number	All tests specified in the applicable specification sheet (type and size)	Types comprising the group 1/
1	DLT	DLT
2	TPUM-6	TPUM
3	MCSF-4	MCSF
4	DSS-3	All sizes of DSS, TSS, 7SS, DSWS, 5SS, S2S, FSS, MSP, MSPW, TSP, MWF, 1SWF, and 2SWF.
5	THOF-42	THOF-42
6	CVSF-4	Type and size CVSF-4, JAS-250, THOF-400 and THOF-500.
7	1PR-A20E	1PR-A20E
8	2SPR-16	1PR-16, 7PR-16, 2SPR-16, 3PR-16, 1Q-16, 1TR-16, 7SPR-16S and 1SPR-16.

1/ Includes all sizes and variations of the cable type."

Preparing activity:
Navy - SH
(Project 6145-N326)

☆U.S. GOVERNMENT PRINTING OFFICE: 1988 — 605-036/44547

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:56Z
Check the source to verify that this is the current version before use.