INCH-POUND
MIL-DTL-915/10F
22 August 2002
SUPERSEDING
MIL-C-915/10E
29 September 1989

DETAIL SPECIFICATION SHEET

CABLE, POWER ELECTRICAL, 600 VOLTS, FOR OUTBOARD USE ONLY (NOT FOR INBOARD USE), TYPE MCSF-4

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-915 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

REQUIREMENTS:

Qualification required.

Construction (watertight)

First	-	Two conductors AWG No. 6, class G stranding, and two conductors AWG No. 1, class G stranding. Stranding shall be 7 by 7 for the no. 6 and 7 by 19 or 19 by 7 for the No. l. Strands shall be 0.025-inch nominal diameter drawn copper alloy in accordance with ASTM B 105 alloy 85.
Second	-	A separator tape over each conductor.
Third	-	Synthetic rubber insulation, 0.070-inch nominal wall thickness on all conductors. Color code one black and one white conductor of each size.
Fourth	-	Insulation jacket of clear polyamide in accordance with ASTM D 4066. Nominal wall thickness of 0.003 inch.
Fifth	-	The four conductors (one black and one white of each size) cabled together - maximum length of lay 20 inches. The No. 6 conductors shall be diametrically opposite to each other. Either nonfibrous or a combination of nonfibrous and fibrous fillers may be used to form a firm, well-rounded assembly.
Sixth	-	Binder or combination binder and barrier.
Seventh	-	Reinforced polychloroprene jacket required. Nominal jacket thickness 0.125 inch. Cable surface marking required.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:06Z
Check the source to verify that this is the current version before use.

NOTES: l.Finished cable diameter shall be 1.5-inch
2. Weight of finished cable shall not exceed 1625 pounds per 1000 feet.
3. Fillers and jacket shall be removable without damage to conductor insulation.

EXAMINATION AND TESTS:

	Requirements
Basic electrical:	
Conductor resistance - ohms/l000 feet at 25°C, maximum	
No. 6 AWG (class G) conductor	0.573
No. l AWG (class G) conductor	0.175
Voltage withstand - volts, root mean square, minimum	2500
Insulation resistance – megohms-l000 feet, minimum	1000
Conductor to conductor and conductor to water	1000
Group A:	
Visual and dimensional	No failure
Watertightness - leakage at 25 lbf/in^2, in 6 hours, in^3, maximum	10.0
(Leakage between 10.0 and 12.0 in^3 shall be considered acceptable, at a 10-percent price reduction.)	
Group B:	
Cold bending, cable - at minus 30 ± 2°C; two complete turns around a mandrel having a diameter 10 times specimen diameter	No damage
Tension - under load of 12,000 pounds, minimum	No damage
Physicals (unaged)	
Insulation (conductor)	
Tensile strength - lbf/in^2, minimum	700
Elongation - percent, minimum	300
Jacket (cable)	
Tensile strength - lbf/in^2, minimum	1800
Elongation - percent, minimum	300
Set - inch, minimum	3/8
Drip - at 95 ± 1°C	Zero
Group C:	
Physicals (aged)	
Insulation (conductor)	
Air pressure heat	
Tensile strength - percent of unaged, minimum	50
Elongation - percent of unaged, minimum	50

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:06Z
Check the source to verify that this is the current version before use.

Jacket (cable)
Air oven
Tensile strength - percent of unaged, minimum 50
Elongation- percent of unaged, minimum 50
Hot oil immersion
Tensile strength - percent of unaged, minimum 60
Elongation - percent of unaged, minimum. 60
Permanence of printing (jacket) - cycles, minimum 250
Cable filler removability ..... No failure

QUALIFICATION INSPECTION:

Qualification inspection shall include basic electrical, plus all of groups A, B, and C.

UNIT ORDERING LENGTH:
1590 feet, minimum to 1650 feet, maximum.

PART OR IDENTIFYING NUMBER (PIN): The PIN consists of the letter M, the general specification number along with the specification sheet, and a dash number representing type and size. Refer to MIL-DTL-915 for an example.

M	**915**	**/10-**	**X-X**
Prefix for Military Specification	Specification Number	Specification Sheet Number	Type and Size

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army – MI
Navy – SH

Preparing activity:
Navy - SH
(Project 6145-2317-006)

Review activities:
Army – AR, CR
Navy - CG, EC
DLA - CC

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:06Z
Check the source to verify that this is the current version before use.