INCH-POUND
MIL-DTL-915/6K
22 August 2002
SUPERSEDING
MIL-C-915/6J
29 September 1989

DETAIL SPECIFICATION SHEET

CABLE, POWER ELECTRICAL, 600 VOLTS, FOR OUTBOARD USE ONLY (NOT FOR INB0ARD USE), TYPE THOF

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-915 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

REQUIREMENTS:

Qualification required.

Construction (non-watertight)

First	-	Copper, conductor, uncoated, (see table I for size).
Second	-	Separator.
Third	-	Ethylene propylene rubber insulation. (see table I for wall thickness). Standard identification code applied by method 3 or 4. A colored rubber filled cotton tape may be used.
Fourth	-	Three conductors cabled together with a left-hand lay (see table I for length of lay). Fibrous fillers shall be employed to obtain a firm, well rounded assembly.
Fifth	-	Binder tape applied helically with overlap on multiconductor cables.
Sixth	-	Jacket of polychloroprene. Jacket shall be black. Cable surface marking required.

NOTE: For types SHOF, DHOF, FHOF, and THOF sizes not listed refer to MIL-DTL-24643/3.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:05Z
Check the source to verify that this is the current version before use.

TABLE I. Details.

Type and size	Conductor size		Insulation thickness nominal (inch)	Lay of conductor max (inches)
	Navy standard	AWG		
THOF - 400	400(2052)	500 MCM	.090	30
THOF - 500		(class K)	.090	33

Type and size	Overall diameter		Conductor resistance per 1000 feet (max) (ohms)	Insulation resistance per 1000 feet (min) (megohms)
	Min (inches)	Max (inches)		
THOF - 400	2.680	2.800	.0283	100
THOF - 500	2.920	3.100	.0230	100

EXAMINATION AND TESTS:

Requirements

Basic electrical:

Conductor resistance - ohms/l000 feet at 25°C, maximum ..... (see table I)
Voltage withstand – volts, root mean square, minimum ..... (2500)
Insulation resistance – megohms-1000 feet, minimum
Conductor to conductor ..... (see table I)
Conductor to water ..... (see table I)

Group A:

Visual and dimensional ..... No failure

Group B:

Physicals (unaged)
Insulation (conductor)
Tensile strength - lbf/in^2, minimum 700
Elongation - percent, minimum 250
Jacket (cable)
Polychloroprene:
Tensile strength - lbf/in^2 1800
Elongation - percent, minimum 300
Set - inch, maximum 3/8

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:05Z
Check the source to verify that this is the current version before use.

Group C:
Flammability – inches, maximum 2
Physicals (aged)
Insulation (conductor)
Air oven
Tensile strength - percent of unaged, minimum 75
Elongation - percent of unaged, minimum. 75
Jacket (cable) (polychloroprene)
Air Oven
Tensile strength - percent of unaged, minimum 50
Elongation- percent of unaged, minimum 50
Hot oil immersion
Tensile strength - percent of unaged, minimum 60
Elongation - percent of unaged, minimum. 60
Permanence of printing (jacket) - cycles, minimum 250

QUALIFICATION INSPECTION:

Qualification inspection shall include basic electrical, plus all of groups A, B, and C.

UNIT ORDERING LENGTH:

Type	Size	Feet (nominal)
THOF	400 and 500	500

PART OR IDENTIFYING NUMBER (PIN): The PIN consists of the letter M, the general specification number along with the specification sheet, and a dash number representing type and size. Refer to MIL-DTL-915 for an example.

M	**915**	**/6-**	**X-X**
Prefix for Military Specification	Specification Number	Specification Sheet Number	Type and Size

Custodians:
Army – MI
Navy – SH

Preparing activity:
Navy - SH
(Project 6145-2317-002)

Review activities:
Army – AR, CR
Navy - CG, EC
DLA - CC

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:05Z
Check the source to verify that this is the current version before use.