INCH-POUND
MIL-DTL-915/9F
22 August 2002
SUPERSEDING
MIL-C-915/9E
29 September 1989

DETAIL SPECIFICATION SHEET

CABLE, POWER ELECTRICAL, 600 VOLTS, FOR OUTBOARD USE ONLY (NOT FOR INBOARD USE), TYPE JAS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-915 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

REQUIREMENTS:

Qualification required.

Construction (non-watertight)

Conductor size 250 MCM (two required)

First	-	Copper, conductor, AWG size 250 MCM, class M stranding, uncoated.
Second	-	Separator.
Third	-	Synthetic rubber insulation. Nominal wall thickness 0.070 inch. Standard identification code applied by method 3, if not accomplished under fourth.
Fourth	-	Tape or braid at manufacturer's option. Standard identification code applied by the tape or braid if no accomplished under third.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:06Z
Check the source to verify that this is the current version before use.

Conductor size 12 (two required)

First - Copper conductor, AWG size 12, class K stranding, uncoated.
Second - Separator.
Third - Synthetic rubber insulation. Nominal wall thickness 0.031 inch.
Fourth - Marker braid. Standard identification code applied by method 4.
Fifth - Two conductors cabled with 3.5 to 4.24-inch lay. Fillers shall be used to form a round assembly.

Assembly

First - Two conductors, size 250, laid parallel with the pair of size 12 laid between them. Fillers of synthetic elastomer or polychloroprene shall be used to fill all spaces and to hold the pair well centered. At manufacturer's option, fillers may be integral with the jacket.
Second - Nylon reinforcement over the assembly.
Third - Polychloroprene jacket (black). Nominal wall thickness 0.156 inch.
Fourth - Cable surface marking in addition to standard marker tape.

NOTES: 1. Fillers and jacket shall be readily removable from the completed cable without damage to the insulation on the conductors.
2. When the insulation on size 250 is applied as a "D" shaped section, the centering and circularity requirements shall not apply.

TABLE I. Details.

Type and size	Conductors			Overall diameter oval shape maximum (inches)
	Number	Size AWG	Diameter nominal (inch)	
JAS -250	2 2	12 250 MCM	0.097 0.713	1.260 minor and 2.480 major

EXAMINATION AND TESTS:

Requirements

Basic electrical:

Conductor resistance - ohms/l000 feet at 25°C, maximum
Size 12 ..... 1.65
Size 250 MCM 0.046
Voltage withstand – volts, root mean square, minimum 2000
Insulation resistance – megohms-1000 feet, minimum
Conductor to conductor and conductor to water
Conductor size 12 200
Conductor size 250 MCM 100

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:06Z
Check the source to verify that this is the current version before use.

Group A:
- Visual and dimensional ..... No failure
- Bending endurance – at 25°C, (performed on one specimen from each lot); 14-inch maximum diameter mandrel, flatwise, cycles, minimum 100,000

Group B:
- Physicals (unaged)
  - Insulation (conductor)
    - Tensile strength - lbf/in^2, minimum 600
    - Elongation - percent, minimum 300
  - Jacket (cable)
    - Tensile strength - lbf/in^2, minimum 1800
    - Elongation - percent, minimum 300

Group C:
- Flammability – inches, maximum 2
- Physicals (aged)
  - Insulation (conductor)
    - Air Oven
      - Tensile strength - percent of unaged, minimum 50
      - Elongation - percent of unaged, minimum 50
  - Jacket (cable)
    - Air Oven
      - Tensile strength – lbf/in^2, minimum 50
      - Elongation- percent, minimum 50
    - Hot oil immersion
      - Tensile strength - percent of unaged, minimum 60
      - Elongation - percent of unaged, minimum 60
- Permanence of printing (jacket) - cycles, minimum 250
- Cable filler removability ..... No failure

QUALIFICATION INSPECTION:

Qualification inspection shall include basic electrical, plus all of groups A, B, and C.

UNIT ORDERING LENGTH:

500 feet (nominal)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:06Z
Check the source to verify that this is the current version before use.

PART OR IDENTIFYING NUMBER (PIN): The PIN consists of the letter M, the general specification number along with the specification sheet, and a dash number representing type and size. Refer to MIL-DTL-915 for an example.

M	**915**	**/9-**	**X-X**
Prefix for Military Specification	Specification Number	Specification Sheet Number	Type and Size

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army – MI
Navy – SH

Preparing activity:
Navy - SH
(Project 6145-2317-005)

Review activities:
Army – AR, CR
Navy - CG, EC
DLA - CC

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:06Z
Check the source to verify that this is the current version before use.