[INCH-POUND]

MIL-R-914/2
12 February 1991

MILITARY SPECIFICATION

RESISTOR NETWORK, SURFACE MOUNT,
16-PIN, SMALL OUTLINE,
ESTABLISHED RELIABILITY, STYLE RNSO20

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. The specification covers the detail requirements for style RNSO20 resistor networks. This style is available in characteristics R, V, H, K, and M and all resistance tolerances.

1.2 Part or Identifying Number (PIN) (see 6.4). Resistor networks covered by this specification are identified by a PIN which consists of the basic number of this specification and a coded number. The military PIN is in the following form:




The coded number is derived in accordance with MIL-R-914.

1.2.1 Schematic. The schematic of the resistor network is identified by a single letter in accordance with figure 1. The resistor element $R_{ref}$ is the reference resistor element used in determining the ratio accuracy (when applicable).

2. APPLICABLE DOCUMENTS


2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Benefical comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Laboratory Command, ATTN: SLCET-R-S, Fort Monmouth, NJ 07703-5000, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the of this document or by letter.

AMSC N/A FSC 5905
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.


Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:54Z
Check the source to verify that this is the current version before use.





SCHEMATIC A




SCHEMATIC B




SCHEMATIC C




SCHEMATIC J

FIGURE 1. Schematics.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:54Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

MILITARY

MIL-R-914 - Resistor Networks, Fixed, Film, Surface Mount, Established Reliability, General Specification for.
MIL-R-39032 - Resistors, Packaging of.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-R-914 and as specified herein.

3.2 Design and construction. The resistor networks shall be of the design, construction, and physical dimensions specified on figure 2.

3.3 Power rating. The power ratings for schematics A, B, C, and J shall be as specified in table I.

TABLE I. Power ratings.

| Schematics | Characteristics K and M | | Characteristics R, H, V | |
|---|---|---|---|---|
| | Element (watts) | Network (watts) | Element (watts) | Network (watts) |
| A | 0.16 | 1.2 | 0.060 | 0.48 |
| B | 0.08 | 1.2 | 0.032 | 0.48 |
| C | 0.08 | 1.2 | 0.060 | 0.48 |
| J | 0.08 | 1.2 | ... | ... |

3.4 Power conditioning. The power applied for power conditioning for schematics A, B, C, and J shall be 1.5 times rated power.


3.5 Temperature range. The operating temperature range shall be from -55°C to +125°C.

3.6 Voltage rating. The maximum voltage rating shall be 50 V dc.

3.7 Resistance range. The resistance range shall be 10 ohms to 2.2 megohms.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:54Z
Check the source to verify that this is the current version before use.




| Inches | mm |
|---|---|
| .0030 | 0.076 |
| .005 | 0.13 |
| .010 | 0.25 |
| .0105 | 0.267 |
| .015 | 0.38 |
| .018 | 0.46 |
| .024 | 0.61 |
| .026 | 0.66 |
| .040 | 1.02 |
| .050 | 1.27 |
| .053 | 1.35 |
| .060 | 1.52 |
| .104 | 2.64 |
| .220 | 5.59 |
| .235 | 5.97 |
| .440 | 11.18 |

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.005 (.13 mm) for three place decimals.
4. Pin 1 locator shall be a dot, stripe, notch, or numeral 1 adjacent to pin number 1, in the shaded area.
5. The picturization of the styles above is given as representative of the envelope of the item. Slight deviations from the outline shown, which are contained within the envelope and do not alter the functional aspect of the device are acceptable.

FIGURE 2. Resistor network.



Source: https://assist.dla.mil -- Downloaded: 202610-16T11:54Z
Check the source to verify that this is the current version before use.

3.8 Standard resistance values. The standard resistance values and the resistance designators for the "J" schematic are as specified in table II.

TABLE II. Standard resistance values.

| Resistance designator | R1 (ohms) | R2 (ohms) | Resistance designator | R1 (ohms) | R2 (ohms) |
|---|---|---|---|---|---|
| A001 | 82 | 130 | A010 | 330 | 470 |
| A002 | 120 | 200 | A011 | 330 | 680 |
| A003 | 130 | 210 | A012 | 1.5K | 3.3K |
| A004 | 160 | 260 | A013 | 3K | 6.2K |
| A005 | 180 | 240 | A014 | 180 | 270 |
| A006 | 180 | 390 | A015 | 270 | 270 |
| A007 | 220 | 270 | A016 | 560 | 560 |
| A008 | 220 | 330 | A017 | 560 | 1.2K |
| A009 | 330 | 390 | A018 | 620 | 2.7K |

3.9 Resistance tolerance. Resistors are available in (B) ±0.1 percent, (D) ±0.5 percent, (F) ±1 percent, (G) ±2 percent, and (J) ±5 percent tolerances.

3.10 Termination. Resistors are available in terminations C, F, and J.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-R-914.

4.2 "J" schematic tests. For the tests on "J" schematic, the dc resistance measurements, resistance temperature characteristic measurement, and short time overload application shall be made between each terminal and applicable common terminal without compensation for the shunt circuits to determine the acceptability to section 3 requirements.

5. PACKAGING

5.1 Packaging requirements. The packaging requirements shall be in accordance with MIL-R-39032.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not manatory.)

6.1 Intended use. Resistor networks are used in surface mounting applications where space is a major concern.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1).

c. Complete PIN.

6.3 Soldering. Extreme care should be taken when soldering these resistors. Prolonged exposure to high temperatures can damage these devices.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:54Z
Check the source to verify that this is the current version before use.

6.4 Part or Identifying Number (PIN) (see 1.2). PIN is a new term encompassing terms previously used in specifications such as part number, type designator, identification number, etc.

## CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AR, MI
Navy - AS, OS
Air Force - 17, 85
DLA - ES

User activities:
Army - AT, AV, ME
Navy - CG, MC
Air Force - 19

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5905-1143-2)



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:54Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

## INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

| I RECOMMEND A CHANGE: | 1. DOCUMENT NUMBER<br>MIL-R-914/2 | 2. DOCUMENT DATE (YYMMDD)<br>91/02/12 |
|---|---|---|

3. DOCUMENT TITLE
Resistor Network, Fixed, Film, 16-Pin, Established Reliability, Style RNS020

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

| a. NAME (Last, First, Middle Initial) | b. ORGANIZATION | |
|---|---|---|
| c. ADDRESS (Include Zip Code) | d. TELEPHONE (Include Area Code)<br>(1) Commercial<br>(2) AUTOVON (If applicable) | 7. DATE SUBMITTED (YYMMDD) |

8. PREPARING ACTIVITY

| a. NAME | b. TELEPHONE (Include Area Code)<br>(1) Commercial | (2) AUTOVON |
|---|---|---|
| ADDRESS (Include Zip Code) | IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:<br>Defense Quality and Standardization Office<br>5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 | |

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:54Z
Check the source to verify that this is the current version before use.