INCH-POUND

MIL-L-6363/11
25 September 1992

MILITARY SPECIFICATION SHEET

LAMPS, INCANDESCENT, AIRCRAFT SERVICE, SINGLE CONTACT BAYONET CANDELABRA BASE, G-6 BULB

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-L-6363




FIGURE 1. Configuration and dimensions.

TABLE I. Part or identifying numbers (PIN) and operating characteristics.

Part or Identifying No. (PIN)	Type Per MIL-L-6363	Bulb Finish	Shock Test Level (G's)	Electrical Ratings			Filament Style	MSCD ±25%	Average Rated Lab Life at DC
				Volts (Nom)	Amperes (±10%)	Watts (Max)		Candelas	Hours
M6363/11-1.	I	Clear	50	12.0	.58	8.29	C-2R	6	750
M6363/11-2		Clear		28.0	.30	9.24	C-2F	6	500

AMSC N/A FSC 6240

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:56Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

1. Configuration and dimensions: See figure 1.

2. Finish: Glass globe finish shall be as indicated in table I.

3. Lamp operating characteristics: When operated at rated voltage, lamp operating characteristics shall be as specified in table I.

4. Coating adhesion: Not applicable.

5. High temperature: Applicable for qualification tests only (85°C/185°F).

6. Thermal shock: Applicable for qualification tests only. Use temperatures for Type I lamps.

7. Random vibration: Applicable for qualification tests only. See figure 2 for random vibration curve.

8. Shock: Applicable for qualification tests only. See table I for applicable "g" level.

9. Humidity: Applicable for qualification tests only.

10. Salt spray: Applicable for qualification tests only.

11. Marking: To be determined for marking of production lamps. Pending investigation of marking with military part number (or portion thereof) versus marking with lamp trade number (as is or modified). This requirement will not affect lamp qualification requirements.

12. Interchangeability: These lamps may be similar to, but are not interchangeable with, other commercial or military lamps due to unique aircraft applications and qualification.

NOTES:


1. Dimensions are in inches.

2. Intended use - aircraft instrument, indicator and interior lighting applications.

3. For design feature purposes, this specification sheet takes precedence over acquisition documents referenced herein.

4. Qualification by similarity - M6363/11-2 is required to be fully qualified in accordance with table I of MIL-L-6363. M6363/11-1 and M6363/10-1 may be qualified by similarity and extension of qualification from M6363/11-2. Refer to MIL-L-6363 for conditions and data requirements for extension of qualification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:56Z
Check the source to verify that this is the current version before use.



Freq Hz	Vibration Level PSD (G^2/Hz)	Upper Limit (+3 DB) PSD (G^2/Hz)	Lower Limit (-3 DB) PSD (G^2/Hz)
5	0.005	0.01	0.0025
10	0.02	0.04	0.01
20	0.08	0.16	0.04
1000	0.08	0.16	0.04
2000	0.04	0.08	0.02

FIGURE 2. Random vibration curve for G-6 lamps.

Source: https://assist.dla.mil Downloaded: 2026-10-17T06:56Z
Check the source to verify that this is the current version before use.

Custodians:
Army - AV
Air Force - 99
Navy - AS

Review activities:
Army -
Air Force - 82, 11
Navy - MC, SH
DLA - GS

Preparing activity:
Navy - AS

(Project 6240-1009-11)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:56Z
Check the source to verify that this is the current version before use.