MILITARY SPECIFICATION SHEET

LAMPS, INCANDESCENT, AIRCRAFT SERVICE, SINGLE CONTACT
MINIATURE BAYONET BASE, T-4-1/2 BULB

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation: MIL-L-6363




FIGURE 1. Configuration and dimensions.

TABLE I. Part or identifying numbers (PIN) and operating characteristics.

Part or Identifying No. (PIN) 1/	Type Per MIL-L-6363	Bulb Finish	Shock Test Level (G's)	Electrical Ratings			Filament Style	MSCP ±25%	Average Rated Lab. Life at DC
				Volts (Nom)	Amperes (±10%)	Watts (Max)		Candelas	Hours
M6363/14-1X	I	Clear	90	28.0	.30	9.24	C-2F	6	500

1/ Gas filled lamp.

AMSC N/A FSC 6240

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:57Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

1. Configuration and dimensions: See figure 1.

2. Finish: Glass globe finish shall be as indicated in table I.

3. Lamp operating characteristics: When operated at rated voltageds, the lamp operating characteristics shall be as specified in table I.

4. Coating adhesion: Not applicable.

5. High temperature: Applicable for qualification tests only (85°C/185°F).

6. Thermal shock: Applicable for qualification tests only - Use temperatures for Type I lamps.

7. Random vibration: Applicable for qualification tests only - See figure 2 for random vibration curve.


8. Shock: Applicable for qualification tests only - See table I for applicable "g" level.

9. Humidity: Applicable for qualification tests only.

10. Salt spray: Applicable for qualification tests only.


11. Marking. Production lamps qualified to MIL-L-6363 and listed on QPL-6363 shall be marked in accordance with ANSI/NEMA C78.390 and as supplemented herein. ANSI/NEMA C78.390 authorized suffix letters shall be supplemented with the letter "Q" (MIL-L-6363 QPL item). The letter "Q" shall be incorporated into the method of designation in accordance with the following example:

EXAMPLE



12. Interchangeability: These lamps may be similar to, but are not interchangeable with, other commercial or military lamps due to unique aircraft applications and qualification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:57Z
Check the source to verify that this is the current version before use.



FREQ. HZ.	VIBRATION LEVEL PSD (G^2/HZ)	UPPER LIMIT (+3 DB) PSD (G^2/HZ)	LOWER LIMIT (-3 DB) PSD (G2/HZ)
5	0.005	0.01	0.0025
10	0.02	0.04	0.01
20	0.08	0.16	0.04
1000	0.08	0.16	0.04
2000	0.04	0.08	0.02

FIGURE 2. Random vibration curve for T-4-1/2 lamps.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:57Z
Check the source to verify that this is the current version before use.

NOTES:

1. Dimensions are in inches.
2. Intended use - aircraft instrument, indicator and interior cockpit light assemblies conforming to MS25027.
3. For design feature purposes, this specification takes precedence over procurement documents referenced herein.
4. Qualification by similarity - Lamp M6363/14-1X is required to be fully qualified in accordance with Table I of MIL-L-6363. Refer to MIL-L-6363 for conditions and data requirements for qualification.

Custodians:
Army - AV
Air Force - 99

Review activities:
Army -
Air Force - 82, 11
Navy - MC, SH
DLA - GS

Preparing activity:
(Navy - AS)
(Project No. 6240-1009-14)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:57Z
Check the source to verify that this is the current version before use.