INCH-POUND

MIL-DTL-6363/3D
30 September 1997
SUPERSEDING
MIL-L-6363/3C
5 November 1990

DETAIL SPECIFICATION SHEET

LAMPS, INCANDESCENT, AIRCRAFT USE, SINGLE CONTACT BAYONET CANDELABRA BASE, REFLECTOR TYPE

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification and MIL-DTL-6363.




FIGURE 1. Configuration and dimensions.

See NOTES on the next page.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:55Z
Check the source to verify that this is the current version before use.

NOTES:
1. Dimensions are in inches. Unless otherwise specified, tolerances: decimals ±0.010 inch, angles ±0.5°.
2. Intended use - aircraft navigational light assemblies.
3. For design feature purposes, this specification takes precedence over procurement documents referenced herein.

REQUIREMENTS:

1. Configuration and dimensions: See figure 1.

2. Finish: Glass globe shall be clear except where reflector surface is required.

3. Lamp operating characteristics: When operating at rated voltage (DC), the lamp operating characteristics shall be as specified in table I.

TABLE I. Part numbers and operating characteristics.

Military Part Number	Type Per MIL-DTL-6363	Temp Rating Continuous Operation 1/		Shock Test Level (G's)	Electrical Ratings			Average Rated Lab Life at DC Hours
		°C	°F		Volts (Nom)	Amperes (Max)	Watts (Max)	
M6363/3-1	II	113	235	90	28.0	1.55	43	300
M6363/3-2	II	113	235	135	6.2	6.93	43	300

1/ For 70 percent of average rated lab life.

4. Light distribution: See tables II and III.

TABLE II. Light distribution (horizontal plane).

LIGHT DISTRIBUTION IN HORIZONTAL PLANE CONTAINING FLIGHT AXIS (0°) AND PASSING THROUGH LIGHT CENTER AND CENTER OF INDEXING PINS

Beam Candlepower Candelas (Minimum)	Angle of Distribution
300	0° forward to 30° outboard
150	30° outboard to 40° outboard
120	40° outboard to 50° outboard
50	50° outboard to 100° outboard

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:55Z
Check the source to verify that this is the current version before use.

TABLE III. Light distribution (vertical plane).

LIGHT DISTRIBUTION IN VERTICAL PLANE CONTAINING FLIGHT AXIS (0°) AND PASSING THROUGH LIGHT CENTER AND PERPENDICULAR TO HORIZONTAL PLANE ABOVE

Beam Candlepower Candelas (Minimum)	Angle of Distribution
300	0° to 20° above and below flight axis
60	20° to 40° above and below flight axis
30	40° to 85° above and below flight axis

5. Coating adhesion: Applicable.

6. High temperature: See table I for applicable high temperature rating.

7. Thermal shock: See table I for applicable high temperature rating.

8. Random vibration: See figure 2 for 28.0v lamp and figure 3 for 6.2v lamp random vibration curves.

9. Shock: See table I for applicable “g” level.

10. Humidity: Applicable.

11. Salt spray: Applicable

12. Inspection lot vibration screening: Sample size and acceptance level as specified by the procuring activity.

13. Marking: Lamps shall be marked with the applicable military part number from table I, voltage rating, manufacturing lot code, and the manufacturer’s name, CAGE code, abbreviation or trademark. Other military or commercial lamp numbers shall not be marked on the lamps.

14. Interchangeability: These lamps may be similar to, but are not interchangeable with, other commercial or military lamps due to unique aircraft applications and qualification.

There are no technical changes in this revision.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:55Z
Check the source to verify that this is the current version before use.




FIGURE 2. Random vibration curve for 28v lamps.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:55Z
Check the source to verify that this is the current version before use.




FIGURE 3. Random vibration curve for 6.2v lamps.

CONCLUDING MATERIAL

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:55Z
Check the source to verify that this is the current version before use.

Custodians:
Army - AV
Navy - AS
Air Force - 99

Review activities:
Navy - MC, SH
Air Force - 11, 82
DLA - GS

Preparing activity
Navy - AS
(Project 6240-1441-03)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:55Z
Check the source to verify that this is the current version before use.