INCH-POUND

MIL-L-6363/6
13 September 1993

MILITARY SPECIFICATION SHEET

LAMPS, INCANDESCENT, AIRCRAFT SERVICE, SINGLE CONTACT
SUBMIDGET FLANGED BASE T-1 BULB

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation: MIL-L-6363




FIGURE 1. Configuration and dimensions.

AMSC N/A FSC 6240
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:55Z
Check the source to verify that this is the current version before use.

TABLE I. Part or identifying numbers (PIN) and operating characteristics.

Part or Identifying No. (PIN) (SEE REQT 2)	Type Per MIL-L-6363	Bulb Finish	Shock Test Level (G's)	Electrical Ratings			Filament Style	MSCD	Average Rated Lab Life at DC
				Volts (Nom)	Amperes (+10%)	Watts (Max)		Candelas	Hours
M6363/6-1	I	Clear	50	5.0	.06	.33	C-2R	.03+25%	30,000
M6363/6-1 AS15		Clear		5.0	.06	.33	C-2R	.03+15%	30,000
M6363/6-2		Clear		5.0	.06	.33	C-2R	.05+25%	20,000
M6363/6-2 AS15		Clear		5.0	.06	.33	C-2R	.05+15%	20,000
M6363/6-3		Clear		5.0	.06	.33	C-2R	.15+25%	2,000
M6363/6-3 AS15		Clear		5.0	.06	.33	C-2R	.15+15%	2,000
M6363/6-4		Clear		5.0	.115	.63	C-2R	.15+25%	20,000
M6363/6-4 AS15		Clear		5.0	.115	.63	C-2R	.15+15%	20,000
M6363/6-5		Clear		28	.024	.74	CC-2F	.13+25%	4,000
M6363/6-5 AS15		Clear		28	.024	.74	CC-2F	.13+15%	4,000

REQUIREMENTS

1. Configuration and dimensions: See figure 1.

2. Construction:

   a. Standard lamp construction shall include a side weld or solder bead and solder bead bottom contact.

   b. Where required for greater reliability and added resistance to corrosion and internal shorting, solderless construction is available as an option by the addition of a dash and suffix letter "S" to the part identification number in table I.

Example

M6363/6-1-S

When specified, solderless construction shall include a side weld and nickel plated brass bottom contact.

   c. Insulator shall be color coded as follows to identify voltage rating of lamps.

5.0 Volt - Green
28 volt - Red

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:55Z
Check the source to verify that this is the current version before use.

3. Finish: Glass globe finish shall be as indicated in table I.

4. Lamp operating characteristics: When operated at rated voltage, the lamp operating characteristics shall be as specified in table I.

5. Where indicated by suffix "AS15" in the part number, lamps shall be aged for a minimum of 10 hours at rated voltage and selected for 15% tolerance on MSCD as indicated in table I.

6. MSCD at 1000 hours shall not be less than 80% of initial MSCD when measured at rated voltage.

7. Coating adhesion: Not applicable.

8. High temperature: Applicable for qualification tests only (85°C/185°F).

9. Thermal shock: Applicable for qualification tests only - Use temperatures for Type I lamps.

10. Random vibration: Applicable for qualification tests only - See figure 2 for random vibration curve.

11. Shock: Applicable for qualification tests only - See table I for applicable "g" level.


12. Humidity: Applicable for qualification tests only.

13. Salt spray: Applicable for qualification tests only.


14. Marking. Production lamps qualified to MIL-L-6363 and listed on QPL-6363 shall be marked in accordance with ANSI/NEMA C78.390 and as supplemented herein. ANSI/NEMA C78.390 authorized suffix letters shall be supplemented with the letter "Q" (MIL-L-6363 QPL item). The letter "Q" shall be incorporated into the method of designation in accordance with the preferred marking below.

EXAMPLE

Preferred Marking



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:55Z
Check the source to verify that this is the current version before use.



Freq Hz	Vibration Level PSD (G^2/Hz)	Upper Limit (+3 DB) PSD (G^2/Hz)	Lower Limit (-3 DB) PSD (G^2/Hz)
5	0.005	0.01	0.0025
10	0.02	0.04	0.01
20	0.08	0.16	0.04
1000	0.08	0.16	0.04
2000	0.04	0.08	0.02

FIGURE 2. Random vibration curve for T-1 lamps.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:55Z
Check the source to verify that this is the current version before use.

Alternate Acceptable Marking.

Where marking area is limited by base size, length or size of marking, or where pre-marked bases are used, the letter "Q" may be marked on any convenient space on the base.

15. Interchangeability: These lamps may be similar to, but are not interchangeable with, other commercial or military lamps due to unique aircraft applications and qualification.

NOTES:

1. Dimensions are in inches.
2. Intended use - aircraft instrument and panel light assemblies.
3. For design feature purpose , this specification takes precedence over procurement documents referenced herein.

4. Qualification by similarity - Lamp M6363/6-5AS15 is required to be fully qualified in accordance with Table I of MIL-L-6363. Lamp M6363/6-4AS15 is required to be qualified in accordance with Table II of MIL-L-6363. All other basic lamps (MSCD ±25%) and "AS" designated lamps may be granted qualification by similarity and extension of qualification from the qualified lamps with no additional testing. Refer to MIL-L-6363 for conditions and data required for qualification.

Custodians:
Army - AV
Air Force - 99
Navy - AS

Review activities:
Army -
Air Force - 82, 11
Navy - MC, SH
DLA - GS

Preparing activity:
(Navy - AS)
(Project No. 6240-1009-6)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:55Z
Check the source to verify that this is the current version before use.