MILITARY SPECIFICATION

TIEDOWN ASSEMBLY, CARGO, AIRDROP, TYPE A-1

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of restraint/release system for use in rigging the type A-22 airdrop container loads in cargo aircraft.

2. APPLICABLE DOCUMENTS

* 2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

T-T-871	-	Twine, Cotton, Wrapping
PPP-B-601	-	Boxes, Wood, Cleated Plywood
PPP-B-636	-	Box, Fiberboard
PPP-T- 76	-	Tape, Pressure-Sensitive Adhesive Paper, (For Carton Sealing)

MILITARY

MIL-B-121	-	Barrier Material, Greaseproofed, Waterproofed, Flexible

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:53Z
Check the source to verify that this is the current version before use.

MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized and Containerized Unit Loads 40" x 80" Pallets, Skids, Runners or Pallet-Type Base

DRAWING

U. S. Air Force

51B6169 - Tiedown Assembly, Aerial Delivery Container, 2200-Lb Capacity, Type A-1

(Copies of specifications, standards and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

(Figure 1 is a miniature reproduction of the referenced drawing and is attached for information only.)

2.2 The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issues in effect on date of invitation for bids or request for proposal shall apply:

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC.

National Motor Freight Classification

(Application for copies should be addressed to American Trucking Associations, Attn: Tariff Order Section, 1616 P Street, N.W., Washington, D. C. 20036.)

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 202 Union Station, 516 W. Jackson Blvd., Chicago, Illinois 60606.)

3. REQUIREMENTS

* 3.1 Materials and construction.- Materials and construction details shall conform to the requirements of Drawing 51B6169, to the requirements of subsidiary specifications, standards and drawings applicable thereto, and as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:53Z
Check the source to verify that this is the current version before use.

* 3.1.1 Stitches and stitchings.- Thread breaks and bobbin runouts or two or more consecutive skipped stitches shall be restitched not less than 1 inch over each end of the defect. Runoffs shall be restitched to conform to the required stitching pattern. Ends of stitching (except for 3.1.1.1) shall be backstitched not less than 1/2 inch except where ends are turned under in a hem or held down by other stitching.

3.1.1.1 Stitching, automatic machinery.- Stitching patterns produced by automatic machines may be utilized in lieu of those specified, providing seam strength efficiency and function are equal to, or better than, the specified pattern and upon approval by the procuring activity. Certification of equivalency, supported by engineering data, may be required.

* 3.2 Marking.- Identification marking of each component shall be in accordance with the applicable drawing.

3.3 Workmanship.- The workmanship shall conform to the quality established by this specification.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Component and material inspection.- In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings and standards, unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

* 4.3 In-process inspection.- Inspection shall be performed at appropriate stages of fabrication to determine conformance to the requirements of this specification. The Government reserves the right to exclude from consideration for acceptance any materials for which in-process inspection has indicated nonconformance.

* 4.4 Inspection.- Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:53Z
Check the source to verify that this is the current version before use.

* 4.4.1 Inspection levels and acceptable quality levels (AQLs).- Inspection levels and AQLs, expressed in defects per hundred units, shall be as follows:

	Inspection level	AQL
For examination in 4.4.1.1	II	0.15 Major 4.0 Total
For examination in 4.4.1.2	S-3	4.0 One class
For examination in 4.4.1.3	S-2	6.5 One class
For examination in 4.4.1.4	S-1	6.5 One class

* 4.4.1.1 Visual examination of end item characteristics.- The sample unit for this examination shall be one complete tiedown assembly. Characteristics to be examined and defects to be scored shall be as set forth below.

Examine	Defect	Classification Major	Minor
Webbing	Not specified type or class	X	
	Color not as specified		X
	Cut, hole, tear, abrasion, or weak area	X	
	Ends, not seared or wax dipped as specified		X
	Edge beaded or corded		X
Thread	Not specified type or size	X	
	Not specified color		X
Hardware	Sharp, burred, or split edges	X	
	Component fractured, malformed or bent	X	
	Any area of rust or corrosion	X	
	Coating blistered, peeling, flaking or otherwise not adherent	X	
	Not material specified	X	
Construction and workmanship	Any component missing, misaligned, or not joined as specified	X	
	Grease, oil, dirt or other foreign matter on surface of webbing		X
Stitches and stitching	Wrong type	X	
	Any open seam	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:53Z
Check the source to verify that this is the current version before use.

Examine		Defect	Classification Major	Minor
Stitches and stitching (cont'd)	NOTE:	A seam will be classified as open when one or more stitches joining a seam are broken or two or more consecutive skipped stitches occur. Repairs of open seams shall not be scored as defects.		
		One stitch per inch less than or more than the minimum or maximum specified		X
		Two or more stitches per inch less than or more than the minimum or maximum specified	X	
		Stitching ends backstitched less than 1/2 inch (except where turned under a hem or held down by other stitching)		X
		Needle chews or holes	X	
		Thread ends not trimmed		X
		Any missing or incomplete row of stitching	X	
		Tension loose, resulting in a loose seam or tension tight, resulting in breaking of thread when normal tension is applied	X	
		Tension loose, resulting in a loose top or bobbin thread or tension tight, resulting in puckering		X
		Runoff at edge and not restitched		X
		Thread breaks and skips not overstitched as specified		X
Marking		Missing, incorrect, illegible, wrong color, improper location or otherwise not as specified		X

* 4.4.1.2 Dimensional examination.- The sample unit shall be one complete tiedown assembly. The examination shall be made to determine compliance with overall length and stitching location dimensions specified for each component.

4.4.1.3 Examination of preparation for delivery.- An examination shall be made to determine compliance with the applicable packaging, packing, and marking

Source: https://assist.dla.mil -- Downloaded: 2020-10-17T00:53Z
Check the source to verify that this is the current version before use.

requirements. The lot shall be the number of containers offered for inspection at one time. The sample unit shall be one container fully prepared for delivery, except that it need not be sealed. Examination for closure defects shall be made of containers fully prepared for delivery. Characteristics to be examined and the defects applicable thereto shall be as specified below:

Examine	Defect
Marking (interior package and exterior container)	Omitted; incorrect, illegible; of improper size, location, sequence, improper method of application, i.e., not on shipping tag or paper label (when applicable)
Materials	Component missing, damaged, defective, or not as specified
Workmanship	Improper packaging or closure of interior packages, improper closure of exterior container, loose strapping or tape banding, bulging or distortion of containers
Contents (interior package and exterior container)	Number per interior package or exterior container not as specified

* 4.4.1.4 Examination for palletization.- An examination shall be made to determine compliance with the palletization requirements of section 5. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully prepared for delivery. The lot size shall be the number of palletized unit loads in the end item inspection lot.

Examine	Defect
Finished dimension	Length, width, or height exceeds specified maximum requirement
Palletization	Not as specified Pallet pattern not as specified Interlocking of loads not as specified Load not bonded with required straps as specified

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:53Z
Check the source to verify that this is the current version before use.

Examine	Defect
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible, of improper size, location, sequence or method of application

5. PREPARATION FOR DELIVERY

5.1 Packaging.- Packaging shall be level A or C, as specified (see 6.2).

* 5.1.1 Level A.- The release knives on each release line shall be completely wrapped with barrier material conforming to type II, grade A, class 1 or 2 of MIL-B-121. The wrap shall extend onto the webbing and be secured with 1-inch minimum width tape conforming to PPP-T-76. The release line shall then be tightly coiled and securely tied in not less than two places with twine conforming to type I or II, 8-ply of T-T-871. Each of the eight remaining components of the tie down assembly shall be tightly coiled or folded and individually secured with the specified twine and then be placed on top of the coiled release line with edges contacting. The complete tie down assembly shall be packaged in a snug-fitting fiberboard box conforming to style FOL (end-opening), grade W6c of PPP-B-636. Each box shall be closed by means of tape in accordance with the appendix of PPP-B-636.

* 5.1.2 Level C.- Each tiedown assembly shall be packaged to afford adequate protection against physical damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

5.2 Packing.- Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A.- Four tiedown assemblies, packaged as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to style RSC, grade V2s of PPP-B-636; or overseas type, style A or J, type 2 load of PPP-B-601, as specified (see 6.2). Each shipping container shall be closed and reinforced in accordance with the appendix of the applicable container specification.

5.2.2 Level B.- Four tiedown assemblies, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:53Z
Check the source to verify that this is the current version before use.

style RSC, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.1 When specified (see 6.2), the fiberboard shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix of the container specification.

5.2.3 Level C.- Tiedown assemblies, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Palletization.- Unless otherwise specified (see 6.2), tiedown assemblies, packed as specified in 5.2, shall be palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

5.4 Marking.- In addition to any special marking required by the contract or order, interior packages, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use.- The type A-1 airdrop cargo tiedown assembly covered by this specification is intended for use as a restraint and release system when dropping the standard type A-22 container from C-119 and C-130 aircraft.

6.2 Ordering data.- Procurement documents should specify the following:

a. Title, number and date of this specification.
b. Item Federal Stock Number.
c. Item quantity required.
d. Selection of applicable level of packaging and packing (see 5.1 and 5.2).
e. Type of shipping container desired for level A packing (see 5.2.1).
f. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
g. When palletization is not required (see 5.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:53Z
Check the source to verify that this is the current version before use.

* 6.3 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever from any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - AS
Air Force - 82

Review activities:

Army - AV
Air Force - 11

User activity:

Navy - MC

Preparing activity:

Army - GL

Project No. 1670-0384

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:53Z
Check the source to verify that this is the current version before use.

	COMPONENTS	ASSEMBLY PART NO. 5186169-6	ASSEMBLY PART NO. 5186169-7
	LINE-RELEASE, AIR DELIVERY CONTAINER — P/N 51D6146-6	1	
	LINE-RELEASE, AIR DELIVERY CONTAINER — P/N 51D6146-7		1
	WEB, TIE DOWN, AIR DELIVERY CONTAINER — P/N 51D6147	2	2
	STRAP, ADAPTER, AIR DELIVERY CONTAINER, 60"LG — P/N 51CG109-1	2	2
	STRAP, ADAPTER, AIR DELIVERY CONTAINER, 120"LG — P/N 51CG109-2	2	2
*	WEBBING, NYLON, TYPE I, CLASS R, OD-7, 60"LG, MIL-W-27265	2	2
		NO. OF COMPONENTS REQD	

NOTE:
PARTS MARKED THUS * REQUIRE NO IDENTIFICATION MARKING

THIS FIGURE IS A MINIATURE COPY OF USAF DWG 5186169. THIS COPY IS FOR REFERENCE ONLY. THE DRAWING REFERENCED IN PARAGRAPH 2.1 GOVERNS.

FIGURE-1

TIE DOWN ASSEMBLY
AERIAL DELIVERY CONTAINER
2200 LB CAPACITY TYPE A-1

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:53Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION
Tiedown Assembly, Cargo, Airdrop, Type A-1 MIL-T-6361D

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?
   ☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:53Z
Check the source to verify that this is the current version before use.