INACTIVE FOR NEW DESIGN

MIL-T-6368(USAF)
AMENDMENT 3
13 APRIL 1983
Superseding
AMENDMENT 2
6 June 1956

MILITARY SPECIFICATION

TRANSMITTER, FUEL FLOW, TOTALIZING, TYPE H-1A

INACTIVE FOR NEW DESIGN AFTER 4 JUN 1971.

This amendment forms a part of Military Specification MIL-T-6368 dated 14 November 1950.

PAGE 1

2.1.1: Add "Specifications, FEDERAL" and the following:

"L-P-378	Plastic Sheet And Strip, Thin Gauge, Polyolefin
PPP-B-636	Box, Shipping, Fiberboard"

Under "Specifications, MILITARY" delete "MIL-D-5028" and "MIL-F-5616". Add the following:

"MIL-P-116	Preservation-packaging, Methods Of
DOD-D-1000	Drawings, Engineering And Associated Lists
MIL-S-7742	Screw Threads, Standard, Aeronautical
MIL-A-8625	Anodic Coatings, For Aluminum And Aluminum Alloys
MIL-P-26514	Polyurethane Foam, Rigid Or Flexible For Packaging"

Delete reference to "AN-QQ-696, AN-M-13, AN-S-126" and "32466".

Add the following boxed paragraph to bottom of page:

Beneficial comments (recommendations, additions, deletions) any pertinent data which may be of use in improving this document should be addressed to: Oklahoma City Air Logistics Center/MMEDO, Tinker AFB OK 73145 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

PAGE 2

2.1.2: Delete referenced document and substitute the following:

"405	Storage Life - Aeronautical Articles"

2.1.3: Delete "AND10066".

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:57Z
Check the source to verify that this is the current version before use.

Add new paragraph "2.1.4" as follows

"2.1.4 Military Standards

MIL-STD-129	Marking For Shipment And Storage
MIL-STD-130	Identification Marking of U.S. Military Property
MIL-STD-143	Standards And Specifications, Order Of Precedence For The Selection Of
MIL-STD-794	Parts And Equipment, Procedures For Packaging And Packing Of
MIL-STD-831	Test Reports, Preparation Of
MS 33678	Connector, Receptacle, Electric, Integral Mounting"

Delete the source paragraph and substitute the following:

"(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)"

3.1.1, line 5: Delete "Bulletin No. 143" and substitute "MIL-STD-143".

Add new paragraph "3.1.4" and "3.1.5" as follows:

"3.1.4 Reclaimed materials. The use of reclaimed materials shall be encouraged to the maximum extent possible without jeopardizing the intended end use of the item.

3.1.5 First article. This specification makes provisions for first article testing."

PAGE 3

3.2, line 3 and 4: Delete "aviation kerosene in accordance with Specification MIL-F-5616 and".

3.3, line 5: Delete "MIL-D-5028" and substitute "DOD-D-1000".

PAGE 6

3.6: Delete "AND10066A-12S-3P" and substitute "MS33678-12S-3P".

3.10: Delete "AN-S-126" and substitute "MIL-S-7742".

3.11.1: Delete "AN-QQ-A-696" and substitute "MIL-A-8625".

Delete "3.12, 3.12.1, 3.12.2, 3.12.3 and 3.12.4. Substitute the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:57Z
Check the source to verify that this is the current version before use.

"3.12 Identification of product. Equipment, assemblies and parts shall be marked for identification in accordance with MIL-STD-130."

PAGE 8

4.1.1: Delete and substitute the following:

"4.1.1 First article tests. First article tests are those tests accomplished on a sample representative of the production transmitter to determine that the production transmitter meets the requirements of this specification. (See 4.3)"

PAGE 9

Delete "4.3" through "4.3.3" and substitute the following:

"4.3 First article testing.

4.3.1 First article test sample tested by the contractor. The contractor shall subject two transmitters to the first article test specified in 4.4.

4.3.1.1 First article test report. After the contractor completes the first article tests, he shall prepare a first article test report according to MIL-STD-831 and furnish three complete copies of the report to the procuring activity.

4.3.2 First article test sample for the procuring activity. Along with the first article test report, the contractor shall submit sample(s) to the procuring activity who will use it (them).

a. for a review of the mechanical construction of the product.

b. to perform any tests, included in the specification, after reviewing the contractor's test report.

4.3.3 First article tests. The first article tests shall consist of all tests specified herein."

Delete 4.4.1 in its entirety.

PAGE 10

4.4.2.5: Delete paragraph in its entirety and substitute the following:

WARNING

The following involve dangerous voltage which may cause severe shock or injury. Avoid contact with energized components. Remove rings, watches and other metallic objects which may cause shock or burn hazards.

"4.4.2.5 Dielectric strength. The transmitter shall be subjected to a test voltage of 1,000V (rms) plus twice the working voltage at commercial frequency for a period of 1 minute. The test voltage shall be applied between the terminals (shorted together) and ground at sea-level atmospheric pressure."

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:57Z
Check the source to verify that this is the current version before use.

PAGE 12

4.4.4.3, lines 2 and 3: Delete "+71 ± 2°C" and substitute +110 ± 2°C" in both places. In line 2, delete "15" and substitute "24".

PAGE 13

4.5, lines 2 and 3: Delete "and/" in both places.

Add new paragraph as follows:

"4.6 Inspection and test. Tests of methods of preservation and packaging shall be accomplished in accordance with Section 4 of MIL-P-116 to insure compliance with Section 5 of this specification."

Delete paragraphs 5. through 5.3.1 in their entirety and substitute the following new paragraphs:

"5. PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Cleaning. Transmitters shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying. Transmitters shall be dried in accordance with process D-4 of MIL-P-116.

5.1.1.3 Preservation application. Not applicable.

5.1.1.4 Unit packaging. Unless otherwise specified by the procuring activity, each fuel flow transmitter shall be packaged in quantity unit packs of one each in accordance with method IC-1 of MIL-P-116. Each transmitter shall be wrapped with L-P-378 and overboxed in PPP-B-636 carton. Carton shall be large enough to allow for application of sufficient cushioning material, MIL-P-26514, between container and bag, of a type, density, and thickness to insure shock transmission does not exceed peak values in G's established for the indicator, when completed packs are subjected to the rough handling drop tests of MIL-P-116.

5.1.2 Level C. Transmitters shall be clean, dry and individually packaged in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from supply source to the first receiving activity.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:57Z
Check the source to verify that this is the current version before use.

5.2.1 Level A. Transmitters packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-636, weather-resistent class, unless otherwise specified by the procuring activity. Insofar as practical, exterior shipping container shall be of uniform shape, size, and of minimum tare and cube, consistant with the protection required. Table II of MIL-STD-794 applies for Army use.

5.2.2 Level B. Transmitters packaged as specified in 5.1.1 shall be packed in domestic class exterior shipping containers conforming to PPP-B-636. Other requirements as specified in 5.2.1 above are applicable.

5.2.3 Level C. Packing shall be applied which affords adequate protection during domestic shipment from the supply source to the first domestic receiving activity for immediate use. This level shall conform to applicable carrier rules and regulations and may be the contractor's commercial practice provided the latter meets the requirements of this level.

5.3 Marking of shipments. Interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129. The nomenclature shall be as follows:

Transmitter, Fuel Flow, Totalizing, 0-1500 GPH, Type H-1A

5.3.1 Reinspection date marking. Reinspection marking shall be in accordance with ANA Bulletin 405."

PAGE 14

6.1: Delete paragraph and substitute the following:

"6.1 Ordering data. Procurement documents should specify the following:

a. Level of packaging and packing desired

b. That invitations to bids, contract or purchase order, will specify that a minimum, of two transmitters will be required as first article samples to be subjected to the first article tests by the contractor to determine compliance with requirements of this specification, and that two transmitters will be required as first article samples to be submitted to the procuring activity."

6.2, lines 9 through 11: Delete "Commanding General, Air Material Command, Wright-Patterson Air Force Base, Dayton, Ohio, attention: MCREXE" and substitute "Oklahoma City Air Logistics Center/MMEDO, Tinker AFB OK 73145".

Custodian:
Air Force-99

Preparing Activity:
Air Force-71

Project Number:
6620-F164

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:57Z
Check the source to verify that this is the current version before use.