MIL-B-46367A(MU)
15 February 1974
SUPERSEDING
MIL-B-46367(MU)
28 February 1963

MILITARY SPECIFICATION
BANDOLEER, M2

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope.-This specification covers one type of bandoleer intended to hold 7.62mm ammunition in 5RD clips for use in 7.62mm rifle.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on the date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

Federal

PPP-B-1055	- Barrier Material, Waterproofed, Flexible
PPP-B-636	- Boxes, Fiberboard

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-129	- Marking for Shipment and Storage

DRAWINGS

Armament Command

F8594723	- Bandoleer, M2, Ctgs, NATO, 7.62MM
D8594724	- Packing and Marking, Bandoleer, M2, Ctgs., NATO, 7.62MM

FSC 1305

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:43Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General.-The bandoleer shall comply with the requirements specified on Drawing F8594723, referenced specifications and the following:

3.2 First article sample.-Requirements for submission of first article sample by the contractor shall be as specified in the contract.

3.3 Strength of material.-The bandoleer loaded with a weight of 4085 plus or minus 10 grains per pocket shall not show any ripping of stitches or material when subjected to a 12 inch free drop with center of strap supporting bandoleer upon completion of drop.

3.4 Workmanship.-The bandoleers shall be free of rips, tears, irregular sewing, and other defects.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality Assurance terms and definitions.-Reference shall be made to MIL-STD-109 to define quality assurance terms used.

4.2 First article sample.

4.2.1 Initial production sample.-At the beginning of regular production, a sample shall be submitted in accordance with the contract requirements. The sample shall be manufactured using the same materials, equipment, processes and procedures as will be used in regular production. All parts and materials, shall be the same as used for regular production and shall be obtained from the same source of supply. The sample shall consist of:

a. 50 ea. - Bandoleers for dimensional and visual examination and drop test (see 6.2)

b. 25 ea. - Straps for dimensional and visual examination.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:43Z
Check the source to verify that this is the current version before use.

4.2.1.1 Examination and test.-After inspection and provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specifications at a Government laboratory or such other facility specified in the contract.

4.2.1.2 Initial production sample failure.-Failure of the sample to comply with the requirements of the drawings and specifications shall result in sample disapproval. Determination as to acceptability of any initial production sample shall be based upon results of the initial tests only and no second tests shall be permitted on that initial production sample.

4.3 Inspection provisions.

4.3.1 Lot.

4.3.1.1 Submission of product.-The product shall be submitted in accordance with MIL-STD-105.

4.3.1.2 Size of lot.-The bandoleer lot size shall be as agreed upon between the contractor and the contracting officer, provided the formation of the lot is in accordance with Standard MIL-STD-105.

4.3.2 Examination.-Examination for major and minor defects shall be performed as specified herein. Each bandoleer found to be defective shall be rejected.

4.3.2.1 Sampling and acceptance criteria.-Sampling plans and procedures shall be in accordance with MIL-STD-105. Defect characteristics for major and minor defects shall be performed on a class basis in accordance with the classification of defects, using applicable sampling plans and acceptance criteria of MIL-STD-105. The Acceptable Quality Level (AQL) for the major class shall be 1.5 percent with no individual defect characteristics associated with the class basis for major defects exceeding an AQL of 0.65 percent. The AQL for minor class shall be 4.0 percent.

4.3.3 Classification of defects.-The classification of defects shall be as follows:

Defects		Method of Inspection
MAJOR		
101.	Improper stitch type	Visual
102.	Skipped, broken or omitted stitching greater than 1/2 inch in length	Measure
103.	Rips or tears	Visual
104.	Soiled	Visual
105.	Missing bar tack	Visual
106.	Width of pockets, min.	Measure
107.	Depth of pockets, min.	Measure
108.	Ends of straps incorrectly located	Measure
109.	Flap, max.	Measure

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:43Z
Check the source to verify that this is the current version before use.

4.3.3 (Cont'd)

Defect	Method of Inspection
MINOR	
201. Twisted strap	Visual
202. Excessive bar tack	Visual
203. Missing or excessive back stitching when required	Visual
204. Insufficient or excessive stitching per inch	Measure
205. Missing identification	Visual
206. Width of pockets, max.	Measure
207. Depth of pockets, max.	Measure
208. Length of strap	Measure
209. Flap, min.	Measure
210. Skipped, borken or omitted stitching, 1/4 to 1/2 inch in length	Measure
211. Length of stitching run-off (Tails)	Measure
212. Missing or incomplete safety pin	Visual

4.3.4 Tests.-The following test shall be conducted in accordance with the test methods and procedures prescribed in 4.4.

4.3.4.1 Drop test.-A sample of 50 bandoleers shall be subjected to the drop test. If three or more bandoleers fail to comply with the requirements of 3.3 the lot shall be rejected. If one or two bandoleers fail to comply with the requirements, a second sample consisting of the same number of units as specified in the first sample shall be tested. If in the accumulated sample four or more units fail to comply with the requirements, the lot shall be rejected.

4.3.5 Packing and marking inspection.-Inspection for packing and marking shall be as directed by the contracting officer.

4.3.6 Inspection equipment.-The examination and tests shall be made using equipment approved by the Government.

4.4 Test methods and procedures.

4.4.1 Drop test.-All pockets of the test bandoleers shall be filled with inertly loaded cartridges, 7.62mm in clips, 5 round as shown on Drawing D8594724 or equivalent weights approximating the shape of loaded clips (4085 plus or minus 10 grains per pocket). The filled bandoleer shall then be suspended by the strap, with the weight evenly distributed, from a rigid horizontal bar of approximately 1/2 inch diameter. The strap, at the point of suspension, shall then be raised vertically one foot and dropped upon the bar.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:43Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packing.-Level C (domestic shipment).-Bandoleers shall be packed in fiberboard box as follows: 1,000 bandoleers in 40 bundles, 25 bandoleers per bundle. Straps are to be placed on back of each bandoleer. Bandoleers are to be packaged oriented in the same direction (front side up) in neat bundles of 25 pieces and securely tied at both ends. The bandoleers shall be packed within a corrugated fiberboard box, 350 lb. test, conforming to style RSC of PPP-B-636, containing a preformed, bag type, interior wrap conforming to barrier material, Class C-1 of PPP-B-1055.

5.2 Marking.-Each box shall be marked with the bandoleer manufacturer's name, lot number and date of manufacture. Shipments shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Ordering data.-Invitations for bids and contracts or orders will specify the following:

6.1.1 Title, number, and date of this specification.

6.1.2 Requirement for contractor to provide and maintain an inspection system in accordance with MIL-I-45208, Inspection System Requirements.

6.2 The 50 samples submitted for first article evaluation should not be subjected to the drop test prior to submission to the Government.

Custodian:

Army - MU

Preparing Activity:

Army - MU

Project No. 1305-A753

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:43Z
Check the source to verify that this is the current version before use.

* The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1305-A511

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:43Z
Check the source to verify that this is the current version before use.