MIL-C-46355(Ord)
18 September 1962

MILITARY SPECIFICATION

CASE, BATTERY COMMAND PERISCOPE: M165

1. SCOPE

1.1 This specification covers a carrying case used to contain Periscope, Battery Command: M43, with accessories.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-F-13926	Fire Control Materiel: General Specification Governing the Manufacture and Inspection of
MIL-F-14619	Fire Control Parts, Equipment and Tools; Packaging of
MIL-I-45208	Inspection Requirements, General Specification for

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-130	Identification Marking of U.S. Military Property

DRAWING

Ordnance Corps

F8624252	Case, Battery Command Periscope: M165

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:41Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Initial production sample.- Unless otherwise directed by the contracting officer an initial production sample case shall be required. The sample shall be manufactured in the same manner, using the same materials, equipment, processes and procedures as will be used in regular production.

3.2 Materials.- The materials shall be in accordance with the drawings, material specifications and general specifications forming a part of this specification.

3.3 Construction.- The case shall be constructed in accordance with Drawing F8624252 "Case, Battery Command, Periscope: M165". The requirements of this specification are detailed only to the extent considered necessary to insure the inherent quality and performance capabilities.

3.4 General specification.- The contractor shall be responsible for adherence to, and compliance with, the following requirements of Specification MIL-F-13926:

(a) Order of precedence
(b) Protective finished surfaces
(c) Finish, painting, and protective
(d) Workmanship

3.5 Environmental.

3.5.1 Storage temperature.- The case shall show no evidence of physical failure and shall meet all performance requirements of this specification at the standard ambient temperature (60 to 90 degrees Fahrenheit) after having been exposed and thermally stabilized at ambient temperatures of plus 160 and minus 180 degrees Fahrenheit.

3.5.2 Operating temperature.- The case shall meet all applicable requirements of 3.6 while exposed and thermally stabilized at ambient temperatures of plus 150 and minus 40 degrees Fahrenheit.

3.5.3 Water immersion.- The locked case shall be exposed to the requirements of Procedure I of the water immersion test specified in Specification MIL-F-13926. Immediately after the water immersion test, the interior of the case shall show no evidence of leakage or moisture.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:41Z
Check the source to verify that this is the current version before use.

3.6 Operation.

3.6.1 Fastening devices.- Fastening devices used to secure the case and interior components shall function without interference; and when secure, shall show no evidence of looseness.

3.6.2 Ease of operation.- The case, including hinge components and handles shall open or close and operate easily without restriction or binding.

3.7 Identification marking.- Unless otherwise specified, identification marking shall be in accordance with Standard MIL-STD-130.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibilities.- The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 General requirements.- Inspection requirements and procedures shall be in accordance with Specification MIL-I-45208.

4.3 Initial production sample.- Prior to production, the contractor shall submit the initial production sample in accordance with 3.1 for inspection by the contractor under the surveillance of the Government. This inspection shall be conducted at the contractor's facility, or Government approved laboratory, using test equipment authorized for use on the contract. The sample shall be inspected for all requirements of this specification by utilizing examination and testing methods prescribed herein.

4.3.1 Initial production sample failure.- Should the production sample fail to pass the prescribed tests, the contractor shall cease those operations which are causing the rejection and shall make the necessary corrections. When corrections in the process have been made, a new production sample shall be examined and tested by the contractor under the surveillance of the Government. Acceptance of production lots will not commence until an acceptable production sample is submitted and corrective actions have been taken to eliminate deficiencies.

4.4 Lot formation.- Inspection lot sizes and lot formation shall be in accordance with Standard MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:41Z
Check the source to verify that this is the current version before use.

4.4.1 Defective units and lots.- Defective units and lots shall be processed as specified in Standard MIL-STD-105.

4.5 Material.- Control of material shall be in accordance with test data requirements of Specification MIL-I-45208.

4.6 Inspection of components.- All positional and functional characteristics shown on drawings, or contained in notes on the drawings or referenced specifications, which indicate precision requirements and have a bearing on the functional accuracy and performance of the case shall be inspected in accordance with the written inspection system required by Specification MIL-I-45208. These characteristics are defined as requirements effecting concentricity, squareness, parallelism, micro-finishes 64 RMS or better, threads, identification marking and performance.

4.6.1 Sampling inspection.- Where quality control has been established on in-process manufacture, sampling inspection of components may be used in lieu of 100 percent inspection and shall be in accordance with Table I.

TABLE I - SAMPLING PLAN

Lot Size Inclusive	Sample Size	Accept Lot	Reject Lot
0 - 25	Use 100% Inspection		
26 - 35	20	0	1
36 - 50	25	0	1
51 - 150	30	0	1
151 - 300	30	1	2
301 - over	60	2	3

4.6.2 Disposition of non-conforming product.- Acceptance and rejection numbers are expressed in terms of defective units. One or more defects on any unit shall constitute a defective unit. Disposition of non-conforming components shall be in accordance with Standard MIL-STD-105.

4.7 Inspection equipment.- Supply, calibration, maintenance and use of inspection equipment shall be in accordance with Specification MIL-I-45208.

4.7.1 Accuracy requirements.- Inspection equipment which incorporates features for measuring values or sizes established by product requirements shall be capable of measuring those values within an accuracy of ten percent of the specified tolerance except as specified in 4.7.2. In cases where the ten percent accuracy imposes impractical or very difficult design and fabrication problems, or results in a test equipment cost factor which is exorbitant in relation to the cost and application of the product to be inspected, the Government shall be expeditiously advised in order that necessary appropriate action can be taken.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:41Z
Check the source to verify that this is the current version before use.

4.7.2 Inspection equipment design requirements.

4.7.2.1 Device to test environmental requirements.- The test apparatus shall be in accordance with the requirements contained in and pertinent to volume and tolerances governing the environmental test conditions and measurements contained in Specification MIL-F-13926.

4.8 Acceptance inspection.

4.8.1 Classification of defects.- The classification of defects in Tables II and III shall constitute the minimum inspection requirements to be performed prior to acceptance or rejection by lots. The AQL specified shall apply to each individual characteristic as a basis for acceptance or rejection.

4.8.2 Disposition of rejected lots.- Rejected lots shall be screened for all defective characteristics. After corrections have been made and the Government inspector informed of the corrective action taken, the lots shall be resubmitted for acceptance as outlined in Standard MIL-STD-105.

TABLE II - CLASSIFICATION OF DEFECTS

Use Inspection Level L-7 in Table III-B with Sampling Plan Table IV-A of Standard MIL-STD-105

CRITICAL: None defined

MAJOR: AQL 4.0% Defective		Reqt Par.	QA Par.	Test Method
101.	Physical failure, post storage temperature	3.5.1	4.9.2.1	Visual-Tactile
MINOR: AQL 10.0% Defective				
201.	Improper function of fastening devices at extreme temperatures	3.5.2 3.6.1	4.9.2.2	Functional
202.	Inability to open or close case with ease at extreme temperatures	3.5.2 3.6.1	4.9.2.2	Manual
203.	Binding of hinges and handles at extreme temperatures	3.5.2 3.6.2	4.9.2.2	Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:41Z
Check the source to verify that this is the current version before use.

TABLE III - CLASSIFICATION OF DEFECTS

Use Inspection Level II in Table III-A with Sampling Plan Table IV-A of Standard MIL-STD-105

CRITICAL: None defined

MAJOR: AQL 1.5% Defective		Reqt Par.	QA Par.	Test Method
101.	Improper construction and materials	3.2.3.3	4.9.1	Visual
102.	Exterior components improperly assembled	3.3	4.9.1	Visual
103.	Interior components improperly assembled	3.3	4.9.1	Visual
104.	Leakage	3.5.3	4.9.2.3	Standard Measuring Equipment(SME) Visual
MINOR: AQL 4.0% Defective				
201.	Improper function of fastening devices	3.6.1	4.9.3.1	Functional
202.	Case opens and closes with restriction	3.6.2	4.9.3.2	Manual
203.	Binding of hinges, or handles	3.6.2	4.9.3.2	Manual
204.	Identification marking improper	3.7	4.9.4	Visual

4.9 Test methods and procedures.

4.9.1 Materials and construction.- Proper materials and construction of case in accordance with the pertinent drawings and specifications can be determined by means of standard measuring equipment, visual, manual and tactile inspection techniques for compliance with 3.2 and 3.3.

4.9.2 Environmental.

4.9.2.1 Storage temperature.- The case shall be exposed to the temperatures indicated in 3.5.1, in accordance with Procedure II of Specification MIL-F-13926. Upon return to standard ambient temperature the case shall be subjected to a visual and tactile examination for any physical damage. If there is no evidence of any physical damage externally or internally, then the case shall be tested for the requirements specified in 3.5.1

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:41Z
Check the source to verify that this is the current version before use.

4.9.2.2 Operating temperature.- The case shall be exposed to the temperatures indicated in 3.5.2, in accordance with Procedure I of Specification MIL-F-13926. When thermal stabilization of the case is reached at plus 150 degrees Fahrenheit and minus 40 degrees Fahrenheit respectively, the case shall be tested for the requirements specified in 3.5.2 at each of the temperatures.

4.9.2.3 Water immersion.- This test shall be accomplished in accordance with Specification MIL-F-13926 as indicated in 3.5.3.

4.9.3 Operation.

4.9.3.1 Fastening devices.- This is a functional check to determine compliance with the requirements specified in 3.6.1.

4.9.3.2 Ease of operation.- This is a functional check to insure that the complete case is operable in compliance with 3.6.2.

4.9.4 Identification marking.- Identification marking shall be visually inspected for conformance to Standard MIL-STD-130.

4.9.5 Preservation, packaging and packing.- Quality assurance provisions for the preservation, packaging, and packing of the case shall be in accordance with the prescribed specification in 5.1.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging and packing.- Preservation, packaging and packing shall be in accordance with Specification MIL-F-14619 and the applicable packaging data sheet.

6. NOTES

6.1 Intended use.- The case is primarily a protective case intended to house and carry the Periscope, Battery Command: M43 and accessories. It is not to be confused with a packing case and is not intended for initial shipment without additional packing.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Applicable packaging data sheet number (See 5.1).
(c) Applicable stock number.
(d) Provisions for the initial production sample including date of delivery (See 3.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:41Z
Check the source to verify that this is the current version before use.

6.3 Design information.- Design information regarding specific equipment not covered or referenced by this specification may be obtained from the procuring activity upon the specific request of the contractor.

6.4 Definitions.

6.4.1 Tactile.- Skillful manipulation or sensing.

6.4.2 Standard measuring equipment (SME).- Standard measuring equipment is defined as the common hand type measuring devices which are usually stocked by commercial supply houses for ready supply (shelf items), and which are normally used by an inspector to perform dimensional inspection of items under procurement. This category also includes commercial testing equipment such as meters, optical comparators, etc.

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any invention that may in any way be related thereto.

Custodian:

Army-Ordnance Corps

Preparing activity:

Army-Ordnance Corps

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:41Z
Check the source to verify that this is the current version before use.