MILITARY SPECIFICATION

COMPUTER, GUN DIRECTION: M18
MANUFACTURING PROCESSES AND INSPECTION OF

This amendment forms a part of Military Specification MIL-C-46357(MU), dated 19 March 1965.

Paragraph 3.2.6.3: Delete fifth sentence: "The edge of the maskant shall be applied along a line formed by prolonging the edges of the end notches across the board to within 1/64 inch of the line." Substitute the following: "The maskant shall be applied to the connector contacts with the edge of the maskant being 1/64-inch (in-board) above the silk screened numbers, except in areas where component leads interfere, in which event the maskant shall be removed from these areas only."

Paragraph 3.3.2: Delete first sentence: "Groups of wire shall be securely bound by means of spot ties spaced at a distance 1/2 inch apart or twice the diameter of the wire group." Substitute the following: "The group of wires along the 130 pin connectors shall be securely bound by means of spot ties at each end where the breakout occurs from the major trunk, plus three other spot ties equally spaced between the end ties. All other groups of wires shall be securely bound by means of spot ties 1/2 inch apart or twice the diameter of the wire group whichever is greater."

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1220-A250Y

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:41Z
Check the source to verify that this is the current version before use.