MIL-C-46357(MU)
AMENDMENT 2
18 July 1966
SUPERSEDING
AMENDMENT 1
31 May 1966

MILITARY SPECIFICATION

COMPUTER, GUN DIRECTION: M18
MANUFACTURING PROCESSES AND INSPECTION OF

This amendment forms a part of Military Specification MIL-C-46357(MU), dated 19 March 1965.

Paragraph 2.1: Delete the following Military Specifications:

"MIL-S-6872 Soldering Process, General Specification For
MIL-P-18177 Plastic Sheet, Laminated, Thermosetting, Glass Fiber Base, Epoxy-Resin"

Paragraph 2.1: Add the following Military Specification:

"MIL-S-45743 Soldering, High Reliability, Electrical Connections, for Guided and Ballistic Missile Systems, with Electrically - Heated Soldering Irons, and Resistance Soldering Apparatus; Procedures For"

Paragraph 3.2.1: Delete in its entirety and substitute the following:

"3.2.1 Circuit board materials.- Unless otherwise specified the copper clad plastic sheet shall conform to MIL-P-13949, Type FL-GE-0.062-C-2/2-CLIII or Type FL-GE-0.062-C-2/0-CLIII as required by applicable drawings."

Paragraph 3.2.6: Delete "3.2.6 Soldering and tinning" and substitute the following:

"3.2.6 Soldering process.- Unless otherwise specified herein, the soldering process shall conform to MIL-S-45743. Should any conflict exist between MIL-S-45743 and this specification, this specification shall take precedence."

Paragraph 3.2.6.1: Delete last sentence and substitute the following: "The solder used shall conform to QQ-S-571, Type SN60 or SN63."

FSC 1220

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:41Z
Check the source to verify that this is the current version before use.

Paragraph 3.2.6.3: Delete fifth sentence: "The edge of the maskant shall be applied along a line formed by prolonging the edges of the end notches across the board to within 1/64 inch of the line." Substitute the following: "The maskant shall be applied to the connector contacts with the edge of the maskant being 1/64 inch (in-board) above the silk screened numbers, except in areas where component leads interfere, in which event the maskant shall be removed from these areas only."

Paragraph 3.3.2: Delete first sentence: "Groups of wire shall be securely bound by means of spot ties spaced at a distance 1/2 inch apart or twice the diameter of the wire group." Substitute the following: "The group of wires along the 130 pin connectors shall be securely bound by means of spot ties at each end where the breakout occurs from the major trunk, plus three other spot ties equally spaced between the end ties. All other groups of wires shall be securely bound by means of spot ties 1/2 inch apart or twice the diameter of the wire group whichever is greater."

TABLE I: Delete the first four lines of the columns and substitute the following new line:

"101. Circuit board materials 3.2.1 MIL-P-13949"

TABLE I, under METHOD OF INSPECTION: Delete "MIL-S-6872" and substitute "QQ-S-571"

TABLE VIII: Delete the first four lines and substitute:

"301.	Circuit board materials	3.2.1
302.	Circuit board material (gold plating)	3.2.3.2(a)
303.	Circuit board material (gold-nickel plating)	3.2.3.2(b)
304.	Soldering process and soldering	3.2.6; 3.2.6.1"

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1220-A258Y

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:41Z
Check the source to verify that this is the current version before use.