MILITARY SPECIFICATION

RANGE FINDER, FIRE CONTROL: M24

This amendment forms a part of Military Specification MIL-R-46358A (MU), dated 27 February 1964.

Paragraph 3.6.15.1: Delete and substitute:

"3.6.15.1 Range scale accuracy.- With a target provided at 1500 meters ± 100 meters and with the range scale set to the range indicated, the horizontal calibration knob shall be adjusted for target range coincidence. When ranging on targets at the following ranges, the range scale shall agree with the target range within the tolerance specified below when read at the center of the field."

Target Range in Meters	Tolerance in Meters
570 to 630	3
770 to 830	5
1400 to 1600	0.0 (by adjustment)
1800 to 2200	27
3700 to 4300	110

Paragraph 3.6.15.3, Table I, line 13: Delete "1°57'" from tolerance column and substitute "1°0'".

Paragraph 3.6.21, Table IV: Delete last line and substitute:

"Occluder lever (in detent position) 45 oz. inch 45 oz. inch 45 oz inch"

Paragraph 3.7: Delete and substitute:

"3.7 Sealing.- The range finder body and end housings shall show no evidence of leakage when subjected to an internal pressure of three pounds per square inch (3 psi) of Nitrogen at standard ambient temperature (plus 60 degrees to 90 degrees Fahrenheit) for a period of 1½ hours. The allowable drop in pressure shall be no more than .10 pound within the required time limit."

Paragraph 4.2.2, Table V: Delete characteristic 133 from major class and substitute:

"133 Range scale accuracy"

Paragraph 4.5.32: Delete and substitute:

"4.5.32 Range scale accuracy.- Range scale accuracy shall be performed with the I.C.S. medium set into the range finder as specified in

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:42Z
Check the source to verify that this is the current version before use.

4.5.31. Set the compensator of the fixture to represent a target distance of 1500 meters. Set the range knob of the range finder to indicate 1500 meters as read on the range scale and obtain coincidence (target image) by means of the horizontal calibration knob. The coincidence test shall be repeated a minimum of 5 times to establish a medium setting of the horizontal calibration knob. Position the fixture compensator to each of the selected ranges specified in 3.6.15.1 and obtain coincidence of the target image by means of the range knob and observe the range readings of the range finder. The range readings shall not exceed the tolerances specified in 3.6.15.1."

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1240-A545Y

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:42Z
Check the source to verify that this is the current version before use.