MIL-S-46347B(MU)
12 October 1964
SUPERSEDING
MIL-S-46347A(MU)
8 March 1963

MILITARY SPECIFICATION

SIGHTUNIT: M53

1. SCOPE

1.1 This specification covers a fire control instrument which is composed of Elbow Telescope: M109 and Telescope Mount: M128.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-F-13926	Fire Control Materiel: General Specification Governing the Manufacture and Inspection of
MIL-P-14232	Parts, Equipment and Tools for Ordnance Materiel, Packaging of
MIL-I-45607	Inspection Equipment, Supply and Maintenance of
MIL-T-46324	Telescope, Elbow: M109
MIL-M-46325	Mount, Telescope: M128

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	Quality Assurance Terms and Definitions

DRAWINGS

U.S. Army Munitions Command

F8245970	Mount, Telescope: M128
F8245971	Sightunit: M53

FSC 1240

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:40Z
Check the source to verify that this is the current version before use.

DRAWINGS (Continued)

U.S. Army Munitions Command

F8588780 Telescope, Elbow: M109

PACKAGING DATA SHEET

MIL-P-14232/P8213867 Packaging of Sightunit: M53

(Copies of specifications, standards, drawings, and packaging data sheet required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Fabrication.- The sightunit shall be manufactured in accordance with Drawing F8245971 and drawings pertaining thereto.

3.1.1 Telescope.- The telescope shall be fabricated in accordance with Drawing F8588780 and drawings pertaining thereto, and shall meet the requirements of MIL-T-46324.

3.1.2 Mount.- The telescope mount shall be fabricated in accordance with Drawing F8245970 and drawings pertaining thereto, and shall meet the requirements of MIL-M-46325.

3.2 General specification.- The contractor shall be responsible for adherence to, and compliance with, the requirements of MIL-F-13926 listed below:

(a) Order of precedence
(b) Dimensions and tolerances
(c) Inorganic protective surface finishes
(d) Part identification and marking
(e) Workmanship

3.3 Telescope retention.- The telescope clamping mechanism shall prevent movement of the telescope within the telescope mount when a 40 pound-inch torque is applied to the telescope body. This requirement shall be met at a standard ambient temperature between +60° and +90° Fahrenheit (F).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:40Z
Check the source to verify that this is the current version before use.

4.1.1 General provisions.- The quality assurance provisions of this specification and of other documents referenced herein form the basis for inspection to be performed by the supplier. Definitions of inspection terms not otherwise defined herein shall be as listed in MIL-STD-109.

4.2 Inspection provisions.

4.2.1 Inspection lot.- Unless otherwise specified by the contracting officer, inspection lot size, formation, and presentation of lots shall be in accordance with "Submission of Product" as specified in MIL-STD-105.

4.2.2 Examination and tests.- The following test related to Section 3 herein shall be performed on a defect (individual characteristic) basis in accordance with MIL-STD-105 and the inspection level and sampling plan specified in Table I titled "Classification of Defects". Examinations and tests for packaging, packing and marking shall be in accordance with MIL-P-14232 and Section 5 herein. The classified defect constitutes the minimum inspection to be performed by the supplier prior to Government acceptance or rejection by lot. The Government reserves the right to inspect for any applicable requirement and to reject individual non-conforming items.

TABLE I - CLASSIFICATION OF DEFECTS

Use Inspection Level II of Table I with
Sampling Plan Table II-A of MIL-STD-105

	REQUIREMENT	TEST PROCEDURE
CRITICAL: NONE		
MAJOR: AQL 1.0%		
101. Telescope retention	3.3	4.4.2
MINOR: NONE		

4.2.3 Disposition of non-conforming product.- Rejected lots shall be screened for all defective characteristics. Removal or correction of defective units and resubmittance of rejected lots shall be in accordance with "Acceptance and Rejection" as specified in MIL-STD-105.

4.3 Inspection equipment.- Except as otherwise provided for by the contract, the contractor shall maintain all required measuring and testing equipment in accordance with the applicable requirements specified in MIL-I-45607. The Government reserves the right to use the test equipment for its own independent inspections to the extent that such use will not unduly interfere with the contractor's delivery schedule.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:40Z
Check the source to verify that this is the current version before use.

4.3.1 Government furnished inspection equipment.- Where the contract provides for Government furnished test equipment, care and maintenance of test equipment shall be in accordance with the applicable requirements specified in MIL-I-45607.

4.4 Test methods and procedures.

4.4.1 Fabrication.- The inspection requirements specified below shall be complied with for all sightunits containing the telescope and mount assembled and submitted for final acceptance inspection.

4.4.1.1 Telescope.- A visual examination of the telescope shall be conducted to insure that no defects are evident and that it has previously met all requirements specified in MIL-T-46324 and 3.1.1.

4.4.1.2 Mount.- A visual examination of the telescope mount shall be conducted to insure that no defects are evident and that it has previously met all requirements specified in MIL-M-46325 and 3.1.2.

4.4.2 Telescope retention.- The telescope clamping mechanism shall be tested in accordance with standard shop practices using a commercial torque wrench accurate to within 1/4 pound inch. . . An appropriate adapter shall be utilized to permit application of the torque wrench to the telescope body. The telescope shall show no movement when the specified torque is applied to the telescope body in accordance with 3.3.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing and marking.- Packaging, packing and marking shall be in accordance with MIL-P-14232 and Packaging Data Sheet MIL-P-14232/P8213867. The level of protection shall be as specified in the procurement document.

6. NOTES

6.1 Intended use.- The sightunit is used as a direct and indirect fire control instrument for laying mortars and rocket launchers in elevation and azimuth.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Selection of applicable levels of preservation, packaging, and packing.
(c) Applicable stock number.
(d) Applicable packaging data sheet number (see 5.1).

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 1240-A426Y

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:40Z
Check the source to verify that this is the current version before use.