MILITARY SPECIFICATION

TELESCOPES, ELBOW: M92D AND M92F

This amendment forms a part of Military Specification MIL-T-46365(MU) dated 20 December 1962.

Paragraph 3.7: Delete and substitute:

"3.7 Sealing. - The telescope shall show no evidence of leakage in excess of 0.2 psig when subjected to an external pressure of dry nitrogen of five (5) pounds per square inch gage pressure (psig) for a minimum period of two (2) hours. Dew point of nitorgen shall be at least as low as minus 25° Fahrenheit (F)."

Delete paragraphs 3.8.1 and 3.8.2 and substitute the following:

"3.8.1 Collimation. - The line of sight through the center of the boresight cross shall be parallel to the axis of the external taper within 0.5 mils.

3.8.2 Parallelism of image and reticle. - With the axis of the external taper horizontal and the cross level vial centered, the horizontal reticle (defined by the lead marks) through the boresight cross shall be parallel to a horizontal target line image within 30 minutes of arc."

Delete paragraphs 4.3 and 4.3.1 and substitute the following:

"4.3 First Article (InitialProduction) Approval. - The requirent for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of (3) telescopes plus three (3) each of all items covered by SQAP. The sample shall be manufactured in the same manner, using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as used in regular production.

4.3.1 Government Testing. - When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it, conforms to all the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials.

4.3.2 Contractor Testing. - When the contractor is responsible for conducting first article approval tests, the sample shall be inspected by the contractor for all the requirements of the contract.The sample and

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:43Z
Check the source to verify that this is the current version before use.

a record of this inspection, including certificates of conformance for materials, shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection."

Add paragraph as follows:

"6.5 International standardization agreement. - Certain provisions of this specification are the subject of international standardization agreement, ABCA-Army-Std-46B. When amendment, revision, or cancellation of this specification is proposed which will effect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels including departmental standardization offices, if required."

* The outside margins have been marked to indicate where additions to the previous amendment have been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notation and relationship to the last previous issue.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1240-A267

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:43Z
Check the source to verify that this is the current version before use.