NOTE: The document identifier and heading have been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.


MIL-PRF-27/313A
14 January 1983
SUPERSEDING
MIL-T-27/313
14 June 1982

PERFORMANCE SPECIFICATION SHEET

TRANSFORMERS, POWER, 10 VOLT-AMPERES, 60 HERTZ, TF4S03YY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the transformer described herein shall consist of this specification and the latest issue of MIL-T-27.



INCHES	MM
.005	0.13
.016	0.41
.031	0.79
.062	1.57
.070	1.78
.375	9.53
.875	22.23
1.25	31.8
1.50	38.1
1.75	44.5
2.06	52.3
2.75	69.9

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.
3. Marking shall be on the sides of the case.
4. Unless otherwise specified, tolerance shall be ±.063 (1.60 mm).
5. Electrical values shall be marked as specified in table I.

FIGURE 1. Dimensions and configuration.

(A) denotes change

FSC 5950

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:08Z
Check the source to verify that this is the current version before use.

REQUIREMENTS: (When numbers in parentheses, i.e., (1-2) are used, they indicate the winding and the extreme terminals of the winding.)

Electrical ratings.

Primary voltage (1-2). 115 volts ac, 50 to 60 hertz.

Primary dc resistance. 36 ohms ±25 percent.

Secondary voltage (3-5). See table I.

Volt-ampere rating 10 volt-amperes.

Ⓐ Working voltage (1-2). 535 volts peak.

Design and construction:

Dimensions and configuration. See figure 1.

Duty cycle: Continuous.

Case: Metal enclosed.

Material: Steel.

Terminals: Solderable hook terminals.

Terminal height. 0.375 ±0.063 inch.

Terminal diameter: 0.062 ±0.005 inch.

Weight: 1.5 pounds, maximum.

Operating temperature range: -55° to +130°C.

Altitude: 10,000 feet.

Terminal strength: MIL-STD-202, method 211, test condition A, 2.0 pounds.

Ⓐ Dielectric withstanding voltage (each winding) (at sea level) 1,500 volts rms.

Electrical characteristics:

Rated load: With 115 volts ac and 60 Hz across (1-2), and rated current in secondary, the voltage across (3-5) shall be as specified in table I.

Regulation. $\frac{\text{Voltage (no load)} - \text{Voltage (rated load)}}{\text{Voltage (rated load)}} \times 100$

Shall not exceed 12 percent.

Polarity. Additive with terminals 2 and 3 connected.

Temperature rise: 35°C with 115 volts ac, 60 hertz across (1-2) at an ambient temperature of 95°C, full load terminals (3-5).

Marking location. See figure 1.

Part number M27/313-(dash number from table I).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:08Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical ratings.

Ⓐ

Dash number	Secondary (3-5)		
	Voltage (volts) ±3 percent	Current 1/ (amperes)	DC resistance (ohms) ±25 percent
01	5.0	2.0	0.12
02	6.3	1.58	0.18
03	8.0	1.25	0.27
04	10.0	1.00	0.42
05	12.6	0.79	0.65
06	14.0	0.72	0.74
07	16.0	0.68	1.08
08	18.0	0.55	1.42
09	20.0	0.50	1.54
10	22.0	0.45	1.90
11	25.0	0.40	2.55
12	28.0	0.36	3.00
13	31.0	0.32	3.80
14	35.0	0.29	4.50
15	39.0	0.26	6.30
16	43.0	0.23	7.00
17	48.0	0.21	9.30
18	55.0	0.18	11.0
19	63.0	0.16	16.4
20	70.0	0.143	19.0
21	80.0	0.125	25.0
22	90.0	0.111	30.4
23	100	0.100	40.5
24	110	0.091	44.5
25	123	0.081	70.0
26	138	0.073	80.0
27	157	0.064	100
28	175	0.057	111
29	200	0.050	160
30	220	0.045	168

1/ For 50 Hz operation, reduce secondary current by 10 percent.

QUALITY ASSURANCE PROVISIONS:

Extent of Qualification:

Ⓐ Qualification testing and approval to M27/312-26, M27/316-30, and M27/322-24 shall be sufficient to grant qualification approval to MIL-T-27/312 through MIL-T-27/322, inclusive, all parts.

Ⓐ Qualification testing and approval to M27/313-30 shall be sufficient to grant qualification approval M27/313-01 through M27/313-30.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:08Z
Check the source to verify that this is the current version before use.

Custodians.
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR
Navy - SH, OS
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - ME
Navy - MC, AS
Air Force - 19

Agent:
DLA - ES

Preparing activity:
Army - ER

(Project 5950-0592-15)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:08Z
Check the source to verify that this is the current version before use.