INCH-POUND

MIL-PRF-27/318C
AMENDMENT 1
27 July 2017
SUPERSEDING
MIL-PRF-27/318C
22 April 2011

PERFORMANCE SPECIFICATION SHEET

TRANSFORMERS, POWER, 80 VOLT-AMPERES, 60 HERTZ

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the transformer described herein shall consist of this document and the latest issue of specification MIL-PRF-27.





FIGURE 1. Dimensions and configurations.


AMSC N/A

FSC 5950


Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:09Z
Check the source to verify that this is the current version before use.



DASH NUMBERS 03 THRU 30



DASH NUMBERS 01 AND 02



CIRCUIT DIAGRAM

Dim	Inches	mm	Dim	Inches	mm
A	3.13 ±.031	79.5 ±0.79	J	.470 ±.031	11.94 ±0.79
B	.164-32 UNC-2B (4 PLACES) 8 FULL THDS min.		K	4.13	104.9
C	2.25 ±.016	57.2 ±0.41	L	.070 ±.005	1.78 ±0.13
D	2.63 ±.031	66.8 ±0.79	M	.062 ±.005	1.57 ±0.13
E	2.00 ±.016	50.8 ±0.41	N	.188 ±.005	4.78 ±0.13
F	.875 DIA	22.22 DIA	O	.094 ±.005	2.39 ±0.13
G	1.063 DIA	27.00 DIA	P	.080 ±.005	2.03 ±0.13
H	.375 ±.031	9.52 ±0.79			

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking shall be on the sides of the case.
4. Unless otherwise specified, tolerance shall be ±.063 (1.60 mm).
5. Electrical values shall be marked as specified in table I, except DCR.
6. The mounting surface can be painted.

FIGURE 1. Dimensions and configurations – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:09Z
Check the source to verify that this is the current version before use.

REQUIREMENTS: (When numbers in parentheses, i.e., (1-2) are used, they indicate the winding and the extreme terminals of the winding.)

Electrical ratings:

Primary voltage (1-2): 115 volts ac, 50 to 60 hertz.

Primary dc resistance: 3.7 ohms ±25 percent.

Secondary voltage (3-5): See table I.

Volt-ampere rating: 80 volt-amperes.

Working voltage (1-2): 535 volts peak.

Design and construction:

Dimensions and configuration: See figure 1.

Duty cycle. Continuous.

Case: Metal enclosed.

Material: Steel.

Terminals: Solderable terminals.

Dash numbers	Terminal type	Height (inches)	Diameter (inches)
01 and 02	Hook	0.473 ±.031	0.080 ±.005
03 through 30	Hook	0.375 ±.031	0.062 ±.005

Weight: 5.0 pounds, maximum.

Operating temperature range. -55° to +130°C.

Altitude: 10,000 feet.

Terminal strength: MIL-STD-202-211, test condition A, 2.0 pounds.

Dielectric withstanding voltage (each winding) (at sea level): 1,500 volts rms.

Electrical characteristics:

Rated load: With 115 volts ac and 60 Hz across (1-2), and rated current in secondary, the voltage across (3-5) shall be as specified in table I.

Regulation: $\frac{Voltage\,(no\ load) - Voltage\,(rated\ load)}{Voltage\,(rated\ load)}\ x\ 100$

Shall not exceed 10 percent.

Polarity: Additive with terminals 2 and 3 connected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:09Z
Check the source to verify that this is the current version before use.

Temperature rise: 35°C with 115 volts ac, 60 hertz across (1-2) at an ambient temperature of 95°C, full load terminals (3-5).

Marking location: See figure 1.

Part or Identification Number (PIN): M27/318-(dash number from table I).

TABLE I. Electrical ratings.

Dash number M27/318-	Secondary (3-5)		
	Voltage (volts) ±3 percent	Current 1/ (amperes)	DC resistance (ohms) ±25 percent
01	5.0	16.00	0.011
02	6.3	12.70	0.016
03	8.0	10.00	0.037
04	10.0	8.00	0.050
05	12.6	6.35	0.070
06	14.0	5.72	0.100
07	16.0	5.00	0.120
08	18.0	4.44	0.160
09	20.0	4.00	0.190
10	22.0	3.64	0.25
11	25.0	3.20	0.30
12	28.0	2.86	0.40
13	31.0	2.58	0.45
14	35.0	2.28	0.50
15	39.0	2.05	0.70
16	43.0	1.85	0.94
17	48.0	1.63	1.00
18	55.0	1.46	1.50
19	63.0	1.27	1.70
20	70.0	1.14	2.40
21	80.0	1.00	2.70
22	90.0	0.890	3.80
23	100	0.800	4.20
24	110	0.726	5.70
25	123	0.650	6.50
26	138	0.580	9.50
27	157	0.510	10.5
28	175	0.457	14.8
29	200	0.400	17.0
30	220	0.364	23.0

1/ For 50 Hz operation, reduce secondary current by 10 percent.

VERIFICATION:

Extent of qualification:

Qualification testing and approval to M27/312-26 or M27/316-30, and M27/322-24 shall be sufficient to grant qualification approval to MIL-PRF-27/312 through MIL-PRF-27/322, inclusive, all parts.

Qualification testing and approval to M27/318-30 shall be sufficient to grant qualification approval M27/318-01 through M27/318-30.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:09Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-PRF-27, this document references the following:

MIL-STD-202-211

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5950-2017-020)

Review activities:
Army – AR, CR4
Navy - AS, MC, OS, SH
Air Force - 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:09Z
Check the source to verify that this is the current version before use.