INCH-POUND

MIL-PRF-27/319C
AMENDMENT 1
27 July 2017
SUPERSEDING
MIL-PRF-27/319C
1 October 2010

PERFORMANCE SPECIFICATION SHEET

TRANSFORMERS, POWER, 120 VOLT-AMPERES, 60 HERTZ

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the transformer described herein shall consist of this document and the latest issue of specification MIL-PRF-27.





FIGURE 1. Dimensions and configurations.


AMSC N/A

FSC 5950


Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:10Z
Check the source to verify that this is the current version before use.



DASH NUMBERS 04 THRU 29



DASH NUMBERS 01, 02, AND 03



CIRCUIT DIAGRAM

Dim	Inches	mm	Dim	Inches	mm
A	3.44 ±.031	87.38 ±0.79	J	.470 ±.031	11.94 ±0.79
B	.190-32 UNF-2B (4 PLACES) 8 FULL THDS min.		K	4.50	114.3
C	2.50 ±.016	63.5 ±0.41	L	.070 ±.005	1.78 ±0.13
D	2.88 ±.031	73.15 ±0.79	M	.062 ±.005	1.57 ±0.13
E	2.25 ±.016	57.2 ±0.41	N	.188 ±.005	4.78 ±0.13
F	.875 DIA	22.22 DIA	O	.094 ±.005	2.39 ±0.13
G	1.063 DIA	27.00 DIA	P	.080 ±.005	2.03 ±0.13
H	.375 ±.031	9.52 ±0.79			

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking shall be on the sides of the case.
4. Unless otherwise specified, tolerance shall be ±.063 (1.60 mm).
5. Electrical values shall be marked as specified in table I, except DCR.
6. The mounting surface can be painted.

FIGURE 1. Dimensions and configurations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:10Z
Check the source to verify that this is the current version before use.

REQUIREMENTS: (When numbers in parentheses, i.e., (1-2) are used, they indicate the winding and the extreme terminals of the winding.)

Electrical ratings:

Primary voltage (1-2): 115 volts ac, 50 to 60 hertz.

Primary dc resistance: 1.9 ohms ±25 percent.

Secondary voltage (3-5): See table I.

Volt-ampere rating: 120 volt-amperes.

Working voltage (1-2): 535 volts peak.

Design and construction:

Dimensions and configuration: See figure 1.

Duty cycle. Continuous.

Case: Metal enclosed.

Material: Steel.

Terminals: Solderable terminals.

Dash numbers	Terminal type	Height (inches)	Diameter (inches)
01, 02, and 03	Hook	0.473 ±.031	0.080 ±.005
04 through 29	Hook	0.375 ±.031	0.062 ±.005

Weight: 5.0 pounds, maximum.

Operating temperature range. -55° to +130°C.

Altitude: 10,000 feet.

Terminal strength: MIL-STD-202-211, test condition A, 2.0 pounds.

Dielectric withstanding voltage (each winding) (at sea level): 1,500 volts rms.

Electrical characteristics:

Rated load: With 115 volts ac and 60 Hz across (1-2), and rated current in secondary, the voltage across (3-5) shall be as specified in table I.

Regulation: $\frac{Voltage\,(no\ load) - Voltage\,(rated\ load)}{Voltage\,(rated\ load)}\ x\ 100$

Shall not exceed 10 percent.

Polarity: Additive with terminals 2 and 3 connected.

Temperature rise: 35°C with 115 volts ac, 60 hertz across (1-2) at an ambient temperature of 95°C, full load terminals (3-5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:10Z
Check the source to verify that this is the current version before use.

Marking location: See figure 1.

Part or Identification Number (PIN): M27/319-(dash number from table I).

TABLE I. Electrical ratings.

Dash number M27/319-	Secondary (3-5)		
	Voltage (volts) ±3 percent	Current 1/ (amperes)	DC resistance (ohms) ±25 percent
01	6.3	19.00	.012
02	8.0	15.00	.018
03	10.0	12.00	.031
04	12.6	9.53	.041
05	14.0	8.59	.055
06	16.0	7.50	.072
07	18.0	6.68	.080
08	20.0	6.00	0.120
09	22.0	5.45	0.125
10	25.0	4.80	0.182
11	28.0	4.29	0.205
12	31.0	3.87	0.310
13	35.0	3.43	0.350
14	39.0	3.07	0.342
15	43.0	2.79	0.480
16	48.0	2.50	0.660
17	55.0	2.18	0.820
18	63.0	1.91	1.11
19	70.0	1.72	1.20
20	80.0	1.50	1.43
21	90.0	1.34	1.96
22	100	1.20	2.75
23	110	1.09	3.05
24	123	0.970	4.35
25	138	0.870	4.85
26	157	0.760	5.45
27	175	0.685	7.60
28	200	1.600	8.80
29	220	0.546	12.1

1/ For 50 Hz operation, reduce secondary current by 10 percent.

VERIFICATION:

Extent of qualification:

Qualification testing and approval to M27/312-26 or M27/316-30, and M27/322-24 shall be sufficient to grant qualification approval to MIL-PRF-27/312 through MIL-PRF-27/322, inclusive, all parts.

Qualification testing and approval to M27/319-29 shall be sufficient to grant qualification approval M27/319-01 through M27/319-29.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:10Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-PRF-27, this document references the following:

MIL-STD-202-211

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5950-2017-021)

Review activities:
Army – AR, CR4
Navy - AS, MC, OS, SH
Air Force - 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:10Z
Check the source to verify that this is the current version before use.