MIL-E-1/358B
7 August 1970
SUPERSEDING
MIL-E-1/358A
21 January 1959

MILITARY SPECIFICATION SHEET

# ELECTRON TUBE, RECEIVING

## TYPE 6AJ5

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

DESCRIPTION: RF pentode, low voltage, sharp cutoff

| | | |
|---|---|---|
| Outline | --- | 5-1 (EIA) See note 1 |
| Base | --- | E7-1 |
| Envelope | --- | T5-1/2 |
| Cathode | --- | Coated unipotential |

Base connections:

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Pin No. | --- | 1 | 2 | 3 | 4 | 5 | 6 | 7 |
| Element | --- | g1 | k, g3 | h | h | a | g2 | k, g3 |

ABSOLUTE-MAXIMUM RATINGS:

| Parameter: | Ef | Eb | Rk | Ec2 | Ik | Pg2 | Pp | Ⓑ Ehk | Ⓑ Alt |
|---|---|---|---|---|---|---|---|---|---|
| Unit: | V | Vdc | Ohms | Vdc | mAdc | W | W | v | ft |
| Maximum: | 6.9 | 200 | --- | 155 | 20 | 0.55 | 1.85 | 100 | (See note 2) |
| Minimum: | 5.7 | --- | --- | --- | --- | --- | --- | --- | --- |
| TEST CONDITIONS: | 6.3 | 28 | 200 | 28 | --- | --- | --- | --- | --- |

## GENERAL

Qualification - Not required

Ⓑ denotes changes



Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:15Z
Check the source to verify that this is the current version before use.

| METHOD | REQUIREMENT OR TEST | CONDITION | AQL (PERCENT DEFECTIVE) | INSPECTION LEVEL OR CODE | SYMBOL | LIMITS MIN | LIMITS MAX | UNIT |
|---|---|---|---|---|---|---|---|---|
| | Quality conformance inspection, part 1 | | | | | | | |
| 1266 | Total grid current | Eb = Ec2 = 50 Vdc, Ec1 = -2 Vdc (see note 4) | 0.65 | II | Ic1 | 0 | -0.25 | µAdc |
| 1256 | Electrode current (1) (anode) | | 0.65 | II | Ib | 1.8 | 4.0 | mAdc |
| 1256 | Electrode current (2) (anode) | Ec1 = -5 Vdc; Rk = 0 | 0.65 | II | Ib | 0 | 50 | µAdc |
| 1306 | Transconductance (1) | See note 3 | 0.65 | II | Sm | 2,000 | 3,500 | µmhos |
| 1306 | Transconductance (2) | Ef = 5.7 V (see note 3) | 0.65 | II | ΔSm | --- | 11 | % |
| (B) 1201 | Short and discontinuity detection | | 0.4 | II | --- | --- | --- | --- |
| | Quality conformance inspection, part 2 | | | | | | | |
| 1031 | Low-frequency vibration | Rp 10,000 ohms | --- | --- | Ep | --- | 600 | mVac |
| 1301 | Heater current | | --- | --- | If | 160 | 190 | mA |
| 1336 | Heater-cathode leakage | | --- | --- | Ihk | 0 | 20 | µAdc |
| 1256 | Electrode current (screen) | | --- | --- | Ic2 | 0.1 | 2.0 | mAdc |
| 1331 | Direct-interelectrode capacitance | Shield No. 316 | --- | --- | Cg1p | --- | 0.020 | pF |
| | | Without shield | | | Cin | 3.6 | 4.6 | pF |
| | | Without shield | | | Cout | 1.6 | 2.4 | pF |
| (B) 1121 | Base strain | | --- | --- | --- | --- | --- | --- |
| (B) 2126 | Glass strain | | 4.0 | I | --- | --- | --- | --- |
| (B) 1105 | Permanence of marking | | --- | --- | --- | --- | --- | --- |
| | Quality conformance inspection, part 3 | | | | | | | |
| --- | Life-test provisions | Group A, Ehk = 100 V, Eb = Ec2 = 120 Vdc, Rk = 750 ohms | --- | --- | --- | --- | --- | --- |
| --- | Life-test end point (500 hours) | Transconductance (1) | --- | --- | Sm | 1,800 | --- | µmhos |

NOTES:

1. Outline 5-1 (EIA) except, seated height equals 1-1/2 inches (38.10 mm) and bulb length from base to point where bulb is 3/8-inch (9.53 mm) equals 1.12 ± .10 inches (28.45 ± 2.54 mm).
2. See "Reduced pressure (altitude) rating", and altitude, maximum peak voltage.
3. This test to be performed at the conclusion of the holding period.



Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:15Z
Check the source to verify that this is the current version before use.

NOTES: -Continued

4. Approved alternate test: The insertion of a 2.7 Meg resistor in the grid circuit shall not change the anode current more than 1.0 mAdc.

Custodians:
Army - EL
Navy - EC
Air Force - 80

Review activities:
Army - EL
Navy -
Air Force - 11, 17, 80
DSA - ES

User activities:
Army - WC
Navy - AS, OS, MC, CG, SH
Air Force - 19

Preparing activity: Navy - EC

Agent: DSA - ES

(Project 5960-2425-23)



Source: https://assist.dla.mil -- Downloaded: 202610-15T13:15Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:15Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
NAVAL ELECTRONIC SYSTEMS COMMAND
WASHINGTON, D. C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-15T13:15Z
Check the source to verify that this is the current version before use.

# SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

S/N-0102-014-1801 C-25254

Source: https://assist.dla.mil -- Downloaded: 202610-15T13:15Z
Check the source to verify that this is the current version before use.