INCH POUND
MIL-PRF-1/302N
10 July 1998
SUPERSEDING
MIL-E-1/302M
20 February 1981

PERFORMANCE SPECIFICATION SHEET

ELECTRON TUBE, POWER
TYPE 8112

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the electron tube described herein shall consist of this document and the latest issue of MIL-PRF-1.

DESCRIPTION: Tetrode, metal-glass and ceramic
See figure I
Mounting position: Any
Weight: 6 ounces nominal

ABSOLUTE RATINGS: F1 (CW) = 500 MHz, F1 (pulsed) = 1,500 MHz

Parameter:	Ef	eb	Eb	ec1	Ec1	ec2	Ec2	Ib	ik	cooling
Unit:	Vac	kv	V dc	v	V dc	kv	V dc	mA dc	a	note 1
Maximum: (notes 1 and 2)										
Class C Telep:	2.5 ± 5%	- - -	1,000	- - -	-250	- - -	300	200	- - -	- - -
Class C Teleg:	2.5 ± 5%	- - -	1,250	- - -	-250	- - -	300	250	- - -	- - -
Class C Pulsed:	2.5 ± 5%	7.0	- - -	-500	- - -	1.5	- - -	- - -	7	- - -
Test conditions:	2.5	- - -	1,000	- - -	Adj	- - -	300	150	- - -	note 3

ABSOLUTE RATINGS: F1 (CW) = 500 MHz, F1 (pulsed) = 1,500 MHz

Parameter:	tp	Pg1	Pg2	Pp	Pi	tk	T (ceramic seals and anode core)	T (glass seal)
Unit:	µs note 4	W	W	W	W	sec (min)	°C	°C
Maximum: (notes 1 and 2)								
Class C Telep:	- - -	2	12	165	200	30	250	150
Class C Teleg:	- - -	2	12	250	312	30	250	150
Class C Pulsed:	5	2	12	250	312	30	250	150
Test conditions:	- - -	- - -	- - -	- - -	- - -	120	- - -	- - -

GENERAL:
Qualification - Required

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:12Z
Check the source to verify that this is the current version before use.

Table 1. Testing and Inspection.

Inspection	Method	Conditions	Acceptance Level	Inspection Level or Code	Symbol	Limits Min	Limits Max	Units
Conformance inspection, part 1								
Pulse emission (1)	2212	Eb = Ec2 = 250 V dc; Ec1 = -100 V dc; egk/ik = 1.5 a; prr = 11.0 ± 1.0; tp = 4,500 µs (min); Ef = 2.25 V ac	0.65	II	Δik	- - -	200	ma
Current division (long pulse, Method A)	1372	Eb = Ec2 = 250 V dc; Ec1 = -100 V dc; egk/ib = 1.0 a; prr = 11.0 ± 1.0; tp = 4,500 µs (min)	0.65	II	egk ic1 ic2	8 - - - - - -	18 200 260	v ma ma
Electrode current (screen)	1256		0.65	II	Ic2	-5.0	+3.0	mA dc
Electrode voltage (grid)	1261		0.65	II	Ec1	-32	-45	V dc
Total grid current	1266	Eb = 2,000 V dc; Ib = 125 mA dc	0.65	II	Ic1	- - -	-15	µA dc
Primary grid emission (control)	1266	Ic1 = 70 mA dc; t = 15; anode and screen grid floating	0.65	II	Isg1	- - -	-25	µA dc
Primary grid emission (screen)	1266	Ec1 = 0; Ic2 = 100 mA dc; t = 15; anode floating	0.65	II	Isg2	- - -	-250	µA dc
Heater current	1301		0.65	II	If	6.20	7.30	Aac
Conformance inspection, part 2								
Low-frequency vibration	1031	No voltages applied	- - -	- - -	- - -	- - -	- - -	- - -
Bump	1036	Angle = 20°	- - -	- - -	- - -	- - -	- - -	- - -
RF useful output power	2214	Class C amplifier; F = 460 to 490 MHz; Eb = 1,250 V dc; Ec1 = -90 V dc; Ec2 = 250 to 300 V dc; Ic1 = 20 mA dc (max); Eg1/1b = 250 mA dc; Ef = 2.30 V ac (see note 5)	- - -	- - -	Po	145	- - -	W useful
Direct-interelectrode capacitance	1331	Grounded grid	- - -	- - -	Cpk Cin Cout	- - - 14.5 4.0	0.010 19.00 4.90	pF pF pF

See notes at end of Table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:12Z
Check the source to verify that this is the current version before use.

Table 1. Testing and Inspection. -Continued

Inspection	Method	Conditions	Acceptance Level	Inspection Level or Code	Symbol	Limits Min	Limits Max	Units
Conformance inspection, part 2 Continued.								
Direct-interelectrode capacitance	1331	Grounded cathode	- - -	- - -	Cgp Cin Cout	- - - 25.0 4.00	0.050 29.0 4.90	pF pF pF
Pulse emission (2)	2212	Eb = Ec2 = 250 V dc; Ec1 = -100 V dc; egk/ik = 1.5 a; prr = 11.0 ± 1.0; tp = 4,500 µs (min); Ef = 2.50 V ac	- - -	- - -	Δik	- - -	100	ma
Conformance inspection, part 3								
Pulse emission (2)	2212		- - -	- - -	Δik	- - -	100	ma
Primary grid emission (control)	1266		- - -	- - -	Isg1	- - -	-100	µA dc
Primary grid emission (screen)	1266		- - -	- - -	Isg2	- - -	-250	µA dc
Life-test (2) provisions	- - -	Group C; Ec1 = Ec2 = Eb = 0; Ef = 2.75 V ac; t = 500 hours	- - -	- - -	- - -	- - -	- - -	- - -
Life-test (2) end points:	- - -							
Interelement leakage resistance	1366	supply voltage = 500 V dc; Rs = 2.5 Meg; anode positive see note 6	- - -	- - -	Rg1g2 Rg2k Rg1k	10 10 10	- - - - - - - - -	Meg Meg Meg
Humidity	1011	see note 7	- - -	- - -	- - -	- - -	- - -	- - -
Post-humidity end point:	- - -							
Total grid current	1266		- - -	- - -	Ic1	- - -	-20	µA dc

Pulse-power output	- - -	Eb = 7 kv;
		ib = 6a;
		ec2 = 1.2 kv;
		tp = 5 µs;
		prr = 1,000;
		F = 1,200 ± 50 MHz
		see note 7
			- - -	- - -	po	17	- - -	kw

See notes at end of Table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:12Z
Check the source to verify that this is the current version before use.

NOTES

1. Forced-air cooling shall be provided for the base and anode. The maximum seal and anode core temperature ratings shall not be exceeded. At an anode dissipation of 250 watts and an incoming air temperature of 25°C maximum, a minimum airflow of 5.6 cfm at sea level shall pass through the anode cooler. With no voltages applied to the tube, the static pressure drop across the anode cooler with airflow of 5.6 cfm, at 25°C sea level, is 0.32 inch of water maximum. The pressure drop varies with the amount of escaping air and with the shape and construction of air director. This airflow requirement applies at bias voltages less than 100 Volts and at frequencies less than 500 MHz (CW) and 1,500 MHz (pulsed). Air cooling on the tube shall be increased with with increased negative grid bias, increased incoming air temperature, or increased frequency of operation. The stem shall be cooled either by a portion of the anode air or by a separate air supply. The airflow shall be applied before or simultaneously with them.

2. The transit-time heating effect of the cathode shall be compensated by a reduction in heater voltage after dynamic operation of the tube has started. The back heating is a function of frequency, grid current, grid bias, and duty cycle. For satisfactory life the heater voltage shall be adjusted to the value indicated below. The rated variation of ±5 percent Ef shall apply to the value selected from this table. Conditions of operation are limited to those which indicate a heater voltage of 2.3 Volts or more.

FREQUENCY (MHz)	Ef (V ac)
Up to 400	2.5
401 to 1,000	2.2
1,000 to 1,500	2.0

3. In all electrical tests involving application of heater voltage, forced-air cooling of the tube shall be allowable at the rate of 6.0 cfm, maximum for the base and anode. A separate source shall be used for the base and anode but neither shall exceed 6.0 cfm. The cooling air shall not have a temperature less than 20° C, nor an absolute pressure greater than 32 in. Hg.

4. With a prr of 1,000 or less and a tp of 5 µs or less, ib shall be limited to 6.0 amperes. For pulses of longer duration or higher repetition rates, ib shall be reduced in accordance with the data contained on figure 2.

5. Use cavity and circuit as shown on Drawing 224-JAN.


6. This test shall be made 30 minutes after Ef is turned off. Rated airflow shall be maintained during the 30-minute interval. Measurement to be made with General Radio Megometer No. 1862C, or equivalent. Unused elements are to be left floating.

7. This test shall be performed yearly. A regular double sampling plan shall be used, with the first sample of three tubes with an acceptance number of zero, and a second sample of three tubes with a combined acceptance number of one. In the event of failure, the test will be made as a part of conformance inspection, part 2, acceptance level 6.5, inspection level S3. The regular yearly double sampling plan may be reinstated after three consecutive samples have been accepted.

8. Reclaimed materials shall be utilized to the maximum extent possible.

9. The tube manufacturer warrants the tube for one year from the date of shipment, or 750 hours of heater on time, whichever first elapses. This warranty applies only when the tube is operated within the maximum ratings (see “Absolute Ratings” of MIL-E-1). A defective tube shall either be replaced, or at the option of the manufacturer, a credit shall be made in the amount of the original purchase price pro-rated on the basis of 750 hours of heater on-time.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:12Z
Check the source to verify that this is the current version before use.




Dimensions in inches with metric equivalents (mm) in parentheses			
Ltr	Minimum	Maximum	Notes
Conformance inspection, part 2			
A		2.750 (69.85)	
B	1.615 (41.02)	1.635 (41.53)	
D	1.417 (35.99)	1.433 (36.40)	
E	0.587 (14.91)	0.597 (15.16)	
F	0.317 (8.05)	0.327 (8.31)	
G	0.088 (2.24)	0.098 (2.49)	
Conformance inspection, part 3 (See note 4)			
C		1.406 (35.71)	
H		0.313 (7.95)	
J	0.719 (18.26)	0.781 (19.84)	2
K	0.750 (19.05)	0.813 (20.65)	
L	0.188 (4.78)		2
M	0.500 (12.70)	0.578 (14.68)	
N	0.234 (5.94)	0.266 (6.76)	
P	0.031 (0.79)	0.063 (1.60)	
T	0.344 (8.74)		2
U	0.406 (10.31)		2
V	0.469 (11.91)		2
Reference dimensions			1
R	0.094 (2.39)		
S	0.125 (3.18)		

NOTES:

1. Reference dimensions are for information only and are not required for inspection purposes.
2. Available contact length.
3. Dome contour shall be such that it will be contained within crosshatch area of template shown on figure 3. Optical comparator techniques are normally used for this purpose.
4. See note 7 Table I.

FIGURE I. Outline drawing of electron tube type 8172.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:12Z
Check the source to verify that this is the current version before use.



Pulse anode current (ib) capability is dependent on pulse length (tp) and duty factor (Du). Maximum ib for a given tp is shown; maximum Du may then be derived from the relationship: $0.25 = ib\sqrt{Du}$

PULSE DERATING CHART

FIGURE 2. Pulse anode current versus pulse length.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:12Z
Check the source to verify that this is the current version before use.




FIGURE 3. Contour template of dome shape.

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - AR, CR4
Navy - AS, CG, MC, OS, SH
Air Force - 11, 17, 80, 99

Preparing activity:
DLA - CC

(Project No. 5960-3453)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:12Z
Check the source to verify that this is the current version before use.