MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING
TYPES 3Q4 AND 3V4

This amendment forms a part of Military Specification Sheet MIL-E-1/343B, dated 4 February 1972, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

ABSOLUTE-MAXIMUM RATINGS: Delete "Altitude" in its entirety.

GENERAL: Delete "Qualification-Required" and substitute "Qualification-Not required."

PAGE 2

Quality conformance inspection, part 1, Method 1251, Audio frequency noise and microphonics, delete method 1251 and all columnar data and substitute:

Method	Requirement or test	Notes	Conditions	AQL (percent defective)	Inspection level or code	Symbol	Limits		Unit
							Min	Max	
1246	Audio frequency noise	1	Ecal (0 vu)= 2.63 Vac; Ecal (50 mW)= 400 mVac; Rg1 = 0.1 meg; Rg2 = 1,000 ohms; Ecc2 = 55 Vdc; Rp = 25,000 ohms; Ef = 2.8 Vdc	1.0	II	EB	---	0	vu

Quality conformance inspection, part 1, Method 1201, Short and discontinuity detection, under conditions column: Add "40 G".

Custodians:
Army - EL
Navy - EC
Air Force - 85

Review activities:
Air Force - 99
DLA - ES

User activities:
Army - WC, AV
Navy - AS, OS, MC, CG
Air Force - 11, 19,

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5960-3154)

☆U.S. GOVERNMENT PRINTING OFFICE 1977 - 703 020/5383

3Q4, 3V4

FSC 5960

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:14Z
Check the source to verify that this is the current version before use.