MIL-C-26485D (USAF)
AMENDMENT 4
30 JUNE 1981
SUPERSEDING
AMENDMENT 3
15 JUNE 1960

MILITARY SPECIFICATION

CONTROL ASSEMBLY, ATTITUDE, GYROSCOPIC AF/A24G-1A

This amendment forms a part of Military Specification MIL-C-26485D (USAF), dated 7 November 1968.

PAGE 1

2.1, under SPECIFICATIONS, Federal: Delete "QQ-P-416

Add:

"PPP-B-601	Boxes, Wood, Cleated Plywood
PPP-B-636	Box, Shipping, Fiberboard

2.1, under SPECIFICATIONS, Military: "MIL-P-116", title should read: "Preservation-Packaging, Methods of"; "MIL-C-5541", title should read: "Chemical Conversion Coatings on Aluminum and Aluminum Alloys"; "MIL-P-7788", title should read: "Panels, Information, Integrally Illuminated"; "MIL-F-15160", should read: "MIL-F-15160/3 Fuse, Instrument, Power and Telephone (Nonindicating), Style Fo3". Delete "MIL-D-25521" and substitute: "MIL-D-26503 Detector, Magnetic, Azimuth and Compensator, Detector Magnetic Azimuth". Add: "MIL-C-83488 Coating, Aluminum Ion Vapor Deposited".

Add boxed paragraph to bottom center of page.

"Beneficial comments (recommendation, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Hq AFLC CASO/LODS, Federal Center, Battle Creek MI 49016 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

PAGE 2

2.1, under "STANDARDS, Military": MIL-STD-143", title should read "Standards and Specifications, Order of Precedence for the Selection of". Delete "MS24534 Meters, Time Totalizing, Round (Indicator, Elapsed Time)". Delete "MS33586 Metals, Definition of Dissimilar" and substitute: "MIL-STD-889 Dissimilar Metals".

FSC 6615

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:41Z
Check the source to verify that this is the current version before use.

3.1: Delete and substitute the following:
"3.1 First article. When specified, the contractor shall furnish sample units for first article inspection and approval (see 4.2)".

PAGE 3

3.4.2.1: Delete "MS 33586" and substitute "MIL-STD-889".

3.6.a: Temperatures should read: "-56° to +98°C (-63° to +208°F)".

PAGE 4

3.6.n: Delete "8" and substitute "eight"; also temperatures should read: "85° ± 5°C (185° ± 9°F) and 5° ± 4°C (41° ± 7°F)."

PAGE 5

Figure 1: Add the following: "NOTE: THE INSTALLATION INSTRUCTIONS SHALL BE PLACED ON THE FORE AND AFT ENDS OF CASE".

PAGE 10

3.8.1.5, line 10: Delete "8 CT's" and substitute "eight control transformers".

PAGE 14

3.8.2.4, line 6: Delete "8 CT's" and substitute "eight control transformers".

PAGE 16

3.8.2.8: Temperatures should read: "-54° to +71°C (-65° to +160°F)".

3.8.4: Delete "26-½" and substitute "26.50".

PAGE 17

3.8.7: Delete "MS 24534-3D" and substitute "MS 17322". Also delete "3000 hours" and substitute "10,000 hours".

PAGE 27

3.10.11: Delete "7-½" and substitute "7.25", also delete "8-½" and substitute "8.50".

Source: https://assist.dla.mil -- Downloaded: 20260-20T09:41Z
Check the source to verify that this is the current version before use.

PAGE 32

3.11.c: Delete "1-1/4" and substitute "1.25".

3.13.3: "MIL-F-15160" should read: "MIL-F-15160/3".

PAGE 33

3.15.1.1, line 3: Temperature should read, "dewpoint -65°C (-85°F)".

PAGE 34

3.18.2: Delete and substitute the following:
"3.18.2 Steel parts. Steel parts shall be coated with ion vapor deposited aluminum, where practicable, in accordance with MIL-C-83488, type I or II as applicable and of a class that is adequate to achieve the degree of protection required. Other protective coating, in lieu of MIL-C-83488, may be used if demonstrated to be satisfactory and approved by the preparing activity. Cadium plating must be avoided when satisfactory alternative processes can be used".

Add new paragraph 3.21:
"3.21 Reclaimed materials. The use of reclaimed materials shall be encouraged to the maximum extent possible without jeopardizing the intended end use of the item."

PAGE 35

4.2.a: Delete "Preproduction" here and throughout the rest of section 4 and substitute "First article".

4.2.b: Delete "acceptance test" and substitute "Quality conformance tests".

PAGE 40

4.3.1.3.1: Delete "MIL-D-25521" and substitute "MIL-D-26503".

PAGE 42

4.3.1.5.3: Delete "MIL-D-25521" and substitute "MIL-D-26503". Also delete "The DT-173/AJN" and substitute "A DT-309/AJN or DT-310/AJN".

4.3.2: Change temperature to read "(Approximately 25°) (77°F)".

PAGE 44

4.3.3.e: Delete "Attitude e" and substitute "attitude d".

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:41Z
Check the source to verify that this is the current version before use.

4.5: Delete "Acceptance tests. Acceptance" and substitute "Quality conformance tests. Quality conformance".

PAGE 51

4.5.2.3: Delete "3" and substitute "three".

PAGE 54

4.6.6.3, line 2: Delete "J" and substitute "j".

PAGE 56

4.6.10, 4.6.11, and 4.6.13: The reference in all paragraphs to "4.3.3.d" and should read "4.3.3.c".

PAGE 57

4.6.15, 4.6.16, and 4.6.17: The reference of all paragraphs to "4.3.3.d" should read "4.3.3.c".

4.6.18: Delete "4.3.3.e" and substitute "4.3.3.d".

PAGE 58

4.6.20: Delete "4.3.3.e and 4.3.3.f" and substitute "4.3.3.d and 4.3.3.e".

4.6.21 and 4.6.22: The reference to "4.3.3.d" should read "4.3.3.c".

PAGE 60

4.6.23: The reference to "4.3.3.d" should read 4.3.3.c".

4.6.23.2: The reference to "4.2.23" should read "4.6.23". Also delete "8 hourly" and substitute "eight hourly".

4.6.26, line 4: Delete "15V ac" and substitute "13.5V ac rms within one minute". Line 5: Add "except there shall be no time delay" to the end of the last sentence.

PAGE 61

4.6.27, line 1: Delete "per" and substitute "in accordance with".

PAGE 64

4.6.40, line 5: The reference to "minus" should read "(minus)".

Source: https://assist.dla.mil -- Downloaded: 20260-20T09:41Z
Check the source to verify that this is the current version before use.

PAGE 65

4.6.42, lines 3,4, and 6: The reference to "N" should read "(N)"; also "15" and "345" should read "(15) and (345)".

4.6.44, line 2: The reference to "8" should read "eight".

PAGE 66

4.6.49, lines 4 and 7: The reference to "3 consecutive" should read "three consecutive".

PAGE 69

4.6.62.3.2, lines 2 and 3: The reference to "5 and 7 oscillations" should read "five to seven oscillations"; also the reference to "3 axes", should read "three axes".

4.6.65, line 2: The temperature should read "-54° ± 2°C [-65° ± 4°F)".

PAGE 70

4.6.65.5: Delete "0° ± 45" and substitute "±45".

4.6.66, line 4: The temperature should read "98°C (208°F)".

PAGE 73

4.6.80, line 3: The temperature should read "63°C (145°F)".

4.6.83, lines 2 and 3: The temperature should read "85° ± 5°C (180° ±9°F) and 5° ±4°C (41° ±7°F)".

PAGE 74

Figure 13: The reference to temperatures should read: "-54°C (-65°F) and +71°C (+160°F)".

PAGE 76

Figure 14: The reference to temperatures should read: "+71°C (+160°F)", "+20°C (+68°F)", "-30°C (-22°F)", "-54°C (-65°F)".

PAGE 77

4.6.86.1.c, line 4: The reference to "1.5° ± 0.50 should read "1.5° ± 0.50°".

Source: https://assist.dla.mil -- Downloaded: 20260-20T09:41Z
Check the source to verify that this is the current version before use.

4.6.86.1.c, line 4: The reference to "4.3.3.d" should read "4.3.3.c".

PAGE 78

4.6.86.1.h, line 2: The reference to "4.3.3.d" should read "4.3.3.c".

4.6.86.1.1.1, line 3: The reference to "5 to 7 oscillations" should read "five to seven oscillations".

PAGE 79

Add the following new paragraphs to section 4.:

"4.7 Packaging inspection.

4.7.1 Quality conformance. The inspection of the preservation-packaging and interior package marking shall be in accordance with group A and B quality conformance inspection requirements, section 4 of MIL-P-116. The sampling and inspection of the packing and marking for shipment and storage shall be in accordance with the quality assurance provisions of applicable container specification and the marking requirements of MIL-STD-129.

4.7.2 First article. When the unit container is capable of serving as the shipping container First Article Inspection, and rough handling tests as outlined in section 4 of MIL-P-116, shall be accomplished followed by a functional test of the unit to insure freedom from operational malfunction".

Delete present section 5 and substitute the following:

"5. PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be level A, B, or C as specified by procuring activity (see 6.2).

5.1.1 Level A.

5.1.1.1 Cleaning. Unit shall be cleaned in accordance with process C-1 or MIL-P-116.

5.1.1.2 Drying. Immediately after cleaning, the unit shall be dried following any one or combination of the drying procedures of MIL-P-116. The drying procedures employed shall not be injurious to the unit.

Source: https://assist.dla.mil -- Downloaded: 20260-20T09:41Z
Check the source to verify that this is the current version before use.

5.1.1.3 Preservation application. Not required.

5.1.1.4 Unit packaging. Unless otherwise specified by the procuring activity, each unit shall be packaged in quantity unit packs of one each in accordance with method IIc of MIL-P-116. Overbox each completed pack in a PPP-B-636 fiberboard, weather-resistant class box. Cushioning material between bag and container shall be of type, density, and thickness that will protect the unit from impact shock damage when tested as specified in paragraph 4.7.2 of this specification.

5.1.2 Level B. Each unit shall be packaged as indicated for Level A except that a specification PPP-B-636 class domestic box shall be used as the unit container.

5.1.3 Level C. Units shall be cleaned, dried, and individually packaged in manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from supply source to the first receiving activity.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Units packaged as specified in 5.1 shall be packed in shipping containers conforming to specification PPP-B-636 weather-resistant. Closure and reinforcing requirements shall be in accordance with the appendix of PPP-B-636. For the Army, specification PPP-B-601 plywood box, shall be used for the shipping container. Insofar as practicable, exterior containers shall be of a uniform shape and size and of minimum cube and tare consistent with the protection required.

5.2.2 Level B. Units packaged as specified in 5.1 shall be packed in shipping containers conforming to specification PPP-B-636, class domestic. Closure and reinforcing requirements shall be in accordance with the appendix of PPP-B-636. For the Army, the shipping containers shall conform to specification PPP-B-636 class weather resistant.

5.2.3 Level C. Packaged units shall be packed in shipping containers in a manner that will afford adequate protection against damage during direct domestic shipment from the supply source to the first receiving activity. These packs shall conform to applicable carrier rules and regulations.

5.3 Marking. In addition to any special marking required by the contract or order, each unit package and shipping container shall be marked in accordance with MIL-STD-129".

Source: https://assist.dla.mil -- Downloaded: 20261O-20T09:41Z
Check the source to verify that this is the current version before use.

6.2.d: Delete and substitute the following:
"d. Levels of preservation - packaging and packing desired".

Add paragraph 6.3 as follows:
"6.3 First article. A first article is required for inspection and it shall be tested and approved under the appropriate provisions of 7-104.55 of the Defense Aquisition Regulation. First article tests are described in 4.2. The contracting officer should include specific instructions in all procurement instruments, regarding arrangements for examinations, test and approval of the first article."

Custodian:
Air Force - 99

Preparing activity:
Air Force - 99

Project number
6615-F057

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:41Z
Check the source to verify that this is the current version before use.