INCH POUND
MIL-L-85824A(AS)
AMENDMENT 1
11 May 90

MILITARY SPECIFICATION

LIFE RAFT, INFLATABLE, ONE-MAN, VEE BOTTOM, LRU-18/U

This amendment forms a part of Military Specification, MIL-L-85824A(AS), dated 20 December 1988 and is approved for use within the Naval Air Systems Command, Department of the Navy, and is available for use by all Department and Agencies of the Department of Defense.

Page 1

2.1.1: Under Military Specifications add: "MIL-G-83489, Cloth, Nylon, Polyurethane Coated."

Page 5

3.6: Delete and substitute:

"3.6: Raft Material.

3.6.1 Technical Requirements. Raft shall be made of coated nylon cloth in accordance with MIL-C-83489 Type I except as follows:

a.	Weight	6.0 - 7.0 oz/sq yd
b.	Coating to fabric adhesion	20 lb min.
c.	Coating to coating adhesion	70 lb min. (HARP DIRECTION)
d.	Breaking Strength	
	Warp	190 lb min.
	Fill	160 lb min.
e.	Tearing Strength	
	Warp	4 lb min.
	Fill	3 lb min.

3.6.2. Color. The color of the life raft and components shall be as specified in the applicable drawings."

AMSC N/A FSC 4220
DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T11:30Z
Check the source to verify that this is the currentversion before use.

3.8.2, line 2: Delete “4.75 psig” and substitute “3.75 psig.”

3.8.4, line 2: Delete “4.2 pounds” and substitute “4.0 pounds. ”

Page 6

3.8.7.1, title sentence: Delete entire title sentence and substitute “Low Temperature.”

line 3: Delete “twenty minutes” and substitute “twelve minutes.”

3.8.7.2, title sentence: Delete entire title sentence and substitute “High Temperature. ”

Page 11

4.8.3, lines 6 and 8: Delete “5.0 psig” and substitute “4.0 psig.”

Page 13

4.8.8.1, title sentence: Delete entire title sentence and substitute “Low Temperature Soak.”

line 7: Delete “for not less than 48 hours.” and substitute “for not less than 8 hours, then raise the temperature to 32° ± 2° Fahrenheit (0° ± 1° Celsius) and let stabilize at that temperature for not less than 2 hours.”

4.8.8.2, title sentence: Delete entire title sentence and substitute “High Temperature Soak.”

line 3, Delete “for not less than 48 hours.” and substitute “for not less than 8 hours, then lower the temperature to 105° ± 2° Fahrenheit (35° ± 1° Celsius) and let stabilize at that temperature for not less than 2 hours.”

Page 20

Table IV, Under Critical Defects add:

“9. any stress relief, heat sealable dot that is not in conformance with the dimensions of 3/4 plus, 1/4 minus 0 inches in diameter.”

Preparing Activity:
Navy - AS
(Project 4220-N364)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:30Z
Check the source to verify that this is the current version before use.