[INCH-POUND]
A-A-3026
November 6, 1996

COMMERCIAL ITEM DESCRIPTION

SCRIBER, MACHINISTS'

The General Services Administration has authorized the use of this Commercial Item Description for the procurement of the type II, class 1 and 2, scribers specified in GGG-S-131E for all federal agencies.

1. SCOPE.

1.1 Scope. This Commercial Item Description covers machinists', double-point scribers used for marking lines on steel or other materials in layout work.

2. CLASSIFICATION.

2.1 Classification. The machinists' scriber shall be of the following types.

Type I - Adjustable sleeve
Type II - Removable point

3. SALIENT CHARACTERISTICS.

3.1 Design. The machinists' scriber shall have one straight and one bent tapered point. The straight tapered point shall coincide with the axis of the round body of the scriber, and the bent tapered point shall be at a 90 degree angle from the axis of the scriber with a length of 1/2 inch. The body of the scriber shall be of steel or aluminum alloy and the scribing points shall be of hardened steel and have a hardness of between 55 and 62 on the Rockwell C scale. Tungsten carbide points shall have a hardness of between 91 and 98 on the Rockwell A scale. All metal parts (except scriber points) shall be of a corrosion resistant type material unless otherwise suitably protected to resist corrosion during normal service life.

3.1.1 Adjustable sleeve. The type I adjustable sleeve scriber shall have a straight scribing point of one-piece construction with a knurled adjustable sleeve which has a chuck to secure the sleeve at any desired location along the body of the scribing point. The scriber shall be similar to Figure 1 and conform to the dimensions of Table I.



Figure 1. Type I machinists' scriber, double point, straight and bent, adjustable sleeve.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any other data which may improve this document should be sent to: General Services Administration, Federal Supply Service, Tools and Appliances Commodity Center, Kansas City, MO 64131.

Distribution Statement A. Approved for public release; distribution is unlimited.

FSC 5120

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

TABLE I. Type I, machinists' scriber, double point, straight and bent, adjustable sleeve

Diameter of sleeve (approximate) (Inch)	Length of sleeve (Inches)	Diameter of scribing point body (approximate) (Inch)	Length of scribing point (Inches)
5/16	2-1/2 to 3	5/32	8 to 9

3.1.2 Removable points. The type II removable scriber shall have a knurled body and two removable scribing points. Threaded holes in the two ends of the body shall accept suitably threaded scribing points. If required, extra long bent tapered scribing points shall be ordered (see 7.2). The scriber shall be similar to Figure 2 and conform to the dimensions of Table II.



Figure 2. Type II machinists' scriber, double-point, straight and bent, removable.

TABLE II. Type II machinists' scriber, double point, straight and bent, removable

Diameter of handle (Inch)	Length of handle (Inches)	Diameter of scribing point body (Inch)	Total length with short bent point (assembled) (Inches)	Total length with both points (assembled) (Inches)
1/4 to 5/16	2-1/2 to 3-1/4	1/8 to 3/16	8 to 9	12 to 13

3.2 Identification marking. The tool shall be marked with the manufacturer's name or identifying symbol and the state or country of manufacture, unless otherwise specified. All identification markings shall be engraved, etched, molded, or indented directly on the item's surface in such a manner that it remains clearly legible throughout the life of the item.

3.3 Workmanship. Details of workmanship shall be in accordance with the best commercial practice. Paints, coatings, platings, and finishes shall be smooth, adherent, continuous, and not stained or discolored. External surfaces shall be free of tool and gouge marks, nicks, or other surface imperfections. The item shall be free from manufacturing workmanship defects (e.g., sharp or rough external edges, corners, or surfaces) and material workmanship defects (e.g., pits, rips, fins, burrs, tears, nodules, cracks, blisters) which may adversely impact the item's serviceability, durability, safety, or appearance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

4. REGULATORY REQUIREMENTS.

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4.2 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified (using conversion tables contained in the latest revision of Federal Standard 376) and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

5. QUALITY ASSURANCE PROVISIONS.

5.1 Product conformance. The product provided to the Government shall conform to the contractually specified requirements. For product characteristics and requirements which are not contractually specified, the provided product shall conform to the producer's own drawings, standards, specifications, and quality assurance practices for the highest quality product commercially offered by the producer. If the product is not commercially offered by the producer, the best commercial practices shall apply. The Government reserves the right to require proof of such conformances prior to first delivery and thereafter as provided for under the provisions of the contract.

5.2 Responsibility for inspection. Unless otherwise specified, the contractor is responsible for the performance of all inspection requirements and may use any commercial facilities (including the contractor's own facilities) suitable for performance of the inspection requirements, unless disapproved by the Government. The Government reserves the right to perform any inspections deemed necessary to assure the item conforms to the specified requirements.

5.3 Bid sample(s). When a bid sample requirement is specified in the solicitation, the bid sample(s) shall be inspected for all salient characteristics by the Government. A failure of any bid sample to meet the salient characteristics shall be cause for rejection.

5.4 First article sample(s). When a first article requirement is specified in the contract, the first article sample(s) shall be inspected for all salient characteristics. A failure of any first article sample to meet the salient characteristics shall be cause for rejection.

6. PACKAGING.

6.1 Packaging. Requirements of preservation, packing, packaging, and marking of packages shall be as specified in the contract or order.

7. NOTES.

(This section contains information of a general or explanatory nature that is not mandatory.)

7.1 Addresses for obtaining copies of referenced documents:

Federal Specifications and Standards: Federal Supply Service Bureau, Specification Section, Suite 8100, 470 L'Enfant Plaza, SW, Washington, DC 20407.

Federal Acquisition Regulations (FAR): Government Printing Office, Superintendent of Documents, Washington, DC 20402-9371.

ANSI/ASQC Z1.4: American Society for Quality Control, P.O. Box 3005, 611 East Wisconsin Avenue, Milwaukee, WI 43201-4606.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

7.2 Ordering data. Purchasers should select the preferred options permitted herein and should include the following information in procurement documents:

(a) Title, number, and date of this Commercial Item Description.
(b) When applicable, the appropriate NSN(s).
(c) When applicable, the specific types, as specified in the Commercial Item Description.
(d) If bid samples are required, the number of samples required, and the subjective inspection requirements.
(e) If first article samples are required and the number of samples required.
(f) If lot sampling inspection is required and the applicable lot sampling requirements. For example:

Sampling for inspection. Sampling for inspection (both examinations and testing) shall be in accordance with ANSI/ASQC Z1.4.

Inspection. Each sample tool shall be examined and tested for all salient characteristics. The Inspection Level shall be S-2 with an Acceptable Quality Level of 4.0, expressed in terms of defects per hundred units.

(g) What preservation, packing, packaging, and marking of packages are required.
(h) If extra long bent tapered scribing point is required (see 3.1.2).

7.3 National Stock Numbers (NSNs). The following list of NSNs corresponds to the types specified in this CID. This list may not be indicative of all possible NSNs associated with this CID.

NSN	TYPE
5120-00-221-7063	Adjustable sleeve
5120-00-596-1543	Removable point

MILITARY INTERESTS:

NONE: DoD has no registered interest in revisions or notices to this Commercial Item Description until further notice.

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:28Z
Check the source to verify that this is the current version before use.