NOT MEASUREMENT SENSITIVE

MIL-B-52690B(ME)
2 June 1994
SUPERSEDING
MIL-B-52690A(ME)
8 July 1987

MILITARY SPECIFICATION

BRACKET, PUSHING, BOW ATTACHMENT, 12-TON

PNEUMATIC HALF FLOAT

This specification is approved for use within the USA Belvoir Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a pushing-bracket for attachment to a 12-ton pneumatic half float for maneuvering with a bridge erection boat.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

PPP-B-601 - Boxes, Wood, Cleated-Plywood.

MILITARY

MIL-T-704 - Treatment and Painting of Materiel.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US ARMY BELVOIR RDE CTR, ATTN SATBE TSE, 10101 GRIDLEY RD STE 104, FT BELVOIR VA 22060-5818 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 5420
AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:29Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of U. S. Military Property.
MIL-STD-889	- Dissimilar Metals.
MIL-STD-1186	- Cushioning, Anchoring, Bracing, Blocking, and Waterproofing with Appropriate Test Methods.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from: STDZN DCMNT ORDER DESK, BLDG 4D, 700 ROBBINS AVE, PHILADELPHIA PA 19111-5094.)

2.1.2 Government drawings. The following Government drawing forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

ME

TA13220E4475	- Bracket, Pushing Assembly, 12-Ton Pneumatic Half Float.

(Copies of drawings required by contractors in connection with specific acquisition functions should be obtained from: USA BELVOIR RDE CTR, ATTN SATBE , JBS, 10101 GRIDLEY RD, STE 104, FT BELVOIR VA 22060-5818.)

2.2 Non-Government publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DoDISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS are the issues of the documents cited in the solicitations (see 6.2).

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Boiler and Pressure Vessel Code, Section IX, Welding Qualifications.

(Application for copies should be addressed to: AMERCN SCTY OF MECHL ENGRS, 345 E 47TH STRET, NEW YORK NY 10017.)

AMERICAN SOCIETY FOR TESTING AND MATERIAL (ASTM)

D 3953	- Strapping, Flat Steel and Seals.
D 4675	- Selection and Use of Flat Strapping Materials.

(Application for copies should be addressed to: AMERCN SCTY FOR TEST & MTRLS, 1916 RACE STRET, PHILADELPHIA PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:29Z
Check the source to verify that this is the current version before use.

AMERICAN WELDING SOCIETY (AWS)

A5.1 - Carbon Steel Covered Arc-Welding Electrodes.
A5.18 - Carbon Steel Filler Metals for Gas Shield Arc Welding.
D1.1 - Structural Welding Code - Steel.

(Application for copies should be addressed to: AMERCN WELD SCTY, 550 NW LEJEUNE RD, PO BOX 351040, MIAMI FL 33135.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT (NMFTA)

National Motor Freight Classification.

(Application for copies should be addressed to: NATL MTR FRGHT TRFC ASS, ATTN TRFC ORDR SECT, 2200 MILL RD, ALEXANDRIA VA 22314.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT (UCC)

Uniform Freight Classification Rules.

(Application for copies should be addressed to: UNFRM FRGHT CLASS CMMTE, ATTN TARIFF PBLSHNG OFCR, ROOM 1106, 222 S RIVERSIDE PLZ, CHICAGO IL 60606.)

(Non-Government standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specification sheets, or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The pushing-bracket shall be as shown in TA13220E4475 and as specified herein.

3.2 First article. Unless otherwise specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.3 Material. Material shall be as specified herein and as shown in TA13220E4475. Material not specified shall be selected by the contractors and shall be subject to all provisions of this specification.

3.3.1 Welding electrodes. Welding electrodes shall conform to AWS A 5.1 or A 5.18, classification and size as required.

3.3.2 Material deterioration prevention and control. The pushing brackets shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable operating and storage environment to which the pushing brackets may be exposed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:29Z
Check the source to verify that this is the current version before use.

3.3.3 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion. Dissimilar metals and methods of protection are defined and detailed in MIL-STD-889. Dissimilar metals shall be protected from one another as called out on the drawings.

3.3.4 Recovered materials. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components in the pushing-bracket may be newly fabricated from recovered materials to the maximum extent practicable, provided the pushing-bracket produced meets all other requirements of this specification. Used, rebuilt, or remanufactured components, pieces, and parts shall not be incorporated in the pushing-bracket.

3.4 Treatment and painting. The pushing-bracket shall be cleaned, treated, and painted in accordance with MIL-T-704, type B.

3.5 Identification marking. The pushing-bracket shall be identified in accordance with MIL-STD-130.

3.6 Workmanship. All parts, components, and assemblies of the pushing bracket, including welded parts shall be clean and free from sand, dirt, fins, pits, sprues, scale, flux, and other harmful, extraneous material. External surfaces shall be free from burrs, sharp edges, and corners, except when sharp edges and corners are required.

3.6.1 Steel fabrication. Steel used in the fabrication of the pushing bracket shall provide original quality surface finish and shall be free from kinks and sharp bends. Steel having an eroded surface is not acceptable. The forming material shall be done by methods that will not cause damage to the metal. Shearing and chipping shall be done neatly and accurately. Corners shall be square and true. Burned surfaces of flame-cut material shall be free of slag. Precautions shall be taken to avoid overheating, and heated metals shall be allowed to cool slowly except where heat treatment is required. All bends of major character shall be made with metal dies or jigs to ensure uniformity of shape.

3.6.2 Welders and welding.

3.6.2.1 Welders or welding operator. Before assigning any welder or welding operator to manual welding work covered by this specification, the contractor shall obtain certification that the welder or welding operator has passed qualification tests as prescribed by either AWS D1.1 or the ASME code for the materials joined and the type of welding operation to be performed and that such qualification is effective as defined. Contractors who only make horizontal welds need not qualify welders for "all position welding". The contractor is responsible for determining that automatic welding equipment operators are capable of producing quality welds in accordance with AWS and ASME codes. In the event of evidence of poor welds, the Government reserves the right to require retesting of any welder or welding operator (see 6.4).

3.6.2.2 Welding. The surface of parts to be welded shall be free from scale, paint, grease, and other foreign matter. Welding shall be done by the shielded

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:29Z
Check the source to verify that this is the current version before use.

metal-arc or gas metal-arc (GMAW) process and shall conform to the provisions of the AWS D1.1. All welded parts shall be free from cracks and other imperfections that may reduce the effectiveness of the part. Work shall be positioned for flat welding when practicable. Before welding over previously deposited weld metal, all traces of slag shall be removed and the deposit and adjoining base metal shall be wire brushed clean.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order and unless disapproved by the Government, the contractor's own facilities or any other, suitable for the performance of the inspection requirements specified herein, may be used. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The contractor is responsible for ensuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.1.2 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection as part of the manufacturing operation, is an acceptable practice to ascertain conformance to requirements. However, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspection. Inspection shall be classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection of packaging (see 4.6).

4.3 First article inspection.

4.3.1 Examination. The first article shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination shall be in accordance with MIL-STD-105. Sample size shall be determined by using MIL-STD-105, table I and table IIa. A lot shall be accepted when zero defects are found and rejected when one or more defects are found.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:29Z
Check the source to verify that this is the current version before use.

4.4.2 Examination. Samples selected as specified in 4.4.1 shall be examined for the following defects. Presence of one or more defects shall be cause for rejection.

4.5 Inspection procedure.

4.5.1 Examination. The pushing-bracket shall be examined for the following defects:

101. Bracket not true to dimensions, lines; contains twists, bends, holes, or other imperfections (see 3.1).
102. Material not as specified (see 3.3).
103. Welding electrodes not as specified (see 3.3.1).
104. Materials are not resistant to corrosion or deterioration or treated to be made resistant to corrosion or deterioration for the applicable storage and operating environment as specified (see 3.3.2).
105. Dissimilar metals as defined in MIL-STD-889 are not effectively insulated from each other as specified (see 3.3.3).
106. Used, rebuilt, or remanufactured components, pieces, and parts are incorporated in the pushing-bracket (see 3.3.4).
107. Treatment and painting not as specified (see 3.4).
108. Workmanship not as specified (see 3.6)
109. Steel or steel surfaces not as specified (see 3.6.1).
110. Welders or welding operators not qualified as specified(see 3.6.2.1).
111. Welding not as specified (see 3.6.2.2).
112. Weld defects such as flux inclusions, spatter, undercutting, porosity, incorrect size, or lack of fusion with parent metal (see 3.6.2.2).
113. Identification marking illegible, incomplete, incorrect, or missing (see 3.5).

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105. Sample size shall be determined by using MIL-STD-105, table I and table IIa. A lot shall be accepted when zero defects are found and rejected when one or more defects are found.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. Presence of one or more defects shall be cause for rejection.

114. Box not close-fitting and in accordance with the referenced document for level A or B (see 5.1.1 and 5.1.2).
115. Components not blocked and braced as specified for level A or B (see 5.1.1 and 5.1.2).
116. Strapping not as specified for level A (see 5.1.1).
117. Marking missing, illegible, incorrect, or incomplete (see 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:29Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. Each complete pushing-bracket shall be packed in a close-fitting box conforming to PPP-B-601, overseas type, style optional. The contents shall be blocked and braced within the box in accordance with MIL-STD-1186. Box closure shall be in accordance with the appendix to the box specification. Strapping shall be in accordance with ASTM D 3953, type 1 or 2, finish B, size as applicable and ASTM D 4675.

5.1.2. Level B. Each complete pushing-bracket shall be packed as specified in 5.1.1 for level A except the box shall be domestic type and strapping may be finish A.

5.1.3 Level C. Each complete pushing-bracket shall be packed in a manner to ensure carrier acceptance and safe delivery to destination at lowest rating in a container complying with Uniform Freight Classification rules or with National Motor Freight Classification rules.

5.2 Marking. Shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES
(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The pushing-brackets are intended for use as attachments to the beam outriggers of 12-ton pneumatic floats and used as a bumper assembly when floats are being maneuvered by bridge erection boats.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Issue of DoDISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. Time frame required for submission of first-produced pushing-bracket (see 3.2.1).
d. Level of packing required (see 5.1).

6.3 First article. When a first article inspection is required, the items should be a first produced pushing-bracket. The first article should consist of one unit. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, tests, and approval of the first article test results and disposition of the first article.

6.4 Consideration of data requirements. The following data requirements should be considered when this specification is applied on a contract. The applicable Data Item Description (DIDs) should be reviewed in conjunction with the specific acquisition to ensure that only essential data are requested/provided and that the DIDs are tailored to reflect the requirements of the specific acquisition. To ensure correct contractual application of the data requirements, a Contract Data

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:29Z
Check the source to verify that this is the current version before use.

Requirements List (DD Form 1423) must be prepared to obtain the data, except where DoD Far Supplement 27.475-1 exempts the requirement for a DD Form 1423.

Reference paragraph	DID Number	DID Title
3.6.2.1	DI-MISC-80876	Welding Procedure Qualification Test Report.
3.6.2.1	DI-MISC-80875	Welding Procedures.

The above DIDs were those cleared as of the date of this specification. The current issue of DoD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL), must be researched to ensure that only current, cleared DIDs are cited on the DD Form 1423.

6.5 Changes from previous issue. Asterisks (or vertical lines) are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

6.6 Subject term (key word) listing.

Bracket pushing
Bow attachment
Pneumatic half float

Custodian:
Army - ME

Review activity:
DLA - CS

Preparing activity:
Army - ME

Project 5420-A397

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-B-526908(ME)	2. DOCUMENT DATE (YYMMDD) 940602

3. DOCUMENT TITLE
BRACKET, PUSHING, BOW ATTACHMENT, 12-TON PNEUMATIC HALF FLOAT

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (if applicable) (2) DSN	7. DATE SUBMITTED

8. PREPARING ACTIVITY

a. NAME Carolyn B. Johnson	b. TELEPHONE (Include Area Code) (1) Commercial (703) 704-3468	(2) DSN 654-3468
c. ADDRESS (Include Zip Code) US ARMY BELVOIR RDE CTR ATTN SATBE TSE 10101 GRIDLEY RD STE 104 FT BELVOIR VA 22060-5818	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: DEFNS QLTY & STDZN OFC 5203 LEESBURG PIKE STE 1403 FLS CHURCH VA 22041-3466 Telephone (703) 756-2340	DSN 289-2340

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:29Z
Check the source to verify that this is the currenversion before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:29Z
Check the source to verify that this is the current version before use.