MILITARY SPECIFICATION

CANISTER, CHEMICAL PROJECTILE: 8 INCH, NM, XM28

This specification is approved for use by US Army Armament Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of filled canister.

2. APPLICABLE DOCUMENTS

2.1 Issue of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

BB-N-411 - Nitrogen, Technical.
BB-H-1168 - Helium, Technical.

MILITARY

MIL-A-2550 - Ammunition and Special Weapons, General Specification For.

FSC 1320

: Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-TSC-S, Aberdeen Proving Ground, MD 21010 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter. :

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:01Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1168 - Lot Numbering of Ammunition.
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes.

DRAWINGS AND TECHNICAL DATA PACKAGE LIST (TDPL)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

CHEMICAL SYSTEMS LABORATORY

TDPL 15-12-156 - Canister, Chemical Projectile: 8 Inch, NM, XM28.

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing TDPL 15-12-156 or on the subsidiary drawings shall conform to the specifications listed thereon, or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the canister shall conform to the specifications and drawings listed on Drawing TDPL 15-12-156 and subsidiary drawings.

3.2 Filling and closing. The canister shall be filled and closed as follows (see 6.3):

(a) Empty canister. Inspect vinyl tape, covering the canister fill port. If tape is punctured or loose so as to prevent the airtight seal, canister shall be removed from filling line for reworking to assure clean, dry canister interior. If tape is acceptable, remove tape and burst disk protective cover and send canister to fill station.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:01Z
Check the source to verify that this is the current version before use.

(b) Purge. Purge the interior of the canister with dry nitrogen, type 1, class 2, grade B of BB-N-411 for 15 seconds at a minimum flow rate of 2 cubic feet per minute (cfm). Immediately after purge cover fill port with clean, dry, tapered teflon plug to maintain purged atmosphere. NOTE: Cover is unnecessary if purge and fill stations are combined or if movement between them is enclosed with the same dry nitrogen atmosphere.

(c) NM filling. Fill the canister with 2.90 ± .10 pounds (1.3 kilograms) of NM (see 6.5) and avoid contamination from foreign material.

(d) Closing (weld). The void over the liquid shall be purged with dry nitrogen, type 1, class 2, grade B of BB-N-411 for 10 seconds at a minimum flow rate of 15 cubic feet per hour (cfh). The weld plug shall be welded in place within 1 minute after nitrogen purge.

3.3 Leakage. The welded closure shall not leak helium, grade A of BB-H-1168, at a rate greater than 1.0×10^{-6} atmospheric cubic centimeters per second under a vacuum of 15 microns of mercury when tested as specified in 4.3.4.1. The preproduction sample of canisters shall be purged in accordance with 3.2(a) except that helium shall be used instead of nitrogen.

3.4 Preproduction. Prior to the start of regular production, a preproduction lot of canisters shall be produced in accordance with this specification for examination and test (see 4.3).

3.5 Workmanship. The canisters shall be free from contamination (NM spillage, (see 6.4) foreign matter, rust, oil or grease) and damage such as dents, cracks or deformation which could affect its intended use and shall conform to the standards of workmanship for parts and assemblies listed in MIL-A-2550.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Contractor's responsibility. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:01Z
Check the source to verify that this is the current version before use.

4.1.2 Objective evidence. The contractor shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Classification of inspections.

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 Preproduction inspection.

4.3.1 Lot. A preproduction lot of 100 canisters shall be filled and closed using the same methods materials, equipment and processes as will be used during regular production (see 6.2).

4.3.2 Sampling. Sampling shall be conducted in accordance with MIL-STD-105.

4.3.3 Inspection procedures. The sample canisters shall be examined in accordance with the classification of defects (4.4.3.3) and MIL-STD-105. Testing shall be conducted in accordance with 4.3.4, and 4.4.4. The acceptance number is zero.

4.3.4 Test. The test shall be conducted as follows:

4.3.4.1 Leakage. The assembled canister shall be placed under a test head connected to a vacuum system and a mass spectrometer type helium leak detector. The test head shall be lowered over the fill port end. The leak detector shall be calibrated to respond to a leak rate of 1.0×10^{-6} atmospheric cubic centimeters per second of helium when a standard leak is introduced.

4.3.5 Acceptance/rejection criteria. The preproduction sample shall comply with the examinations and tests specified in 4.3.3 to be acceptable. The contractor shall obtain written approval from the contracting officer prior to proceeding with regular production.

4.4 Quality conformance inspection.

4.4.1 Lotting. Each lot shall be identified and controlled in accordance with MIL-STD-1168. A lot shall consist of canisters of one interfix number, produced by one manufacturer, from the same materials and under essentially the same manufacturing conditions. Contained in any one lot number of containers, no more than one lot number of the chemical fill is permitted:

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:01Z
Check the source to verify that this is the current version before use.

4.4.2 Sampling.

4.4.2.1 For examination. Sampling shall be conducted in accordance with MIL-STD-105.

4.4.2.2 Weight of fill. Sampling shall be conducted in accordance with MIL-STD-1235, CSP-1, code letter G.

4.4.3 Inspection procedure.

4.4.3.1 For examination. The sample canisters shall be examined in accordance with the classification of defects (4.4.3.3) and MIL-STD-105.

4.4.3.2 Weight of fill. The sample canisters shall be tested in accordance with 4.4.4.1 using an AQL of 1.0 percent defective.

4.4.3.3 Classification of defects.

(a) Canister, chemical projectile: 8 inch, NM, XM28 (Drawing D15-12-156).

Categories		Defects
Critical:		None defined
Major:	AQL 1.0 percent defective	
101		Weld plug position
102		Weld plug height
103		Burst disk damaged
104		Pin incorrectly installed or missing
105		Workmanship (3.5)

(b) Canister, marking, chemical projectile, NM, XM28 (Drawing D15-12-183).

Categories		Defects
Critical:		None defined
Major:	AQL 1.0 percent defective	
101		Marking missing or incorrect

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:01Z
Check the source to verify that this is the current version before use.

4.4.3.3 Classification of defects (continued).

(c) Packaging (section 5).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Fiber containers incorrect
102	Plywood spacer unbonded in tube end
103	Chipboard spacer missing
104	Tape applied incorrectly
105	Marking illegible or missing on tube end
106	Packages placed incorrectly in box
107	Wood box incorrect
108	Filler pads missing
109	Strapping missing or loose
110	Box marking illegible, missing or incorrect

4.4.4 Tests. Tests shall be conducted as follows:

4.4.4.1 Weight of fill. The weight of fill shall be determined by weighing and marking the weight of unfilled canisters at the stated inspection interval (see 4.4.2.2). After filling and closing the sample canisters shall be weighed to the required accuracy to determine the net fill weight.

5. PACKAGING

5.1 Packaging, level A. The canisters shall be packaged in accordance with Drawing D15-12-201.

5.2 Packing.

5.2.1 Level A. Canisters packages as specified in 5.1, shall be packed in accordance with Drawing D15-12-201.

5.3 Marking. Marking shall be in accordance with Drawing D15-12-202 and D15-12-203.

5.4 Palletization. When specified in the contract or order, (see 6.2) shipping containers shall be palletized in accordance with Drawing D15-12-211.

Source: https://assist.dla.mil -- Downloaded: 20261O-22T21:01Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. This item is a component of the XM736 projectile.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) If canisters are to be palletized.
(c) Preproduction.

(1) Time allowed for contractor submission of samples for any Government tests and evaluation after award of contract.
(2) Name and address of test facility and shipping instructions when testing is performed by the Government.
(3) Time required for the Government to notify the contractor whether or not to proceed with production.

6.3 Caution. Due to the hazardous nature of filling canisters with chemicals, contractors are advised to take all necessary precautions to protect personnel during filling and testing.

6.4 NM spillage. Minor NM spillage can be cleaned from the exterior of the canister by using a sodium hypochlorite bleach solution and then flushing with clean water. Massive NM spillage will require cleaning with a solution of calcium hypochlorite, technical conforming to O-C-114 or decontaminating agent, STB conforming to MIL-D-12468 and then flushing with clean water.

6.5 NM filling by height. For production purposes, the canister filling operation may be process controlled by monitoring the fill height, provided the overall fill weight requirement is maintained. The Marton liquid level switch Model 14-03 is one type of liquid level monitor found suitable for checking height of liquid fill (Marton Inc., 1626 East Maywood, Santa Ana, CA 92705). To perform the necessary calculations, the following NM density equation can be used.

Density NM (gm/ml) = 1.379 - .00099T
T = Temperature (°C)

6.6 Supersession data. This specification supersedes Chemical Systems Laboratory Purchase Description, EA-C-1168, dated 14 April 1977.

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 1320-A471

☆U.S. GOVERNMENT PRINTING OFFICE: 1979-603-022/3389

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:01Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-C-51457

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSF OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1426 1 OCT 76

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 20261O-22T21:01Z
Check the source to verify that this is the current version before use.