INCH-POUND

MIL-K-52338B
9 September 1991
SUPERSEDING
MIL-K-52338A(ME)
15 June 1971

MILITARY SPECIFICATION

KEEPER ASSEMBLY: CABLEWAY, MEDIUM

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a keeper assembly for the medium cableway.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards, form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir, Research, Development, and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5420

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-T-704 - Treatment and Painting of Materiel.

STANDARDS

FEDERAL

FED-STD-595 - Colors.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-889 - Dissimilar Metals.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Document Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Government drawings. The following Government drawings form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those in effect on the date of the solicitation.

DRAWINGS

ME

TA13208E5019 - Keeper Assembly: Cableway, Medium.

(Copies of drawings required by contractors in connection with specific acquisition functions should be obtained from the USA Belvoir Research, Development, and Engineering Center, ATTN: STRBE-JBS, Fort Belvoir, VA 22060-5606.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Boiler and Pressure Vessel Code, Section IX, Qualification Standard for Welding and Brazing Procedures, Welders, Brazers, and Welding and Brazing Operators.

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:15Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIAL (ASTM)

D 3953 - Strapping, Flat Steel and Seals.
D 4675 - Selection and Use of Flat Strapping Materials.

(Application for copies shall be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103).

AMERICAN WELDING SOCIETY (AWS)

A5.1 - Covered Carbon Steel Arc Welding Electrodes.
A5.18 - Carbon Steel Filler Metals for Gas Shielded Arc Welding.
D1.5 - Bridge Welding Code.

(Application for copies should be addressed to the American Welding Society, 550 N.W. LaJuene Road, P.O. Box 351040, Miami, FL 33135.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC. (NMFTA)

National Motor Freight Classification Rules.

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Tariff Order Section, 2200 Mill Road, Alexandria, VA 22314.)

UNIFORM CLASSIFICATION COMMITTEE, (UCC)

Uniform Freight Classification Rules.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Non-Government standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The keeper assembly shall be in accordance with TA13208E5019 and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are engineering design drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Any data (e.g. shop drawings, layouts, flow sheets, processing procedures,

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

etc.) prepared by the supplier or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.3 Material. Material shall be as specified herein and as shown on the applicable drawings. Materials not specified shall be selected by the supplier and shall be subject to all provisions of this specification.

3.3.1 Materiel deterioration prevention and control. The keeper assembly shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable operation and storage environment to which the item may be exposed.

3.3.2 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion. Dissimilar metals and methods of protection are defined and detailed in MIL-STD-889.

3.3.3 Identification of materials and finishes. The contractor shall identify the specific material, material finish or treatment for use with component and subcomponent, and shall make information available upon request to the contracting officer or designated representative.

3.4 Welding electrodes. Welding electrodes for structural steel shall conform to AWS A5.1 or A5.18, E60XX series or E70XX series, size as required.

3.5 Identification marking. The keeper assembly shall be metal-die stamped as shown on the applicable drawing. Die stamping shall be legible after painting.

3.6 Cleaning, treatment and painting. The keeper assembly shall be cleaned, treated and painted as specified on the drawings except that the color number designation shall be 24094 or 34094 in accordance with FED-STD-595.

3.7 Stenciling. The nomenclature, Federal stock number, weight and cube shall be stenciled on each keeper assembly. The letters "NET WT" shall precede the numerals in the weight and the letters "CU" shall precede the cubic displacement. The markings shall be Gothic-type capitals and Arabic numerals, 1/2-inch high. Stenciling shall conform to MIL-T-704.

3.8 Workmanship.

3.8.1 Steel fabrication. Steel used in the fabrication of the keeper assembly shall be free from laminations, kinks, and sharp bends. The straightening of material shall be done by methods that will not cause injury

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:15Z
Check the source to verify that this is the current version before use.

to the metal. Corners shall be square and true. Flame cutting with a tip suitable for the thickness of metal may be employed instead of shearing or sawing. Burned surfaces of flame-cut material shall be ground or machined sufficiently to remove ash and cooling checks. All bends shall be made with metal dies or fixtures to insure uniformity of size and shape. Precautions shall be taken to avoid overheating, and heated metal shall be allowed to cool slowly. All burrs, rough edges and edges of holes shall be ground smooth.

3.8.1.1 Sheaves and rollers. Sheaves and rollers shall be free to rotate.

3.8.2 Welders and welding.

3.8.2.1 Welders and welding operators. Before assigning any welder or welding operator to welding work covered by this specification, the supplier shall provide the contracting officer with certification that the welder or welding operator has passed qualification tests as prescribed by either of the following listed codes for the materials joined and the type of welding operation to be performed and that such qualification is effective as defined by the particular code:

ASME Boiler and Pressure Vessel Code, Section IX.
AWS D1.5 - Bridge Welding Code.

In the event of evidence of poor welds, the Government reserves the right to require recertification of any welder or welding operator. The test results shall be made available for review by the contracting officer or the contracting officer's representative.

3.8.2.2 Welding. The surfaces of parts to be welded shall be free from scale, paint, grease, and other foreign matter. Welding shall be done by the shielded metal-arc or gas metal-arc (MIG) process and shall conform to the provisions of the ASME or AWS code. All welded parts shall be free from cracks and other imperfections that may reduce the effectiveness of the part. Work shall be positioned for flat welding when practicable. Before welding over previously deposited weld metal, all traces of slag shall be removed, and the deposit and adjoining base metal shall be wire brushed clean.

3.8.2.3 Jigs and fixtures. Components, except for minor parts, shall be assembled in steel jigs or frames and welded while securely held in position. Minor parts may be held securely and tightly in position by any means that will insure secure and correct positioning. The jigs or frames shall be designed so that distortion of the parts will be held to a minimum.

3.8.3 Interchangeability. Components of like description shall be fabricated to be duplicates within the tolerances specified and shall be interchangeable.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:15Z
Check the source to verify that this is the current version before use.

of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Parts and components. Parts and components detailed on the drawings shall be inspected in accordance with the Quality Assurance Provisions (QAP) shown on the drawings. The drawings specify the characteristics requiring QAP inspection, the sampling plan, and the basis for acceptance or rejection (see 6.4 and 6.5).

4.2 Classification of inspections. Inspection shall be classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection of packaging (see 4.6).

4.3 First article inspection.

4.3.1 Examination. The first article keeper assembly shall be examined for the defects specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling for examination. Sampling for examination shall be in accordance with MIL-STD-105. Sample size shall be determined by using MIL-STD-105, table I and table IIa. A lot shall be accepted when zero defects are found and rejected when one or more defects are found.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined for the major and minor defects specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.5 Inspection procedure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

4.5.1 Examination. The keeper assembly shall be examined as specified herein, for the following defects:

Major

101. Any part or component not in accordance with the QAP requirements shown on the drawings (see 3.1.1).
102. Materials are not resistant to corrosion or deterioration or treated to be made resistant to corrosion or deterioration for the applicable storage and operating environment as specified (see 3.3.1 and 3.3.2).
103. Dissimilar metals as specified in MIL-STD-889 are not effectively insulated from each other as specified (see 3.3.2).
104. Contractor does not have documentation available for identification of material, material finishes, or treatments (see 3.3.3).
105. Material not as specified (see 3.3).
106. Workmanship not as specified (see 3.8).
107. Sheaves and rollers not free to rotate (see 3.8.1.1).
108. Welders and welding operators not certified as specified (see 3.8.2.1).
109. Welding and welds not as specified (see 3.8.2.2).
110. Weld defects such as flux inclusions, spatter, undercutting, porosity, incorrect size, or lack of fusion with parent metal (see 3.8.2.2).

Minor

201. Dimensions other than those identified by QAP data not as specified (see 3.1.1).
202. Identification marking incorrect, missing, or illegible (see 3.5).
203. Cleaning, treatment, and painting not as specified (see 3.6).
204. Stenciling not as specified (see 3.7).

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. Presence of one or more defects shall be cause for rejection.

111. Keeper assemblies packed in quantities other than two (see 5.1).
112. Boxes not as specified for level A or B (see 5.1.1 and 5.1.2).
113. Blocking and bracing not adequate to prevent movement for level A or B (see 5.1.1 and 5.1.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

114. Strapping not as specified for level A or B (see 5.1.1 and 5.1.2).
115. Marking missing, illegible, incorrect, or incomplete (see 5.2).

5. PACKAGING

5.1 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. Two keeper assemblies shall be packed together in a close-fitting box conforming to PPP-B-621, class 2, style optional or PPP-B-601, overseas type, style optional. Blocking and bracing shall be provided to prevent movement of the keeper assemblies within the box. The box shall be closed in accordance with the appendix to the applicable box specification. Strapping shall be in accordance with ASTM D 3953, type 1 or 2, zinc-coated, size as applicable and ASTM D 4675.

5.1.2 Level B. The keeper assemblies shall be packed as specified in 5.1.1 for level A except boxes shall be domestic type or class as applicable. Strapping may be zinc-coated.

5.1.3 Level C. Two keeper assemblies shall be packed together in a manner to assure carrier acceptance and safe delivery to destination at lowest rating in a container complying with Uniform Freight Classification rules or National Motor Freight Classification rules.

5.2 Marking. In addition to any special marking specified by the contract or purchase order (see 6.2), shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The keeper assembly is intended to be used as a support for the fall block and haul ropes, of the medium cableway. This item is listed in Supply Catalog (SC) 5420-97-CL-E04.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. Time frame required for submission of first article (see 3.2).
d. Level of packing required (see 5.1).
e. Any special marking required (see 5.2).

6.3 First article. When a first article inspection is required, the keeper assembly should be a preproduction model. The first article should consist of one or more units. The contracting officer should include specific instructions in the acquisition documents regarding arrangements for

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:15Z
Check the source to verify that this is the current version before use.

examinations, approval of the first article test results and disposition of the first articles. Invitation for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation. Any changes or deviations of production keeper assemblies from the approved first article during production will be subject to the approval of the contracting officer. Approval of the first article will not relieve the supplier of his obligation to furnish keeper assemblies conforming to this specification.

6.4 Quality assurance provisions (QAP). The contracting officer should require the supplier to maintain records of all QAP inspections. A suggested paragraph is as follows:

> "The contractor shall maintain complete records of all examinations and tests performed to verify the requirements of classified QAP characteristics. The records shall include as a minimum, lot size, sample size, drawing requirement, actual measurement, number and type of deficiencies found, quantity approved, quantity rejected, corrected action taken when applicable."

6.5 Definitions.

6.5.1 Quality assurance provisions (QAP). A QAP is a contractual requirement that supplements section 4 of the specification. QAP indicates the minimum requirements which must be inspected on the product drawings to verify the design objectives of the product and assure interchangeability of repair parts.

6.6 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

6.7 Subject term key word listings.

Assembly
Cableway
Keeper

Custodians:
Army - ME

Review Activities
DLA-CS

Preparing activity:
Army - ME

Project 5420-0183

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:15Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

The preparing activity must complete blocks 1,2,3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4,5,6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of this letter.

NOTE: This form may not be used to request copies of documents, nor to request waives requirements in current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or do amend contractual requirements.

RECOMMENDED CHANGE:	1. DOCUMENT NUMBER MIL-K-523388	2. DOCUMENT DATE (YYMMDD) 910909

3. DOCUMENT TITLE
Keeper Assembly: Cableway, Medium

4. NATURE OF CHANGE (identify paragraph number and include proposed if possible. Attach extra sheets as needed).

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (LAST,FIRST MIDDLE INITIAL)	b. ORGANIZATION	
c. ADDRESS (Include zip code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (if applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. Name Gerry Harlow	b. TELEPHONE (In lude Area Code) (1) Commercial (2) AUTOVON (703) 664-2071 354-2071
ADDRESS (Include zip code) Belvoir RDE Center ATTN: STRBE-TSE Fort Belvoir, VA 22060-5606	If you do not receive a reply with 45 days, contact: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403 Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:15Z
Check the source to verify that this is the currentversion before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.