MIL-P-80178A
31 March 1976
SUPERSEDING
MIL-P-80178
14 April 1969

MILITARY SPECIFICATION

PRESS, HYDRAULIC, STRAIGHTENING, GAP TYPE, VERTICAL, ELECTRIC MOTOR DRIVEN

This specification is approved for use by all Departments and Agencies of Department of Defense.

1. SCOPE

1.1 Scope. This specification covers vertical, gap type frame, electric motor driven, hydraulic powered, floor mounting type, straightening presses capable of performing general purpose press operations.

* 1.2 Classification. Straightening presses covered by this specification are of the following sizes. The size supplied shall be as specified (see 6.2.1):

Size 15	15 Ton Capacity
Size 25	25 Ton Capacity
Size 35	35 Ton Capacity
Size 50	50 Ton Capacity
Size 75	75 Ton Capacity
Size 100	100 Ton Capacity
Size 150	150 Ton Capacity
Size 200	200 Ton Capacity

2. APPLICABLE DOCUMENTS

2.1 Military publications. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATION

MIL-M-18058	Machinery, Metal and Woodworking Preparation for Delivery of

FSC 3442

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

STANDARDS

MIL-STD-130	Identification Marking of U.S. Military Property
MIL-STD-461	Electromagnetic Interference Characteristics Requirements for Equipment

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

OCCUPATIONAL SAFETY AND HEALTH ACT (OSHA) OF 1970

Title 29, Code of Federal Regulation, Chapter XVII, Part 1910, and amendments.	Occupational Safety and Health Administration Standards

NATIONAL BUREAU OF STANDARDS (NBS)

Handbook H-28 - Screw-Thread Standards for Federal Services

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

JOINT INDUSTRIAL COUNCIL (JIC)

H1 - JIC Hydraulic Standards for Industrial Equipment and General Purpose Machine Tools

EGP-1 - JIC Electrical Standards for General Purpose Machine Tools

(Application for copies should be addressed to the National Machine Tool Builders' Association, 7901 Westpark Drive, McLean, Va 22101.)

AMERICAN GEAR MANUFACTURERS ASSOCIATION (AGMA)

AGMA 360 - Manual for Machine Tool Gearing

(Application for copies should be addressed to the American Gear Manufacturers Association, 1330 Massachusetts Ave., NW, Washington, DC 20005.)

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:44Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First Article approval. If First Article approval is required (see 6.2.1 and 6.3), inspection therefor shall be in accordance with Section 4. A First Article comprises a preproduction model or initial production sample; approval involves testing and evaluating the First Article for conformance with the requirements herein before, or in the initial stage of, production under a contract.

3.2 Design. The presses shall be new and of the manufacturer's current design. The press shall be of the open gap frame or "C" frame design providing unobstructed access from all sides of the table, except the rear. The press shall be hydraulically powered, electric-motor driven, self-contained and designed to perform general purpose straightening operations. Each press shall include all components, parts and features necessary to meet the performance requirements specified herein. All parts subject to wear, breakage, or distortion shall be accessible for adjustment, replacement and repair.

* 3.2.1 Safety and health requirements. Each press shall be fitted with safety devices or coverings for all parts that present safety hazards. The devices shall include guards for belts, pulleys, chains, gears, and sprockets and shall exclude point-of-operation guarding unless required under 6.2.1. All guards shall be designed to provide access to the guarded parts by the use of hinges, removable sections, or similar devices. Except as otherwise specified by the procuring activity the press shall comply with the standards promulgated under OSHA applicable to the press itself. Exceptions and additional requirements for safety and health shall be as specified (see 6.2.1 and 6.4).

3.2.2 Lubrication. All bearings (except sealed, permanently-lubricated type), mating gears, and sliding, reciprocating, or rotating parts shall have means for lubrication. All oil holes, grease fittings, and filler caps shall be accessible without removal of parts other than coverings.

3.2.3 Interchangeability. To provide for replacement of worn parts, all parts shall be manufactured to definite dimensions and tolerances that will permit installation of replacement parts without modification of the part or press.

3.2.4 Material. All material used in the manufacture of the press shall be new and of the quality necessary to produce a press to meet the requirements described herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

* 3.3 Construction. Each press shall be constructed of parts that are new and without defects. Repaired parts shall not be used. The material, design and construction of the press shall be such that operation at 110% of its maximum rated tonnage capacity, shall not result in damage or permanent distortion of any component thereof.

3.3.1 Castings and forgings. All castings and forgings shall be free of scale and mismatching. No process such as welding, peening, plugging or filling with solder or paste shall be used for reclaiming any defective part.

3.3.2 Welding, brazing or soldering. Welding, brazing, or soldering shall be employed only where required in the original design. None of these operations shall be employed as a repair measure for any defective part.

3.3.3 Fastening devices. All screws, pins, bolts and other fasteners shall be installed in a manner to prevent change of tightness. Those devices subject to removal or adjustment shall not be swaged, peened, staked, or otherwise permanently installed.

3.3.4 Surfaces. All surfaces shall be clean and free of sand, dirt, fins, sprues, scale, flux, and other harmful or extraneous materials. All edges shall be either rounded or beveled unless sharpness is required to perform a necessary function.

3.3.5 Painting. Unless otherwise specified (see 6.2.1), the press shall be painted in accordance with the manufacturer's standard commercial practice.

3.3.6 Threads. All threaded parts shall be in the inch system and in accordance with Handbook H28.

3.3.7 Dials. All dials shall be graduated in the inch system. Dial diameters shall be such that the graduation may be easily read from the normal operating position. Dials shall be permanently and legibly engraved or etched on a non-glare background.

3.3.8 Plates. All words on instruction and indicating plates shall be in the English language. Characters shall be engraved, etched, embossed or stamped in boldface on a contrasting background.

3.3.9 Gears. All gears used in the press and its components shall be machined in the inch system and shall conform to the applicable requirements of AGMA 360.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

3.4 Electrical equipment. Unless otherwise specified (see 6.2.1), the electrical system shall be in accordance with this paragraph. The electrical system or each press shall conform to JIC EGP-1. Each press shall be completely wired through the controls and ready for connecting to the applicable power source. Each press shall be equipped with a magnetic starter and shall have overload and undervoltage protection with manual reset. A single disconnecting means shall disconnect all ungrounded conductors, and a identified terminal shall be provided for connecting the size grounding conductor specified in Table 15-1 of EGP-1. The press shall operate from a single service 230/460 volt, 3 phase, 60 Hz AC power supply and be wired to operate on 460 volts. A stepdown transformer shall be provided for the control circuits and the controls shall operate on 115 nominal volts.

3.4.1 Motor. Motors shall be rated for continuous duty and shall be equipped with ball or roller bearings.

3.4.2 Electromagnetic interference control. When specified (see 6.2.1), equipment procured under this specification shall comply with the requirements of MIL-STD-461.

3.5 Performance. Each press shall be capable of exerting a force of not less than 110% of its rated tonnage at any point of the ram stroke and shall be capable of holding this force for a time of not less than three seconds. When required, the press shall be capable of pressing or holding its rated tonnage for the period of time specified (see 6.2.1).

3.5.1 Ram speed. Unless otherwise specified, the ram speed shall be as specified in Table I for the size press offered under this contract. When a different ram speed is required it shall be as specified (see 6.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

TABLE I

Sizes and Characteristics								
Characteristics	Size 15	Size 25	Size 35	Size 50	Size 75	Size 100	Size 150	Size 200
Capacity (Tons)	15	25	35	50	75	100	150	200
Daylight (Table to Ram, Ram Fully Up, Inches)	19	19	22	22	23	26	28	28
Ram Travel, (Inches)	12	12	12	12	12	18	18	18
Ram Speeds,								
Closing (ipm)	170	170	150	100	65	40	40	25
Pressing (ipm)	80	80	80	40	30	17	17	8
Return (ipm)	160	160	160	90	60	38	38	20
Throat, Ram Centerline to Frame (Inches)	8	8	10	10	10	15	18	18
Table Size, (Inches)								
Front to Back	8	10	12	12	12	18	21	21
Left to Right	36	36	48	48	60	72	72	84

All requirements shall be not less than those specified in the Table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

3.6 Components. Major components of the press shall consist of a frame, table, ram assembly, hydraulic system and controls.

3.6.1 Frame. The press shall have a "C" or gap type frame and shall be a one piece casting or welded fabrication of steel plate, angles and shapes. If the frame is a fabricated structure, each side of the structure shall be fabricated from a single steel plate that forms the head, throat, and table base into a single integral structure. The frame shall have adequate strength and rigidity to meet all performance and alignment tolerances specified herein. The frame shall support all components of the press and withstand pressing forces of not less than 110 percent of its rated tonnage without damage or permanent deformation. The table surface area of the frame shall be flat within 0.002 inch per foot left to right and front to back. Unless otherwise specified (see 6.2.1), the frame shall provide a working height from the top of the table to floor level of 32 inches $\pm$1 inch. The base of the frame shall have means for securing the press to the floor.

3.6.1.1 Table. Unless otherwise specified the press table shall have a key slot(s) for mounting table blocks and work fixtures. When specified (see 6.2.1), the table shall be solid without key slots. The table shall be removable and unless otherwise specified (see 6.2.1), of the dimensions specified in Table 1.

3.6.1.2 Ram. The ram end shall have threaded bolt holes and set screws, or have an adapter to receive tooling. The ram shall be perpendicular to the table surface within 0.005 inch per foot of ram stroke. Means shall be provided to prevent rotation of the ram. When specified (see 6.2.1), the ram shall be provided with a guide to minimize deflection through the complete ram stroke.

3.6.2 Hydraulic system. The hydraulic system shall consist of a fluid reservoir, an electric motor driven pump, a hydraulic cylinder and piston assembly and necessary pressure release and control valves, pressure gauge, controls, piping, hose and fittings. The system shall enable the ram to move at the speeds specified for press and the ram shall be capable of exerting force up to 110% of the maximum rated tonnage of the press. A pressure relief valve or similar device, shall be provided to prevent loading the press in excess of 110% of its rated tonnage. Means shall be provided to prevent extension of the ram beyond its normal end of stroke position. Design, capacity, and cooling requirements of the hydraulic system shall be such that under conditions of continuous press operations at maximum loads and speeds the pump inlet temperature of the fluid shall not exceed 130°F. The hydraulic system of the press shall conform to the requirements of JIC H-1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

3.6.2.1 Filter system. The hydraulic system shall have a suction strainer, full flow filteration system and magnetic devices of sufficient quantity and strength to remove detrimental material from hydraulic fluid.

3.6.2.2 Pump. The pump shall be of the positive displacement type and shall have pressure and volumetric capacity to enable the press to comply with all performing requirements specified herein.

3.6.2.3 Cylinder assembly. The cylinder assembly shall consist of the cylinder, piston, rings and seals. The cylinder shall be rigidly mounted in the press workhead and maintain the ram alignment specified herein. The cylinder assembly shall be designed and constructed to preclude leakage of hydraulic fluid under all operating conditions specified herein.

3.6.2.4 Fluid reservoir. The fluid reservoir shall be capable of holding not less than 1-1/4 time the volume of fluid required to fill the hydraulic system and force the ram to the bottom of the stroke. The reservoir shall have a cleanout opening, fluid drain, fluid level sight gauge and filler strainer. All openings shall be fitted with gaskets or seals.

3.6.2.5 Gauge. A pressure gauge having a face diameter not less than 3½ inches shall be provided. The gauge shall be calibrated to read both pressure of the hydraulic system and tons of ram force. The gauge shall be legible from the operator's normal work station and shall not be obstructed by any part of the press.

3.6.2.6 Bleeding devices. The hydraulic system shall either be self-bleeding or shall have provisions for bleeding air from the system after the system is filled. After the system is bled, it shall remain free of air under all conditions of operation except draining and refilling of the system.

3.6.3 Controls. The control system of the press shall be in accordance with JIC H-1. The control system of each press shall be provided with external means to adjust the operating force of the ram. The ram force shall be adjustable for any desired pressure from 5% or less of rated tonnage through the maximum capacity of the press.

3.6.3.1 Palm button and lever control. Unless otherwise specified (see 6.2.1) the press shall be controlled by a combination button and lever, with a single button for the left hand and a single lever for the right hand. The controls shall provide complete control of ram

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

movement and pressure, shall be interlocked to require activation of both controls prior to movement of the ram and have a no-tie-down timer between the button and lever. The controls shall provide for stopping, inching, re-starting or retracting the ram at any point of the ram stroke. Ram movement either up or down shall be direct proportional to lever movement. Releasing the levers at any ram position shall cause the ram to return to the up position and stop.

3.6.3.2 Palm button. When specified (see 6.2.1), the press shall have an automatic control system utilizing dual palm buttons to actuate ram movement. The control system shall provide for selecting either automatic or single cycle control of the ram. The controls shall provide both pressure and ram stroke length control. The pressure control shall provide for the ram to reverse automatically upon attaining a preset pressure. The ram stroke control shall provide for the ram to reverse automatically upon attaining a preselected stroke length. The control system shall provide for inching or jogging the ram movement. The controls shall be interlocked and have a no-tie-down timer between the buttons.

3.6.3.3 Dwell controls. When specified (see 6.2.1), the press control system shall have adjustable dwell control to permit the ram to dwell at either the top or bottom of the stroke for the preset period of time specified.

3.6.3.4 Dual ram speed control. When specified (see 6.2.1) presses equipped with palm button control system shall have dual ram pressing speed control. The control system shall provide for the ram to descend at normal closing speed, automatically change to a slower speed at a predetermined distance over the workpiece, exert the preset pressure and return to the up position at normal opening speed. Presses equipped with lever controls shall provide for the ram to descend at normal closing speed until the ram head contacts the workpiece, dwell until further downward movement of the control lever causes pressure to be exerted in proportion to lever movement.

3.6.3.5 Return limit control. The control system shall have a ram return limit control. The mechanism shall provide for reversing the ram at any preset opening distance greater than one inch from the bottom of the stroke.

* 3.7 Optional equipment. Optional equipment or accessories such as ram adapters, ram blocks, table blocks, and center holding fixtures shall be furnished when specified (see 6.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

* 3.8 Lubrication chart or plate. Unless otherwise specified (see 6.2.1), a lubrication chart or plate shall be permanently and securely attached to each machine. If a chart is furnished, it shall be placed in a transparent plastic folder, or permanently sealed between clear plastic sheets, with suitable means for mounting. The following information shall be furnished on the chart or plate:

Points of application

Service interval

Type of lubricant

Viscosity

Military or Federal Specification covering recommended lubricants

If there are no points on the press requiring lubrication, the chart or plate shall be inscribed "No lubrication required" in lieu of the information required above.

* 3.9 Nameplate. Unless otherwise specified (see 6.2.1), a corrosion-resistant metal nameplate identifying the press in accordance with MIL-STD-130 shall be securely attached to each press. The nameplate shall contain the information listed below. If the press is a special model, the model designation shall include the model of the basic standard press and a suffix identified in the manufacturer's permanent records. The captions listed may be shortened or abbreviated, provided the entry for each caption is clear as to its identity.

Nomenclature

Manufacturer's name

Manufacturer's serial number

Power input (volts, total amps, phase, frequency)

Hydraulic system maximum-operating pressure (PSI)

Hydraulic system fluid capacity (gallons)

Capacity, tons, maximum rated

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:44Z
Check the source to verify that this is the current version before use.

Contract Number or Order Number

National Stock Number or Plant Equipment Code

Date of manufacture

U S

3.10 Technical data. Technical data shall be furnished as specified (see 6.2.2).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may utilize his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification when such action is deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First Article inspection. When First Article approval is required under 3.1, First Article inspection shall be performed. Unless otherwise specified (see 6.2.1), First Article inspection shall comprise the examination in 4.4, and all tests in 4.5. Failure of the item to pass any examination or test shall be cause for disapproval of the First Article.

* 4.3 Quality conformance inspection. Each press shall be subjected to quality conformance inspection prior to being offered for acceptance. Unless otherwise specified (see 6.2.1), quality conformance inspection shall consist of the examination in 4.4, the tests in 4.5.1 and the inspection in 4.6. Failure of the press to pass any examination, test, or inspection shall be cause for rejection.

4.4 Examination. The press and equipment shall be examined to determine compliance with the requirements of this specification.

4.5 Tests.

4.5.1. Operational tests. Each press shall be operated at no load for 30 minutes, during which time the controls, electric motors, and driven

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:44Z
Check the source to verify that this is the current version before use.

components shall be actuated and observed to determine that the press operates properly. During the no load test, fail-safe features for stopping slide travel shall be tested and each device or system shall perform its intended function. The press shall be operated through all control functions and stroke positions. The ram shall be observed during operating cycles for binding, chatter, loose motion and the complete hydraulic system shall be inspected for leaks. If any of these conditions are present and the condition is not correctable by adjustment, that condition shall be cause for rejection.

* 4.5.2 Performance test. Each press shall be tested with jacks, gages and timing devices, or devices which measure and indicate the ram speeds and maximum tonnage, to assure conformance to the requirements of Section 3. Each press shall be subjected to an overload test which exceeds maximum tonnage rating by 10 percent. The ram closing speed, pressing speed and opening speed shall be tested. The press shall be tested at 100% of rated tonnage at different points of ram stroke and the hydraulic system shall hold its rated tonnage for the time period specified. Presses equipped with control devices, such as dwell control, inching control, return limit control, pressure and stroke control and pressing speed control shall be tested under operating conditions. The press shall be operated under conditions of continuous production at maximum speeds and pressure. The hydraulic fluid temperature shall be monitored at the pump inlet until the fluid temperature stabilizes at maximum and the fluid temperature shall not exceed 130°F. Following these test, the press shall be visually examined, without dismantling, for damage to components, adjustment, alignment, and fluid leaks.

4.5.3 Electromagnetic interference control tests. Equipment requiring electromagnetic interference control shall be tested for compliance with 3.4.2.

4.6 Inspection of preparation for delivery. Preservation, packaging and marking shall be inspected to determine compliance with the requirements of Section 5.

5. PREPARATION FOR DELIVERY

5.1 Preservation-packaging, packing and marking. Preservation, packing and marking shall be in accordance with the applicable requirements of MIL-M-18058. The required level of preservation and packing, and any special marking requirements shall be as specified (see 6.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. Straightening presses covered by this specification are intended for use in machine and repair shops for such operations as straightening weldments, castings and shafts.

* 6.2 Ordering data.

6.2.1 Procurement requirements. Purchasers should specify their requirements in procurement documents, including whether each choice is required of not required, by entering an appropriate statement identified to each of the following:

a. Title, number, and date of this specification.

b. Size press required (see 1.2).

c. First Article, if required (see 3.1).

d. When safety and health requirements are different; specify and fully describe point of operation guarding, if required (see 3.2.1 and 6.4).

e. Painting, if different (see 3.3.5).

f. Electrical requirements, if different (see 3.4).

g. Electromagnetic interference control, if required (see 3.4.2).

h. Pressing or holding time, if different (see 3.5).

i. Ram speeds, if different (specify closing, pressing, and return speeds ipm) (see 3.5.1).

j. Table working height, if different (see 3.6.1).

k. Table without keyslot and table size if different (see 3.6.1.1).

l. Ram guide, if required (see 3.6.1.2).

m. Controls, if different (see 3.6.3.1).

n. Palm button automatic controls, if required (see 3.6.3.2).

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:44Z
Check the source to verify that this is the current version before use.

o. Dwell control and dwell time, if required (see 3.6.3.3). (Specify dwell at top or dwell at bottom of stroke)

p. Dual ram speed control, if required (see 3.6.3.4).

q. Optional equipment, if required (specify) (see 3.7).

r. Lubrication plate, if different (see 3.8).

s. Nameplate, if different (see 3.9).

t. First Article, if different (see 4.2).

u. Quality conformance, if different (see 4.3).

v. Required level of preservation, packing and special marking requirements (see 5.1).

6.2.2 Contract data requirements. Required technical data such as operators manuals, parts lists, foundation and anchor bolt plans, wiring diagrams and other instruction for operation and maintenance as identified on a numbered DD Form 1664, should be specified on a DD Form 1423 incorporated into the contract.

6.3 First Article. When First Article approval is required under 3.1, the solicitation should adhere to the applicable portions of Section 1, Part 19 of the Armed Services Procurement Regulation.

6.4 Safety and health determinations. In order that equipment integrated into the user's operational environment will comply with the standards promulgated under the Occupational Safety and Health Act of 1970, limitation and control of noise levels, radiation, electromagnetic emission, noxious vapors, heat, etc. as applicable, specific requirements concerning guarding the point(s) of operation, and other safety and health requirements should be specified.

6.5 Mercury prohibited. When the use of mercury or its compounds in the press and its components and accessories is to be prohibited, procurement documents should include a statement to that effect.

6.6 Classification. Classification of presses covered by this specification have been restructured and the following table show sizes of presses in this revision in comparison to the sizes in the previous revision.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

MIL-P-80178		MIL-P-80178A		
Size	Capacity (Tons)			
1	15		Size 15	- 15 Ton Capacity
2	25		Size 25	- 25 Ton Capacity
3	50	(New Size)	Size 35	- 35 Ton Capacity
4	75		Size 50	- 50 Ton Capacity
5	100		Size 75	- 75 Ton Capacity
6	150		Size 100	- 100 Ton Capacity
			Size 150	- 150 Ton Capacity
		(New Size)	Size 200	- 200 Ton Capacity

6.7 Marginal notations. The margins of this specification are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the enitre content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - WC
Navy - SH
Air Force - 84

Preparing Activity:
DSA - IP

Project Number: 3442-0034

Review:
Army - WC
Navy - SH
Air Force - 84

User:
Navy - MC
Army - SM, WV

U S GOVERNMENT PRINTING OFFICE 1976— 603—766 3608

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:44Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:44Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Headquarters
Military Traffic Management Command
ATTN: MT-SA
Washington, DC 20315

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:44Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026/10 23:04:44Z
Check the source to verify that this is the current version before use.