MIL-V-52456A(ME)
13 April 1973
SUPERSEDING
MIL-V-52456(MO)
9 August 1965

MILITARY SPECIFICATION

VALVE ASSEMBLY, PNEUMATIC

FLOAT REPAIR, MECHANICAL-TYPE

1. SCOPE

1.1 This specification covers a mechanical-type, repair valve assembly.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

QQ-S-571	- Solder, Tin Alloy, Lead-Tin Alloy and Lead Alloy.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-636	- Boxes, Shipping, Fiberboard.

Military

MIL-R-3065	- Rubber, Fabricated Products.
MIL-S-6872	- Soldering Process, General Specificatio for.

STANDARDS

Federal

FED. TEST METHOD STD. No. 601	- Rubber: Sampling and Testing.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:18Z
Check the source to verify that this is the current version before use.

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-417	- Rubber Compositions, Vulcanized General Purpose, Solid (Symbols and Tests).

DRAWINGS

ME

TA13214E6080	- Valve Assembly, Pneumatic Float Repair, Mechanical Type.
13214E8327	- Instruction Sheet.

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Tariff Order Section, 1616 P Street NW, Washington, DC 20036.)

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:18Z
Check the source to verify that this is the currentversion before use.

3. REQUIREMENTS

3.1 Description. The valve assembly shall be as shown on top assembly TA13214E6080 and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissable without prior approval of the contracting officer. Any data (e.g. shop drawings, layout, flow sheets, processing procedures, etc.) prepared by the supplier or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 First article (preproduction model). The supplier shall furnish one or more valve assemblies for examination and test within the time frame specified (see 6.2) to prove, prior to starting production, that his production methods will produce valve assemblies that comply with the requirements of this specification. Examination and tests shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.3).

3.3 Material. Material shall be as specified herein and as shown on the applicable drawings. Materials not specified shall be selected by the supplier and shall be subject to all provisions of this specification.

3.4 Soldering. The mating surfaces and adjacent areas of the parts to be joined shall be thoroughly cleaned prior to soldering. Particular attention shall be given that the entire mating surfaces be totally bonded. Soldering shall be done in accordance with MIL-S-6872.

3.5 Valve cap. The cable and toggle attached to the valve cap shall withstand a pull of 200 pounds without any evidence of failure or permanent deformation of any part of the valve cap assembly.

3.6 Instructions. One copy of instructions, in accordance with 13214E8327, shall be furnished with each valve assembly. These instructions, covering step-by-step procedures for installing the valve assembly, shall be printed as specified on the drawing and shall be legible and durable.

3.7 Workmanship. All parts, components, and subassemblies of the valve assembly including forgings, stampings, rubber moldings, machined parts, and soldered parts, shall be clean and free of rust, scale, scrapes, burrs, dirt, pits, and other harmful extraneous material. Edges and surfaces of

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:18Z
Check the source to verify that this is the currentversion before use.

the valve assembly shall be finished as specified on the drawings, with no metal projections, slivers, or other extraneous material that would be injurious to handling personnel or that would adversely affect the serviceability of the valve assembly.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The supplier is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications, standards, and drawings.

4.1.2 Parts and components. Parts and components detailed on the drawings shall be inspected in accordance with the Supplementary Quality Assurance Provisions (SQAP) shown on the drawings. The drawings specify the characteristics requiring SQAP inspection, the sampling plan, and the basis for acceptance and rejection (see 6.4 and 6.5).

4.2 Classification of inspection. Inspection shall be classified as follows:

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).
(c) Inspection of preparation for delivery (see 4.6).

4.3 Preproduction inspection.

4.3.1 Examination. The preproduction valve assembly shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The preproduction valve assembly shall be tested as specified in 4.5.2. Failure of any test shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:18Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination and tests shall be in accordance with MIL-STD-105, inspection level S2.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined for the major and minor defects as specified in 4.5.1. AQL shall be 2.5 percent defective for major defects, 4.0 percent defective for minor A defects, and 6.0 percent defective for minor B defects.

4.4.3 Tests. Samples selected in accordance with 4.4.1 shall be tested as specified in 4.5.2. AQL shall be 2.5 percent defective.

4.5 Inspection procedure.

4.5.1 Examination. The valve assemblies shall be examined for the following defects:

MAJOR

101. Materials not as specified.
102. Nonconformance to any requirement designated on SQAP as major.
103. Soldering not as specified.
104. Instruction sheet not as specified.
105. Workmanship not as specified.

MINOR A

201. Nonconformance to any requirement designated on SQAP as minor.

MINOR B

301. Nonconformance to any requirement on drawings not designated on SQAP as major or minor.

4.5.2 Tests.

4.5.2.1 Rubber components. Rubber material representative of that used in respective components of the valve assembly shall be tested in accordance

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:18Z
Check the source to verify that this is the currentversion before use.

with methods referenced or detailed in MIL-STD-417 and MIL-R-3065. Nonconformance to the requirements specified on the drawings shall constitute failure of this test.

4.5.2.2 Valve cap. The toggle of the valve cap shall be attached to the fixed head of a tension testing machine or device. The valve cap shall be attached to the moving head of the machine or the moving load. The load shall be increased to 200 pounds. The attached cable and toggle to the valve cap shall withstand a pull of 200 pounds without breaking or evidence of deformation to any part of the assembly.

4.6 Inspection of preparation for delivery.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

106.	Containers not as specified for level A or B. Each incorrect container shall be considered one defect.
107.	Valve assembly and instruction sheet not packaged together as specified.
108.	Valve assemblies intermediate packaged together in quantities exceeding 30 pounds for level A and B.
109.	Boxes not waterproof-sealed as specified for level A packaging and level B packing.
110.	Strapping not zinc coated for level A.
111.	Marking missing, illegible, incorrect, or incomplete.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.2).

5.1.1 Level A. Each valve assembly, with the instruction sheet, shall be packaged in a commercial grade, close-fitting paperboard box.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:18Z
Check the source to verify that this is the current version before use.

5.1.1.1 Intermediate packaging. The valve assemblies packaged as specified in 5.1.1 shall be intermediate packaged together in quantities not to exceed 30 pounds, in close-fitting boxes conforming to PPP-B-636, W6c, style optional. The boxes shall be waterproof sealed as specified for slotted style boxes in accordance with the appendix to the box specification.

5.1.2 Level B. The valve assemblies, with instruction sheets, shall be packaged as specified in 5.1.1 except the boxes for intermediate packaging shall be type CF, class domestic, variety SW, grade 125, and waterproof sealing of the box shall not be required.

5.1.3 Level C. The valve assemblies, with instruction sheets, shall be individually packaged as specified in 5.1.1. Intermediate packaging is not required.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. The valve assemblies, packaged as specified in 5.1, shall be packed together in a close-fitting box conforming to PPP-B-601, overseas type, style optional. The boxes shall be closed and strapped in accordance with the appendix to the applicable box specification. Strapping shall be zinc coated.

5.2.2 Level B. The valve assemblies, packaged as specified in 5.1, shall be packed in a close-fitting box conforming to PPP-B-636, V3c or V3s. The gross weight or size shall not exceed the limitation of the box specification. The box shall be reinforced with bands of reinforced tape and waterproof sealed as specified for slotted style boxes in accordance with the appendix to the box specification.

5.2.3 Level C. The valve assemblies, packaged as specified in 5.1, shall be packed in fiberboard containers in a manner to assure carrier acceptance and safe delivery to destination at lowest rating, complying with Uniform Freight Classification rules or with National Motor Freight Classification rules.

6. NOTES

6.1 Intended use. The valve assembly is intended for use in repairing pneumatic ponton floats and rollers of military floating bridges.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.

Source: https://assist.dla.mil -- Downloaded: 20261O-22T21:18Z
Check the source to verify that this is the currentversion before use.

(b) Time frame required for submission of preproduction model (see 3.2).
(c) Level of packaging and level of packing required (see 5.1 and 5.2). Level B packaging and packing is intended to provide economical but limited protection and should be specified only when it has been determined the valve assemblies will be held in covered storage.

6.3 Preproduction model. Any changes or deviations of production valve assemblies from the approved preproduction model will be subject to the approval of the contracting officer. Approval of the preproduction model will not relieve the supplier of his obligation to furnish valve assemblies conforming to this specification.

6.4 Supplementary quality assurance provisions (SQAP). The contracting officer should require the supplier to maintain records of all SQAP inspections. A suggested paragraph is as follows:

"The supplier shall maintain complete records of all examinations and tests performed to verify the requirements of classified SQAP characteristics. The records shall include as a minimum, lot size, sample size, drawing requirement, actual measurement, number and type of deficiencies found, quantity approved, quantity rejected, corrected action taken when applicable."

6.5 Definitions.

6.5.1 Supplementary quality assurance provisions (SQAP). A SQAP is a contractual requirement that supplements section 4 of the specification. SQAP indicates the minimum requirements which must be inspected on the product drawings to verify the design objectives of the product and assure interchangeability of repair parts.

Custodian:

Army - ME

Preparing activity:

Army - ME

Project No. 5420-A191

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:18Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION: MIL-V-52456A(ME) Valve Assembly, Pneumatic Float Repair, Mechanical Type

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1426
11 Oct 72 (Rev)

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:18Z
Check the source to verify that this is the currentversion before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. ARMY MOBILITY EQUIPMENT
RESEARCH, DEVELOPMENT
CENTER
FORT BELVOIR, VIRGINIA 22060

OFFICIAL BUSINESS

AMSME-RZD-S

POSTAGE AND FEES PAID
DOD-314

COMMANDER
U. S. ARMY MOBILITY EQUIPMENT
RESEARCH, DEVELOPMENT CENTER
ATTN: AMSME-RZD-S
FORT BELVOIR, VIRGINIA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:18Z
Check the source to verify that this is the current version before use.