INCH-POUND

MIL-W-80192C
10 February 1989
SUPERSEDING
MIL-W-80192B
14 August 1984

MILITARY SPECIFICATION

WELDING MACHINE, RESISTANCE, SPOT AND SEAM, METAL FOIL, SINGLE PHASE, PORTABLE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers portable type, single phase, metal foil, spot and seam, resistance welding machines, with equipment and accessories specified herein. This specification covers welding machines of one type and one size with capacity to weld metal foil of thicknesses from 0.001 to 0.010 inches.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATION

MILITARY

MIL-W-45562 - Welding and Soldering Equipment, Supplies, and Accessories, Packaging of.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Industrial Plant Equipment Center, ATTN: DIPEC-SSG, Memphis, TN 38114-5051, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3432

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED-STD-H28 - Screw Thread Standards for Federal Service.

FED-STD-376 - Preferred Metric Units for General Use by the Federal Government.

MILITARY

MIL-STD-461 - Electromagnetic Emission and Susceptibility Requirements for the Control of Electromagnetic Interference.

MIL-STD-462 - Electromagnetic Interference Characteristics, Measurement of.

2.1.2 Other Government documents. The following other Government document forms a part of this specification to the extent specified herein. Unless otherwise specified, the issue shall be that in effect on the date of the solicitation.

CODE OF FEDERAL REGULATIONS (CFR)

U. S. DEPARTMENT OF LABOR, OCCUPATION, SAFETY AND HEALTH ADMINISTRATION (OSHA)

29 CFR 1910 - Occupational Safety and Health Standards.

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington , DC 20402-0001.)

(Copies of specifications, standards, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment document which is current on the date of the solicitation.

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

ANSI B93.114M - Pneumatic Fluid Power - Systems Standard for Industrial Equipment and Machine Tool Applications.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American National Standards Institute, ATTN: Sales Dept., 1430 Broadway, New York, NY 10018-3363.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D 3951 - Standard Practice for Commercial Packaging.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, PA 19103-1187.)

NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION (NEMA)

NEMA ICS 5 - Resistance Welding Control.

(Application for copies should be addressed to the National Electrical Manufacturers Association, 2101 L Street, N.W., Washington, DC 20037-1580.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

NFPA 79 - Electrical Standard for Industrial Machinery.

(Application for copies should be addressed to the National Fire Protection Association, Batterymarch Park, Quincy, MA 02269-9101.)

RESISTANCE WELDER MANUFACTURERS ASSOCIATION (RWMA)

RWMA Bulletin Number 16 - Resistance Welding Equipment Standards.

(Application for copies should be addressed to the Resistance Welder Manufacturers Association, 1900 Arch Street, Philadelphia, PA 19103-1403.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2.1), one complete machine shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Design. The welding machine shall be new (not a prototype) and one of the manufacturers' current production models capable of welding heat resistance metal foil in accordance with the requirements herein. The machine

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

shall include all components, parts, and features necessary to meet the performance requirements specified herein. All parts subject to wear, breakage, or distortion shall be accessible for adjustment, replacement, and repair.

3.2.1 Design and construction dimensional systems. Unless otherwise specified (see 6.2.1), either the inch-pound or the International System of Units (SI) shall be used in the design and construction of the welding machine. In this specification, all dimensions, measurements, sizes, and capacities are given in inch-pound. These dimensions may be converted to SI units through the use of the conversion factors and methods specified in FED-STD-376.

3.2.2 Reclaimed materials. The machine may contain reclaimed materials provided such materials will not jeopardize the intended use, performance, and design life of the machine. The reclaimed materials shall have been reprocessed, remanufactured, or recycled in a manner which will restore them to the same chemical composition and physical properties as the materials originally selected for use on the machine.

3.2.3 Energy efficiency. The machine and its components that directly consume energy in normal operation shall be designed and constructed for energy efficiency in accordance with the developments available within the industry.

3.2.4 Controls. All mechanical, hydraulic, and pneumatic operating controls shall be located conveniently to the operator's work station.

3.2.5 Safety and health requirements. All parts, components, mechanisms, and assemblies furnished on the welder, whether or not specifically required herein, shall comply with all of the requirements of 29 CFR 1910 that are applicable to the welder itself. The welding machine shall be equipped with all point-of-operation guarding normally furnished as standard on the manufacturer's commercial welder supplied to the commercial market. If specific point-of-operation guarding is required, the procuring activity shall specify the exact configuration of the guard required. Additional safety and health requirements shall be as specified (see 6.2.1).

3.2.6 Mercury restriction. The machine shall not contain mercury or mercury compounds nor be exposed to free mercury during manufacture.

3.2.7 Asbestos restriction. Asbestos and materials containing asbestos shall not be used on or in the machine.

3.2.8 Environmental protection. During operation, service, transportation, or storage of the machine, it shall not emit materials hazardous to the ecological system as prohibited by Federal, state, or local statutes in effect at the point of installation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

3.2.9 Lubrication. Means shall be provided to ensure adequate lubrication for all moving parts. Each lubricant reservoir shall have means for determining fluid level. All oil holes, grease fittings, and filler caps shall be accessible.

3.2.10 Interchangeability. To provide for replacement of worn or damaged parts, all parts shall be manufactured to definite dimensions and tolerances that will permit installation of replacement parts without modification of the part or machine.

3.3 Construction. The welding machine shall be constructed of parts which are new, without defects, and free of repairs. The structure shall withstand all forces encountered during operation of the machine to its maximum rating and capacity without permanent distortion.

3.3.1 Castings and forgings. All castings and forgings shall be free from defects, scale, and mismatching. Processes such as welding, peening, plugging, or filling with solders or pastes shall not be used on castings or forgings to reclaim any defective components for use on the machine. Such processes may be used only for enhancing surface finish and appearance.

3.3.2 Welding, brazing, or soldering. Welding, brazing, or soldering shall be employed only where specified in the original design. None of these processes shall be employed as a repair measure for any defective part.

3.3.3 Fastening devices. All screws, pins, bolts, and other fasteners shall be installed in a manner to prevent change of tightness. Fastening devices subject to removal or adjustment shall not be permanently installed.

3.3.4 Surfaces. All surfaces shall be clean and free of sand, dirt, fins, sprues, flash, scale, flux, and other harmful or extraneous materials. All edges shall be either rounded or beveled unless sharpness is required to perform a necessary function. Except as otherwise specified herein, the condition and finish of all surfaces shall be in accordance with the manufacturer's commercial practice.

3.3.5 Painting. Unless otherwise specified (see 6.2.1), the welding machine shall be painted in accordance with the manufacturer's commercial practice and color.

3.3.6 Threads. All threaded parts used on the machine and its related attachments and accessories shall conform to FED-STD-H28 and the applicable "Detailed Standard" section referenced therein.

3.3.7 Electromagnetic interference control. When specified (see 6.2.1), equipment furnished under this specification shall comply with MIL-STD-461. The equipment and subsystems class and the emission and susceptibility requirement shall be as specified.

3.4 Components. The welding machine shall consist of, and be furnished with at least the following basic components: electrical system, electrodes and cable assemblies, enclosure portability, and portable attachments.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

3.4.1 Electrical system. Unless otherwise specified (see 6.2.1), the electrical system shall conform to NFPA 79. Each machine shall draw all of its electrical power from a single 230 volt, 1 phase, 60 Hz circuit. The electric input cable shall be not less than 5 feet in length.

3.4.1.1 Power supply unit. The power supply unit shall be solid state and shall include the transformer and control equipment.

3.4.1.1.1 Transformer. The transformer shall conform to the requirements of RWMA Bulletin Number 16 and shall have class B insulation or better.

3.4.1.1.2 Control equipment. Unless otherwise specified (see 6.2.1), a synchronous precision welding control unit conforming to, or equivalent to NEMA ICS 5 shall be provided in order that each half-cycle or full-cycle of welding current is uniform in amplitude and time. Control equipment shall be capable of operating on control circuit voltage which varies as much as ±10 percent from the voltage for which the equipment is adjusted. Operator controls shall be located convenient to the operator. All calibrations, phase shift controls, and similar characteristics shall be clearly marked in standard English industrial terminology.

3.4.1.1.2.1 Operator control panel. The operator control panel shall have a circuit breaker that will serve as an overload protection and as an "on-off" switch, a power "on" light, a current adjustment control, a weld timer, a weld processor selector control and weld power cable connections. All meters shall have accuracy of ±2 percent or better at full scale reading.

3.4.1.1.2.2 Current adjustment control. Unless otherwise specified (see 6.2.1), the variable adjustment control for the welding current shall have a capacity of heat adjustment with a range from a low of not more than 20 percent to a high of not less than 90 percent of maximum adjustment. The adjustment shall be by means of phase shift heat control, transformer tap switches or digital input selection of a combination thereof.

3.4.1.1.2.3 Weld timer. Unless otherwise specified (see 6.2.1), the weld timer range shall be in cycles of power source frequency. The cycle range shall be from a low of not more than 1/2 to a high of not less than 29 cycles. Unless otherwise specified (see 6.2.1), the repeat accuracy of the timer shall be zero cycles.

3.4.1.1.2.4 Weld process selector control. The spot, roll spot, and seam welding processes shall be controlled by a knob or switch selector. When the control is set for spot welding, actuating and releasing the switch on the electrode holder shall produce one spot weld. When the control is set for roll spot and seam welding, actuating and holding in the switch shall produce roll spot or seam welds according to the setting on the controls.

3.4.2 Electrodes and cable assemblies.

3.4.2.1 Electrodes. The machine shall be furnished with a spot welding electrode, a seam wheel welding electrode, and a ground electrode made of copper alloy conforming to RWMA Bulletin Number 16, Class 2 requirements and

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

of a style to make the specified welds using manual pressure. The ground electrode shall have a smooth tapered surface to insure good contact on the material being welded.

3.4.2.2 Welding and ground cables. All cables shall be the extra flexible, fine stranded type, with an oil resistant, synthetic rubber insulation. The cable shall be 4 AWG or larger in size. The cables shall be not less than 8 feet in length, measured from the machine connection to the handle of the electrode holder.

3.4.2.3 Electrode handles. The electrode handles shall be made of a heat resistant dielectric material or be finished with a heavy baked enamel coating. The welding electrode handles shall have an actuating switch of the push-button type, recessed in the handles. Each electrode handle shall be attached to its welding or ground cable, and ready for use.

3.4.3 Actuator switch control cables. The actuator switch control cables shall be type SO conforming to NFPA 79 not less than 8 feet long measured from the machine connection to the handles of the electrode holders. The cables shall be assembled to the switches in the electrode holders, and ready for use.

3.4.4 Enclosure and portability. The metal enclosure shall be constructed of corrosion resistant material or metal treated to resist corrosion. Ventilation cooling shall be adequate to prevent temperatures in excess of design requirements under operating conditions at rated power output. Cooling systems, when furnished, shall be the forced air type. The components shall be enclosed in one or more sheet metal cabinet with removable panels or doors. The cabinet shall have means for attaching handles and wheels for portability, or a 2 wheel cart may be provided to hold and transport the cabinet. The portability shall be such that the operator may tip the machine to a balanced position on the wheels and roll it over a shop floor or concrete apron. The wheels shall have solid rubber tires and antifriction bearings mounted on an axle not less than 1/2 inch in diameter. The wheel and tire assembly shall be not less than 8 x 1.75 inches in size. Provisions shall be provided for storing the welding, ground, and actuator cables inside the enclosure when not in use.

3.4.4.1 Welding cable support. The welding machine enclosure or cart frame shall be furnished with a telescoping cable support to hold the welding cables at the desired working level. The cable support shall be adjustable from a minimum of not more than 44 inches to a maximum of not less than 66 inches above the floor level. The machine shall have brackets fastened to the side of the cabinet or cart frame for coiling and storing the electric input cable when not in use.

3.4.5 Pneumatic system. Unless otherwise specified (see 6.2.1), the pneumatic system shall conform to ANSI B93.114M. The system shall have an air line filter, water trap, and oil mist lubricator, as necessary. The system shall include all devices such as pressure regulators, pressure reducers, solenoid valves, and check valves that are necessary to meet the requirements specified herein. Air pressure gauges shall be provided to indicate input air pressure in all lines that are downstream from a pressure control device.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

3.5 Performance. The welding machine shall be capable of joining two pieces of stainless steel, conforming to the requirements of AISI 302 Steel Products Manual, of equal thickness ranging from .001 to .010 inches inclusive with spot and roll spot welds, and from .001 to .008 inches with seam welds. The diameter of the spot welds and width of the seam welds shall be 3 x the thickness for the thinnest material thru 1.5 x the thickness of the thicker materials.

3.6 Stardard equipment. All standard equipment normally furnished with the manufacturer's commercial machine shall be furnished, if different (see 6.2.1).

3.7 Optional equipment. Optional equipment shall be furnished as specified (see 6.2.1).

3.8 Repair parts. Repair parts shall be furnished, as specified (see 6.2.1).

3.9 Marking of instruction plates, indicating plates and name plates. All words on instruction plates, indicating plates and name plates shall be in the English language. Characters shall be engraved, etched, embossed, or stamped in boldface on a contrasting background. When these methods are not practical, the instructions shall be applied directly on the item by environmentally protected decalcomania transfer, a metal wrap-around tag, stenciling, silk screening, or by any other method suitable for the use intended which shall be as permanent as the normal life expectancy of the item to which they are applied and shall be capable of withstanding the environmental test and cleaning procedures specified for the item.

3.9.1 Lubrication chart or plate. Unless otherwise specified (see 6.2.1), a lubrication chart or plate shall be permanently and securely attached to each welding machine. If a chart is furnished, it shall be placed in a transparent plastic folder, or permanently sealed between clear plastic sheets, with suitable means of mounting. The chart or plate shall contain the following information:

Points of lubricant application
Servicing interval
Type of lubricant
Viscosity

3.9.2 Nameplate. Unless otherwise specified (see 6.2.1), a corrosion resistant metal nameplate shall be securely attached to each welding machine. The nameplate shall contain the information listed below and that information required in RWMA Bulletin Number 16, Name and Rating Data Plates. If the welding machine is a special model, the model designation shall include the model of the basic standard welding machine and a suffix keyed to the manufacturer's permanent records. The captions listed may be shortened or abbreviated, provided the entry for each caption is clear as to its identify.

Nomenclature
Manufacturer's name

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

Manufacturer's model designation
Manufacturer's serial number
National Stock Number or Plant Equipment Code

3.10 Technical data. When technical data is required, it shall be furnished in accordance with the requirements of the contract.

3.11 Workmanship. Workmanship of the welding machine and accessories shall be of a quality equal to that of the manufacturer's commercial equipment of the type specified herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspections set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When specified (see 6.2.1) one complete welding machine shall be subject to the examination in 4.5 and the test in 4.6. Failure of any examination or test shall constitute failure of first article inspection.

4.4 Quality conformance inspection. Quality conformance inspection shall be applied to each item prior to being offered for acceptance under the contract. The quality conformance inspection shall consist of the examination in 4.5, the tests in 4.6. The machine shall pass the examination, all tests, and the inspection to be accepted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

4.5 Examination. Each machine shall be examined to determine compliance with all visual and dimensional requirements of this specification.

4.6 Tests.

4.6.1 Operational test. The welding machine shall be operated at no load for not less than 15 minutes. Proper operation of all controls, motors, adjusting mechanisms, and accessories shall be verified during the trial period.

4.6.2 Welding test. After the test in 4.6.1 has been completed and the power supply is at operating temperature, spot and seam welds shall be made. The test material shall be stainless steel panels, conforming to the requirements of AISI 302 Steel Products Manual, at least six inches long. The panels for the spot and roll spot welding test shall be .001 and .010 inch thick. The panels for the seam welding test shall be .001 and .008 inch thick. The welds shall be made using material of two equal thicknesses of the minimum and maximum thicknesses specified. Fifteen spot welds shall be made spaced 1/4 inch apart. Thirty roll spot welds shall be made 1/8 inch apart. A continuous seam weld shall be made six inches long. The diameter and width of the welds shall be as specified in 3.5. The welds shall be tested by pulling the material apart. There shall be no weld separations, and the material shall tear at the weld nuggets.

4.6.3 Continuous operation test. The machine shall be adjusted to the manufacturer's recommended settings to weld two pieces of .010 inch stainless steel. The machine shall operate continuously for 2 hours at 1800 simulated welds per hour. There shall be no overheating, arcing, or malfunctions of the machine. The welding test specified in 4.6.2 shall then be performed to demonstrate the machine capability to weld satisfactorily after the continuous operation test.

4.6.4 Electromagnetic interference control tests. Equipment requiring electromagnetic interference control shall be tested for compliance with 3.3.7 using the procedures given in MIL-STD-462.

4.7 Packaging inspection. Packaging of each item shall be inspected to determine compliance with the requirements of section 5.

5. PACKAGING

5.1 Packaging, packing, and marking. Unless otherwise specified, packaging, packing, and marking shall be in accordance with ASTM D 3951. When specified (see 6.2.1), level A or level B preservation, level A or level B packing and special marking shall be accomplished in accordance with MIL-W-45562.

6. NOTES

6.1 Intended use. The equipment covered by this specification is intended for use in the repair and fabrication of insulating blankets and honeycomb components used in jet aircraft, and for other related welding processes on heat resistant metal foil. The machine is intended for use in manufacturer's plants and military and contractor's repair shops.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. When first article is required for inspection and approval (see 3.1).

c. If machine is required to be configured in a specific measurement system (inch-pound or SI), state required system (see 3.2.1).

d. Additional safety and health requirements, if required (see 3.2.5)

e. Painting, if different (see 3.3.5).

f. If electromagnetic interference control is required, specify the equipment and subsystem class and the emission and susceptibility required (see 3.3.7)

g. Electrical system and input power supply, if different (see (3.4.1).

h. Control equipment, if different (see 3.4.1.1.2)

i. Current adjustment, if different (see 3.4.1.1.2.2).

j. Weld timer, if different (see 3.4.1.1.2.3).

k. Pneumatic system, if required (see 3.4.5).

l. Standard equipment, if different (see 3.6).

m. Specify and fully describe optional equipment required, if different (see 3.7).

n. Repair parts, if required (see 3.8).

o. Lubrication chart or plate, if different (see 3.9.1).

p. Nameplate, if different (see 3.9.2).

q. First article inspection, if different (see 4.3).

r. Level of packaging, packing and marking, if different (see 5.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

6.2.2 Contract data requirements. Required technical data such as operator's manuals, parts lists, wiring diagrams, and examination, original alignment and tolerance test reports and other instructions for operation and maintenance (as identified on a DD Form 1664, Data Item Description) should be specified on a DD Form 1423, Contract Data Requirements List, incorporated into the contract.

6.3 First Article. When first article inspection is required, the item to be tested should be the first item offered for acceptance under the contract. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

6.4 Safety health requirements. 29 CFR 1910 limits only the total hazard level (noise, radiation, electromagnetic emissions, noxious vapors, air contaminants and heat) of the environmental in which a machine will operate. It does not limit the hazard level of individual machines in an operating environment. The procuring activity is advised to analyze the existing hazard level in the proposed operating environment and specify additional requirements necessary to integrate this new machine into its future environment.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

6.6 Subject term (key word) listing.

Electric Welding
Joining
Metal Joining
Resistance Welding
Seam Welding
Seaming
Spot Welding

Custodians:

Army - AL
Air Force - 99

Preparing activity:

DLA-IP
(Project 3432-0139)

Review activities:

Army - AR
Air Force - 84
DLA - GS

User activities:

Army - SM, AV

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-W-80192C	Welding Machine, Resistance, Spot and Seam, Metal Foil, Single Phase, Portable

3a. NAME OF SUBMITTING ORGANIZATION

b. ADDRESS *(Street, City, State, ZIP Code)*

4. TYPE OF ORGANIZATION *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.