INCH-POUND

MS14181C
AMENDMENT 1
19 JUNE 1998

MILITARY SPECIFICATION SHEET

BOLT, TENSION, NICKEL ALLOY 718, 220 KSI Ftu, EXTERNAL WRENCHING, SPLINE DRIVE, FLANGED HEAD

This amendment forms a part of MS14181C, dated 30 January 1989, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

NOTE 7. Fourth sentence, after "PASSIVATION" add: "WITH DRY FILM LUBRICANT."

NOTE 7. After last sentence, add: "NO CODE AFTER GRIP LENGTH DASH NUMBERS INDICATES PASSIVATION ONLY."

NOTE 8. In third example of part number, after " UNDRILLED HEAD" add: ",PASSIVATED." Delete: "(INACTIVE FOR NEW DESIGN)"

NOTE 8. In fourth example of part number, after "DRILLED HEAD" add: ",PASSIVATED." Delete: "(INACTIVE FOR NEW DESIGN)"

Custodians:
Army - AV
Navy - AS
Air Force - 99

Preparing Activity:
DLA-IS

(Project 5306-2050)

AMSC N/A FSC 5306

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:36Z
Check the source to verify that this is the current version before use.