PPP-A-1182B
December 19, 1974
SUPERSEDING
Int. Fed. Spec. PPP-A-001182A(GSA-FSS)
May 5, 1970

FEDERAL SPECIFICATION

ALUMINUMWARE: BAKESHOP AND KITCHEN:
PACKAGING, PACKING, AND MARKING OF

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE

1.1 This specification covers the requirements for the packaging, packing, and marking of aluminum bakeshop and kitchenware (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

RR-B-500 - Boilers, Kettles, and Pots, (Aluminum Alloy).
RR-K-260 - Kitchen and Food Serving Utensils (Aluminum).
RR-P-54 - Pans, Aluminum Alloy.
PPP-B-585 - Boxes, Wood, Wirebound.
PPP-B-591 - Boxes, Shipping, Fiberboard, Wood-Cleated.
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock Corner.
PPP-B-636 - Boxes, Shipping, Fiberboard.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-L-10547 - Liners, Case and Sheet, Overwrap; Water-Vaporproof or Waterproof, Flexible.

FSC PACK

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-147 - Palletized Unit Loads for 40 inch by 48 inch Pallets.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza., Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Material. The material used in the packaging and packing shall be as specified herein and in the applicable specifications. The material shall be free from all defects and imperfections which may affect the serviceability of the packaging and packing.

3.2 Compatibility of container. The container closure, lining, or space fillers shall not interact physically or chemically with the contents of the container so as to be altered or to alter the strength, quality, or purity of the container contents.

3.3 Packaging. Packaging shall be level A, B, or C, as specified (see 6.2).

3.3.1 Level A.

3.3.1.1 Unit wrapping and positioning. Aluminumware shall be unit wrapped as specified below, in quantities specified in table I.

3.3.1.1.1 Aluminumware. Aluminumware shall be individually wrapped in two sheets of minimum basis weight of ten pounds per ream (24 x 36 - 500) kraft paper. Multiple piece items (double boilers, percolators, pots with covers, etcetera) shall be wrapped, each part separately, before assembly.

3.3.1.1.2 Nestable aluminumware. Aluminumware of one type, style, class and size only, individually wrapped as specified above, shall be nested in quantities as noted in table I where practical, to reduce cube, except that disposable pie pans shall not be wrapped.

3.3.1.1.3 Partially nestable aluminumware. Partially nestable aluminumware having handles or other attachments which prevent nesting to full depth of the item shall have scored corrugated fiberboard pads or taped corrugated fiberboard tubes placed between the items. The corrugation of the inserts shall be parallel to the vertical dimensions of the item and height shall be adequate to allow minimum 1/4 inch clearance between handles, ears, or other attachments and the point of contact with the item.

3.3.1.1.4 Long handle aluminumware. Domestic type double boilers, dippers, ladles, or similar items having long handles, in the quantities as specified in table I, shall be nested into two stacks. The stacks shall be separated by a sheet of corrugated fiberboard made of the same material as the box, and the bowl section of one stack shall be adjacent to the handle section of the other stack.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

3.3.1.1.5 Sets. Aluminumware to be procured as sets (like items of various sizes), where possible, shall have each complete set packaged in one box. The smaller size items shall be nested within the larger size items, where practical, separated by a sufficient amount of cushioning material to prevent movement, one within another. Cushioning material shall consist of scored and folded corrugated fiberboard pads, clean kraft paper, cellulose wadding, shredded paper, or single-faced corrugated paper cushioning material.

3.3.1.1.6 Strainer, china cap with or without wood roller. The strainer with or without wood rollers shall be packaged in the most compact manner in a box and immobilized with cushioning material as specified in 3.3.1.1.5.

3.3.1.2 Unit package. All aluminumware except disposable pie pans, wrapped as specified in 3.3.1.1 in the quantities specified in table I, shall be packaged in a close-fitting corrugated fiberboard box conforming to PPP-B-636, type CF, class domestic. Each box shall be closed in accordance with the appendix to the box specification. Disposable pie pans shall not be unit packaged. When specified (see 6.2), the fiberboard box shall conform to PPP-B-636, grade V3c, V3s or V4s, and shall be closed in accordance with Method IV of the appendix to PPP-B-636.

3.3.2 Level B. Aluminumware shall be packaged as specified in 3.3.1 except that unit wrapping shall be accomplished with one sheet of minimum 10 pound basis weight per ream (24 x 36 - 500) kraft paper.

3.3.3 Level C (Commercial Packaging). Aluminumware shall be packaged to afford adequate protection against physical damage during shipment from the supplier to the first receiving activity. The package and the quantity per package shall be the same as that normally used by the supplier for retail distribution.

3.4 Packing. Packing shall be level A, B or C as specified (see 6.2).

3.4.1 Level A. Aluminumware, packaged as specified in 3.3, shall be packed in the quantities and placement, as specified in table I, in snug-fitting shipping containers conforming to PPP-B-636, grade V2s; PPP-B-591, class II; PPP-B-601, overseas type; PPP-B-585, style 1, 2 or 3, class 3; or PPP-B-621, class 2, style 2 or 4. Each fiberboard shipping container shall be waterproofed by means of tape in accordance with the appendix to PPP-B-636. Other shipping containers shall be provided with a type I or II, grade C case liner conforming to MIL-L-10547. Shipping containers packed with weather resistant grade unit packages need not be waterproofed. Each shipping container shall be closed and reinforced in accordance with the appendix to the applicable container specification. When specified (see 6.2), fiberboard shipping containers shall not be used.

3.4.2 Level B. Aluminumware, packaged as specified in 3.3, shall be packed in quantities and placement as specified in table I in close-fitting shipping boxes conforming to PPP-B-636, type CF or SF, class domestic, style RSC. Each box closed in accordance with the appendix of the box specification.

3.4.2.1 When specified (see 6.2), the shipping container shall conform to PPP-B-636, grade V3c, V3s or V4s and shall be closed in accordance with method III of the appendix to PPP-B-636.

3.4.3 Level C (Commercial Packing). Aluminumware, packaged as specified in 3.3, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. The quantity per shipping container shall be the same as that normally used by the supplier for retail distribution. The shipping containers shall comply with the Uniform Freight Classification rules or National Motor Freight Classification rules, as applicable.

3.5 Palletization. When specified (see 6.2), aluminumware of one description only, packed as specified in 3.4, shall be palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be banded with primary and secondary straps in accordance with loading means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

3.6 Marking. Marking shall be in accordance with 3.6.1 or 3.6.2 as specified (see 6.2).

3.6.1 Civil agencies. In addition to any special marking required by the contract or order, unit packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

3.6.2 Military requirements. In addition to any special marking required by the contract or order, unit packages and shipping containers shall be marked in accordance with MIL-STD-129.

3.7 Workmanship. The workmanship of the packaging, packing and marking shall conform to the quality established by this specification.

TABLE I. Packaging and Packing

Nomenclature	Applicable Specification	Type	Style	Size No.	Size Capacity	Unit Package No. of Items	Shipping Container No. of Pkgs.	Shipping Container Placement L W D	Shipping Container No. of Items
BOILERS									
Coffee									
Double, Domestic	RR-B-500	II	A	1	3 qt.	4	4	212	16
Double, Institutional	RR-B-500	II	B	1	5-1/2 qt.	1	12	322	12
Double, Institutional	RR-B-500	II	B	2	8 qt.	1	8	222	8
Double, Heavy Duty	RR-B-500	II	C	1	11 qt.	2	4	221	8
Double, Heavy Duty	RR-B-500	II	C	2	17-1/2 qt.	1	4	221	4
Double, Heavy Duty	RR-B-500	II	C	3	8 qt.	1	8	222	8
BOWLS									
Food Mixing	RR-K-260	I		1	5-1/2 qt.	4*	12	223	48
Food Mixing	RR-K-260	I		3	20 qt.	4*	2	112	8
COLANDER,									
Institutional	RR-K-260	II		1	11 qt.	2	6	321	12
Institutional	RR-K-260	II		2	16 qt.	2	6	321	12
DIPPERS, KITCHEN									
Institutional	RR-K-260	III		1	30 oz.	3	8	222	24
Institutional	RR-K-260	III		2	64 oz.	3	18	323	54
KETTLES, TEA									
With cover, Loop handle and Spout	RR-B-500	III			4 qt.	1	12	322	12
Open Top with Bail and Pouring Lip	RR-B-500	V	D	1	24 qt.	3	2	211	6
MEASURES, LIQUID									
Bakers, Flanged Lip	RR-K-260	IV	A	1	1/2 qt.	6	12	322	72
Baker, Flanged Lip	RR-K-260	IV	A	2	1 qt.	6	16	422	96
Baker, Flanged Lip	RR-K-260	IV	A	3	2 qt.	6	8	421	48
Baker, Flanged Lip	RR-K-260	IV	A	4	4 qt.	6	4	411	24
Measuring	RR-K-260	IV	B		1 cup	12	18	323	216
PANS									
Baking and Roasting									
Domestic, Baking	RR-P-54	I		1	13-1/4 by 9-1/4 in.	3*	8	222	24
Institutional, Baking	RR-P-54	I		2	17-13/16 by 11-7/8 in.	6*	4	221	24
Institutional, without stacking straps	RR-P-54	I		3	23-7/16 by 13-7/16	6*	2	211	12
Roaster, Double, Top section	RR-P-54	I		4	24 by 18 in.	2*	3	311	6

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

TABLE I. Packaging and Packing (con.)

Nomenclature	Applicable Specification	Type	Style	Size No.	Size Capacity	Unit Package No. of Items	Shipping Container No. of Pkgs.	Shipping Container Placement L W D	Shipping Container No. of Items
PANS (con.)									
Roaster, Double, Bottom Section	RR-P-54	I		5	24 by 18 in.	2*	3	311	6
Baking Sheet	RR-P-54	II		1	25-1/8 by 17-1/8 in.	6*	1	111	6
Baking Sheet	RR-P-54	II		2	12-1/2 by 9 in.	12*	1	111	12
Cake, Round, Domestic Layer	RR-P-54	III	A		9 in. dia.	6*	8	222	48
Cake, Rectangular Institutional	RR-P-54	III	B		21-1/2 by 13-1/2 in.	6*	2	211	12
Dish, Domestic	RR-P-54	VI		1	14 qt.	4*	3	311	12
Dish, Institutional	RR-P-54	VI		2	21 qt.	3*	3	311	9
Muffin, 12 Cups, Institutional	RR-P-54	IV	A		14-3/4 by 11-3/16 in.	6*	5	511	30
Muffin, 12 Cups	RR-P-54	IV	B		12-7/8 by 9-7/8 in.	6*	5	511	30
Sauce, with Long Handle, Institutional									
Deep	RR-P-54	VII	A	1	1-1/2 qt.	4	15	531	60
Deep	RR-P-54	VII	A	2	2-1/2 qt.	2	9	331	18
Deep	RR-P-54	VII	A	3	4-1/2 qt.	2	6	321	12
Deep	RR-P-54	VII	A	4	8-1/2 qt.	1	4	221	4
Tapered	RR-P-54	VII	B	1	1-1/2 qt.	6*	9	331	54
Tapered	RR-P-54	VII	B	2	2-3/4 qt.	6*	4	221	24
Tapered	RR-P-54	VII	B	3	3-3/4 qt.	6*	4	221	24
Pie	RR-P-54	V	A		9 in. dia.	6*	16	224	96
Pie	RR-P-54	V	B		9 in. dia.	N/A	N/A	N/A	1000
Pudding	RR-P-54	VIII		1	1 qt.	12*	4	221	48
Pudding	RR-P-54	VIII		2	3 qt.	12*	4	221	48
POACHER, EGG	RR-K-260	V			1-1/2 or 2 qt.	4	4	212	16
POTS									
Coffee Boiler	RR-B-500	IV			4 qt.	4	2	211	8
Cooking, Sauce, with Loop Handles									
Domestic	RR-B-500	V	A	1	14 qt.	2	4	221	8
Domestic	RR-B-500	V	A	2	16 qt.	1	4	221	4
Institutional	RR-B-500	V	B	1	12 qt.	1	4	221	4
Cooking, Stock, Deep Institutional Heavy Duty with Loop Handles	RR-B-500	V	C	1	11 qt.	2	4	221	8
Heavy Duty with Loop Handles	RR-B-500	V	C	2	20 qt.	1	4	221	4
Heavy Duty with Loop Handles	RR-B-500	V	C	3	32 qt.	1	4	221	4
Heavy Duty with Loop Handles	RR-B-500	V	C	4	40 qt.	1	2	211	2
Heavy Duty with Loop Handles	RR-B-500	V	C	5	60 qt.	1	1	111	1
SCOOPS, KITCHEN	RR-K-260	VI			1 qt.	6	8	222	48

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

TABLE I. Packaging and Packing (con.)

Nomenclature	Applicable Specification	Type	Style	Unit Package Size No.	Unit Package Size Capacity	Unit Package No. of Items	Shipping Container No. of Pkgs.	Shipping Container Placement L W D	Shipping Container No. of Items
SHAKERS, SALT AND PEPPER, COOKS									
Salt	RR-K-260	VIII	A		9 cu. in.	12	8	222	96
Pepper	RR-K-260	VIII	B		9 cu. in.	12	8	222	96
SIEVES, FLOUR, BAKERS	RR-K-260	VII			16 in. top dia 3-1/2 deep	2	6	213	12
STRAINER China Cap with or without wood roller	RR-K-260	IX			10 in. dia.	4	6	321	24

*See 3.3.1.1.2

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling for inspection and acceptance. Sampling for inspection and acceptance shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated.

4.3 Inspection. An inspection shall be made to determine that the packaging, packing, and marking as required by this specification are complied with. Defects shall be scored in accordance with Table II. The sample unit shall be one shipping container fully prepared for delivery. The lot shall be the number of containers offered for delivery at one time. The inspection level shall be S-2 with an acceptable quality level (AQL) of 4.0, expressed in terms of defects per hundred units.

TABLE II. Classification of defects

Examine	Defects
Marking (exterior and interior container)	Omitted, incorrect, illegible, of improper size location, sequence, or method of application.
Materials	Component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of case liners or container flaps, loose strapping or tape banding, inadequate stapling, bulging or distortion of containers.
Contents (exterior and interior)	Contents per container is more or less than required.

4.4.1 Examination of palletization. When palletization is required, examination shall be made to determine that palletization is in compliance with this specification. Defects shall be scored as specified in table III. The sample unit for this examination shall be one palletized unit load ready for shipment. The lot shall be the number of palletized unit loads submitted for inspection at one time. The inspection level shall be S-1 with an AQL of 6.5, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

TABLE III. Examination of palletization

Examine	Defects
Finished dimension	Length, width, or height exceeds maximum requirement.
Palletization	Not as specified. Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps specified. Pallet damaged. Straps not properly tensioned to immobilize the load.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

5. THIS SECTION IS NOT APPLICABLE TO THIS SPECIFICATION.

6. NOTES

6.1 Intended use. It is intended that this specification be used for reference in section 5 of Aluminumware, Bakeshop and Kitchen, commodity specifications. It is also intended to be used for direct reference in procurement documents. The packaging, packing, and marking requirements, specified herein, are intended to insure proper and safe storage to or shipments processed at a Government agency.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Level of packaging required (see 3.3).
(c) Level of packing required (see 3.4).
(d) Marking required (see 3.6).
(e) When class weather-resistant containers are required (see 3.3.1.2 and 3.4.1.2).
(f) When wood shipping containers are required (see 3.4.1).
(g) When palletization is required (see 3.5).

MILITARY INTERESTS:

Custodians:

Army - GL
Navy - SA
Air Force - 84

Review activities:

Army - MD
Navy - MS, SA, YD

User activities:

Navy - MC, CG

Preparing activity:

GSA-FSS

CIVIL AGENCY INTEREST:

GSA-FSS
VA-DMS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price 30 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.