PPP-B-1087B
March 31, 1983
SUPERSEDING
PPP-B-1087A
September 27, 1974

FEDERAL SPECIFICATION

BAG, COTTON DUCK (SOIL AND GRAIN)

This specification is approved by the Assistant Administrator, Office of Federal Supply and Services, General Services Administration, for use of all Federal Agencies.

1. SCOPE This specification covers the requirements for a plain selvage top bag, made up of cotton duck, designed without hem, grommets, or draw string, with a capacity of 1 bushel.

2 APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specification:

PPP-B-636 - Boxes, Shipping, Fiberboard.

Federal Standards:

Fed. Std. No. 123 - Marking for Shipment (Civil Agencies).
Fed. Std. No. 751 - Stitches, Seams and Stitchings.

(Activities outside the Federal Government may obtain copies of Federal specifications, standards, and commercial item descriptions, as outlined under General Information in the Index of Federal Specifications, Standards, and Commercial Item Descriptions. The Index, which includes cumulative bimonthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification, other Federal specifications, and commercial item descriptions required by activities outside the Federal Government for bidding purposes are available without charge from General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta; GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Houston, TX, Denver, CO; Los Angeles, CA; San Francisco, CA; and Seattle, WA.

(Federal Government activities may obtain copies of Federal standardization documents, and the Index of Federal Specifications, Standards and Commercial Item Descriptions from established distribution points in their agencies.)

Military Standard:

MIL-STD-105 Sampling Procedures and Tables for Inspection by Attributes

(Copies of military specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Association, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

FSC 8105

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials.

3.1.1 Cloth, cotton duck. The cloth shall be hard texture, minimum weight 11.16 ounces per square yard, a minimum break of 195 pounds in the warp direction, and a minimum of 120 pounds in the filling direction. The warp yarns shall be plied and the filling yarns shall be singles or plied (see 4.4.1 for test requirements)

3.1.2 Thread. The thread shall be 4-ply cotton glazed, with a minimum length per pound of 2,811 feet and a maximum of 3,880 feet, with a minimum breaking strength of 7.5 pounds.

3.2 Dimensions. The dimensions of the bag shall be 17 inches ± 1 inch in width and 32 inches -0 inches, +2 inches in length

3.3 Stitching. All stitching shall conform to types 301 and 401 of Fed. Std. No. 751, four to six stitches per inch. Thread breaks in stitching shall be overstitched not less than 1 inch at each break for type 301 stitching or 1-1/2 inch for type 401 stitching. The ends of each continuous row of stitches may be anchored by backstitches for a length of not less than 1 inch, except where anchorage is provided by another seam or stitching. Alternatively, a 3/4 inch bartack may be used instead of backstitches.

3.4 Construction. The bag shall be constructed of a single width of material folded in half, with one double row of stitches, not less than 1/2 inch from the edge of the material, forming the side opposite the fold. Two rows of stitches across one open end not less than 1/2 inch from the edge of the material, shall form the bottom of the bag. The thread tension shall be maintained to prevent loose stitching All outside thread ends shall be trimmed.

3.5 Workmanship. The bags shall be free from defects which affect their serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein Except where otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling for examination and tests. Sampling for examination, inspection, and physical tests shall be performed using the procedures prescribed by MIL-STD-105.

4.3 Inspection of the end item.

4.3.1 Examination of the end item. The sample unit for this examination shall be one bag. The inspection level shall be S-2 with an acceptable quality level (AQL) of 4.0 expressed in terms of percent defective.

4.3.1.1 Examination of the end item for visual defects and workmanship. The sample unit shall be one bag selected at random and taken from any one shipping container. Defects in appearance shall be holes, cuts, or tears in fabric; open seams, wrong seams or stitch type, margin of stitching less than specified, too loose or too tight stitching, and number of stitches not as specified, stains on bag or not properly trimmed, and malfunction in closing of bag.

4.3.1.2 Examination for dimensional defects. Defects in dimensions shall be smaller or larger than dimensions specified.

4.3.1.3 Examination of preparation for delivery. An examination shall be made to determine compliance with the requirements of section 5. The sample unit shall be one container fully prepared for delivery. Sampling shall be in accordance with MIL-STD-105. The inspection level shall be S-2 with an AQL of 4.0 expressed in terms of percent defective.

4.4 Test methods The following tests shall be conducted for breaking strength of cloth used in the fabrication of the bags Failure of test shall be cause for rejection

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

4.4.1 Breaking strength. Ten specimens per lot of woven cloth (4 by 6 inches with long dimensions parallel to the direction being evaluated) shall be tested as follows: Each specimen shall be placed in a machine which is equipped with a constant rate of extension straining mechanism. The distance between the clamps at the start of each test shall be 3 inches, and the clamps shall travel at a uniform rate of 12 inches ± 0.5 inch per minute. The force required to break the specimens shall be read from the recording mechanism. The breading strength shall be the average of the results and reported to the nearest pound.

5. PREPARATION FOR DELIVERY

5.1 Packing. Packing shall be level A or commercial, as specified (see 6.2).

5.1.1 Level A. Each bag, compactly folded, in quantities as specified (see 6.2), shall be packed in a close fitting fiberboard box conforming to PPP-B-636, class weather-resistant. The box shall be closed, waterproofed, and reinforced in accordance with the appendix to PPP-B-636.

5.1.2 Commercial. The bags shall be packed in fiberboard boxes to insure delivery at destination, to provide for redistribution by the initial receiving activity, and shall be acceptable by common carrier under National Motor Freight Classification and Uniform Freight Classification.

5.2 Marking. In addition to the marking specified in the contract or order, marking shall be in accordance with Fed. Std. No. 123.

6. NOTES

6.1 Intended use. This specification describes cotton duck bags for use in handling soil, grain, etc.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Level of packing (see 5.1).

CIVIL AGENCIES COORDINATING ACTIVITIES:

GSA - FSS
VA - OSS

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.