INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

BOX, CORRUGATED FIBERBOARD, HIGH COMPRESSION STRENGTH, WEATHER-RESISTANT, WAX-RESIN IMPREGNATED

This interim amendment was developed by the General Services Administration, Federal Supply Service, Washington, DC 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this interim amendment as a valid exception to Federal Specification PPP-B-1163B, dated February 27, 1970, and Amendment-2 dated July 23, 1974.

Delete Appendix as written and substitute the following:

APPENDIX

10. SCOPE

10.1 This appendix covers requirements for the closure of boxes fabricated in accordance with the requirements of this specification.

20. APPLICABLE DOCUMENTS

20.1 The following specifications and standards, of the issue in effect on date of invitation for bids, form a part of this appendix to the extent specified herein:

Federal Specifications:

QQ-S-781 - Steel, Strapping, Flat
PPP-S-760 - Strapping, Nonmetallic (and Closure Seals)
PPP-T-60 - Tape, Pressure-Sensitive, Adhesive
PPP-B-636 - Boxes, Shipping, Fiberboard

30. REQUIREMENTS

30.1 Closure. Boxes shall be closed in accordance with appendix to PPP-B-636 (weather-resistant) with the following exceptions:

1. Slotted style boxes for produce may have stitched closures in accordance with common carrier rules.

2. Tape shall conform to Federal Specification PPP-T-60 and shall be a minimum of 3 inches wide.

3. The glue used does not have to conform to MMM-A-750 as specified in Method III of the appendix of PPP-B-636 (see note).

4. Style HSCS shall be closed as follows. Unless otherwise specified, prior to loading, this box shall be placed on a pallet or wood skid. The pallet or skid shall be 1-inch longer and 1-inch wider than the box. The box shall be closed and secured by means of strapping conforming to QQ-S-781, type I, class A or B or PPP-S-760, type I, grade B,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

type II and III. Two straps, positioned approximately 10 inches from the edge of the box, shall be placed lengthwise around the box. These straps shall be placed either on top or underneath the pallet or skid. Straps shall also be placed girthwise around the box; within 6 inches of each end; and one additional strap for every 24 inches of box length. The straps shall be placed under or through the pallet or skid in such a manner as not to be changed during the handling and shipping.

5. Slotted style boxes serving as outer containers for flexible plastic inner containers for liquids may have stitched closures in accordance with common carrier rules, providing weather-resistant corrugated or solid fiberboard pads are placed under the flaps to keep the stitches from puncturing the liquid container.

NOTE: Due to the variation in waxed boxes from different manufacturers, activities planning to use adhesive closures are advised to test their adhesives for compatibility with the boxes they intend to use. A hot melt adhesive may be necessary.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.