PPP-T-001471
June 10, 1968
SUPERSEDING
(See 6.2)

INTERIM FEDERAL SPECIFICATION

TOOL EQUIPMENT TE-49, PACKAGING, PACKING, AND MARKING OF

This Interim Federal Specification was developed by the Federal Supply Service, General Service Administration, Washington, D. C. 20405, based upon currently available technical information. It is recommended that Federal agencies use it for procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE

1.1 This specification covers the requirements for preservation, packaging, packing, and marking of Tool Equipment TE-49 for storage and shipment.

2. APPLICABLE DOCUMENTS

2.1 Specifications and standards. The following specifications and standards, of the issues in effect on the date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

T-T-871 - Twine, Cotton, Wrapping.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Box, Fiberboard.
PPP-F-320 - Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.
PPP-T-60 - Tape; Pressure-Sensitive Adhesive, Waterproof for Packaging and Sealing.

Federal Standards:

Fed. Std. No. 123 - Marking For Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C., 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Ft. Worth, Denver, San Francisco, Los Angeles, and Seattle, Washington.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specifications:

MIL-P-116 - Preservation, Method Of.
MIL-B-117 - Bags, Interior, Packaging.
MIL-B-121 - Barrier Material, Greaseproofed, Flexible (Waterproofed).
MIL-B-131 - Barrier Material, Water-Vaporproof, Flexible.
MIL-L-10547 - Liners, Case, Waterproof.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specification and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:51Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

Uniform Freight Classification Rules.

(Application for copies should be addressed to the Uniform Classification Committee, 202 Union Station, Chicago, Illinois, 60606.)

National Motor Freight Classification Rules.

(Application for copies should be addressed to the National Classification Board, 1616 P Street N. W., Washington, D. C., 20036.)

3. REQUIREMENTS

3.1 Material. Material shall be as specified herein. Material not definitely specified shall be of good commercial quality, entirely suitable for the purpose. Material shall be free from all defects and imperfections that affect the serviceability or performance of the preservation, packaging, and packing requirements prescribed herein.

3.2 General requirements. The components of Tool Equipment TE-49 shall be preserved, packaged, and packed in accordance with the provisions outlined below.

3.3 Preservation and packaging. Preservation and packaging shall be level A or C, as specified (see 6.1).

3.3.1 Level A. Tool Equipment TE-49 shall be preserved and packaged in accordance with the procedures specified for the designated methods as prescribed in MIL-P-116 and as described in 3.3.1.1 through 3.3.1.5.

3.3.1.1 Test Set TS-190/U. Each test set shall be packaged method IA-8 as follows: Wind cords into a coil of proportionate dimensions and tie in three places with cotton twine conforming to T-T-871, type I, 6-ply. Secure plugs and headsets to coil with ties. Cushion each test set by wrapping in single-face, flexible, corrugated fiberboard conforming to PPP-F-320. Secure the wrap with gummed paper tape conforming to PPP-T-60. Enclose each cushioned test set within a close-fitting bag fabricated of barrier material conforming to MIL-B-131. Heat seal to effect closure.

3.3.1.2 Hand tools. Each hand tool shall be packaged method I, as follows: Clean and preserve metal parts of all hand tools (include exposed metal surfaces of electrical hand tools, which shall not be dipped) prior to placement within the unit package, following procedure as specified in MIL-P-116 for C-1 cleaning and P-7 preservative. Wrap the preserved metal parts in greaseproof barrier material conforming to MIL-B-121, type II, to resist penetration of cutting edges and secure with tape conforming to PPP-T-60.

3.3.1.3 Gage. Each gage shall be packaged method IC-1 as follows: Clean and preserve each gage prior to placement within the unit package, following procedures specified in MIL-P-116 for C-5 cleaning and for P-7 preservation. Wrap the preserved gage in greaseproof barrier material conforming to MIL-B-121, type I, grade A, class 2. Place the cushioned gage within a close-fitting bag conforming to MIL-B-117, type II, class C. Heat seal to effect closure.

3.3.1.4 Sets. Tool sets, having bags or cases, shall be placed within their respective bags or cases and secured.

3.3.1.5 Tool Box. Each tool box shall be packaged method IC-5 as follows: Stow the items specified in 3.3.1.2 through 3.3.1.4 within the appropriate compartments of the tool box. Fill the voids with flexible corrugated fiberboard conforming to PPP-F-320. Close the tool box and secure all fastenings. Cushion the chest on all surfaces with cells or pads or both, with corrugated fiberboard conforming to PPP-F-320, grade not less than 200. Place the cushioned chest in a fiberboard box conforming to PPP-B-636, class weather-resistant, W5c. Closure shall be in accordance with the appendix to PPP-B-636. In addition, all seams and joints shall be sealed with tape conforming to PPP-T-60.

3.3.2 Level C. Tool Equipment TE-49 shall be packaged in accordance with commercial practice in a manner that will afford protection against corrosion, deterioration, and physical damage during direct shipment to the first receiving activity.

3.4 Packing. Packing shall be level A, B, or C, as specified (see 6.1).

3.4.1 Level A. Tool Equipment TE-49, packaged as specified in 3.3, shall be packed in a box conforming to PPP-B-621, class 2. The box shall fit the contents snugly. Shipping containers being shipped to ports shall be strapped in accordance with the appendix to PPP-B-621.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:51Z
Check the source to verify that this is the current version before use.

3.4.2 Level B. Tool Equipment TE-49, packaged as specified in 3.3, shall be packed in a fiberboard box conforming to PPP-B-636, class domestic.

3.4.2.1 When specified (see 6.1), the fiberboard box shall conform to PPP-B-636, class weather-resistant, W5c or W5s.

3.4.3 Level C. Tool Equipment TE-49, packaged as specified in 3.3, shall be packed for shipment in containers conforming to the requirements of the Uniform Freight Classification Rules or National Motor Freight Classification Rules.

3.5 Marking.

3.5.1 Civil agencies. Each unit package shall be marked with the Federal stock number, nomenclature, and quantity. Each shipping container shall be marked in accordance with Fed. Std. No. 123 and shall include the contract and purchase order numbers. Any special markings required by the contract or order (see 6.1), shall also be included.

3.5.2 Military agencies. In addition to any special markings required by the contract or order (see 6.1) interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

3.6 Workmanship. Workmanship shall be of the highest grade throughout.

4. QUALITY ASSURANCE PROVISIONS.

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification when such inspections are deemed necessary to assure that supplier's services conform to prescribed requirements.

4.2 Visual examination. An examination shall be made to determine compliance with the requirements in table I. The inspection level shall be S-4, with an AQL of 4 percent for major defects and 10 percent for minor defects, in accordance with MIL-STD-105.

TABLE I. Classification of defects for visual inspection.

MAJOR

1. Two or more items having different stock numbers in the same unit package. This does not include those instances where a unit package contains a stock numbered item which in itself consists of several subitems, each of which has its own stock number assigned.
2. Material which is bulk packaged when unit packaging is required.
3. Critical portions of material not properly preserved.
4. Incorrect packaging material used.
5. Incorrect quantity in unit package.
6. Insufficient cushioning, blocking, and bracing which could cause material to become damaged.
7. Unsealed, punctured, or improperly sealed barrier, bag, wrap, envelope.
8. Evidence of improper cleaning.
9. Improper type of preservative.
10. Wrong or defective barrier or wrapping materials.
11. Container damaged, unserviceable.
12. Stock number omitted, incorrect, or unreadable.

MINOR

1. Unsealed carton.
2. Defective taping or sealing of carton (poor adherence).
3. Air not expelled from barrier.
4. Package not in accordance with weight limitation.
5. Container damaged but serviceable.
6. Conforming wraps are not snug-fitted and contain voids.
7. Cushion wraps do not fill the containers snugly, resulting in full contact not being made with all surfaces.
8. Closure not properly made.
9. Marking blurred but legible.

4.3 Examination of preservation and packaging. Where preservation and packaging is specified to be in

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:51Z
Check the source to verify that this is the current version before use.

accordance with MIL-P-116 an examination shall be made to determine that the requirements of MIL-P-116 are met.

5. PREPARATION FOR DELIVERY

5.1 Not applicable to this specification.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein and shall include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Level of preservation, packaging, and packing (see 3.3 and 3.4).
(c) When special type of fiberboard box is required for level B (see 3.4.2.1).
(d) Special markings required (see 3.5.1 and 3.5.2).

6.2 Supersession data. This specification includes the requirements of MIL-T-11493 (SigC).

MILITARY CUSTODIANS:

Army - SM
Navy - AS
Air Force - 43

Review activities:

Army - EL

Preparing activity:

GSA - FSS

GSA DC 69-310

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:51Z
Check the source to verify that this is the current version before use.