METRIC

A-A-59441/2

16 January 2004

COMMERCIAL ITEM DESCRIPTION SPECIFICATION SHEET

VAPOR CORROSION INHIBITORS, TYPE II

The General Services Administration has authorized the use of this commercial item description, for all federal agencies.

The complete requirements for procuring Type II vapor corrosion inhibitors (VCIs) described herein shall consist of this document and the latest issue in effect of A-A-59441.

1. SCOPE. This commercial item description covers the requirements for Type II VCIs to provide corrosion protection for metals used in mechanical, electrical and electronic components and equipment that are subjected to corrosive environments inside of enclosures.

2. SALIENT CHARACTERISTICS.

2.1 Physical characteristics. See Table I.

2.2 Performance. VCI emitters shall not interfere with or modify the electrical, optical, or mechanical surface properties of the materials within the enclosure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:14Z
Check the source to verify that this is the current version before use.

TABLE I. Physical characteristics.

VAPOR CORROSION INHIBITORS -- TYPE II								
Item	**Description**	**Application**	**Protection Volume m^3 (ft^3)**	**Protection Life (yr)**	**Metals Protected**	**Length cm (in)**	**Width or Diameter cm (in)**	**Height cm (in)**
	RANGE OF PROTECTED VOLUME < 0.15 ft^3 [< 0.005 m^3]							
1	Plastic tab, thin, rigid, VCI	Use in thin channels between circuit boards or electrical, electronic equipment, both in operation or packaged for storage or shipment.	.003 (.1)	2	MM	1.2 to 1.4 (.47 to .53)	1.2 to 1.4 (.47 to .53)	.1 to .2 (.04 to .08)
	RANGE OF PROTECTED VOLUME 0.15 to 0.35 ft^3 [0.005 to 0.01 m^3]							
2	Plastic tab, thin, rigid, VCI	Use in thin channels between circuit boards or electrical, electronic equipment, both in operation or packaged for storage or shipment.	0.006 (.2)	2	MM	1.8 to 2.0 (.7 to .8)	1.8 to 2.0 (.7 to .8)	.1 to .2 (.04 to .08)
3	Tablet, VCI	Use in small cavities, components or subassemblies packaged in corrugated boxes, plastic wrap or bags.	0.008 (.3)	0.5	MM	.96 to 1.06 (.38 to .42)	--	.7 to .8 (.28 to .31)
	RANGE OF PROTECTED VOLUME 0.35 to 0.70 ft^3 [0.01 to 0.02 m^3]							
4	Plastic tab, thin, rigid, VCI	Use in thin channels between circuit boards or electrical, electronic equipment, both in operation or packaged for storage or shipment.	.01 (.4)	2	MM	2.5 to 3.3 (1.0 to 1.3)	2.5 to 3.3 (1.0 to 1.3)	.1 to .2 (.04 to .08)
5	Tablet, VCI	Use in small cavities, components or subassemblies packaged in corrugated boxes, plastic wrap or bags.	.01 (.5)	0.5	MM	.96 to 1.06 (.38 to .42)	--	.7 to .8 (.28 to .31)
6	Foam or rigid assembly	For metal components and electrical and electronic assemblies.	.014 (.5)	2	MM	2.5 to 3.3 (1.0 to 1.3)	2.5 to 3.3 (1.0 to 1.3)	1.4 to 1.6 (.55 to .63)
	RANGE OF PROTECTED VOLUME 0.7 to 1.5 ft^3 [0.02 to 0.04 m^3]							
7	Tablet, VCI	Use in small cavities, components or subassemblies packaged in corrugated boxes, plastic wrap or bags.	.03 (1)	0.5	MM	.96 to 1.06 (.38 to .42)	--	.7 to .8 (.28 to .31)
8	Plastic tab, thin, rigid, VCI	Use in thin channels between large circuit boards, bottom or side of chassis or tool box.	.03 (1)	2	MM	7 to 9 (2.8 to 3.5)	2.5 to 3.3 (1.0 to 1.3)	.1 to .2 (.04 to .08)
9	Pouch, VCI	Protect products, components or assemblies packaged in corrugated boxes, plastic wrap or bags, and metal, plastic or wood containers.	.03 (1)	2	MM	5 to 8 (2 to 3)	5 to 8 (2 to 3)	1.3 to 1.8 (.5 to .7)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:14Z
Check the source to verify that this is the current version before use.

TABLE I. Physical characteristics - Continued.

VAPOR CORROSION INHIBITORS -- TYPE II								
Item	**Description**	**Application**	**Protection Volume m^3 (ft^3)**	**Protection Life (yr)**	**Metals Protected**	**Length cm (in)**	**Width or Diameter cm (in)**	**Height cm (in)**
	RANGE OF PROTECTED VOLUME 0.7 to 1.5 ft^3 [0.02 to 0.04 m^3]							
10	Tablet, VCI	Protect products, components or assemblies packaged in corrugated boxes, plastic wrap or bags, and metal, plastic or wood containers.	0.007 (.25)	2	MM	?	?	?
	RANGE OF PROTECTED VOLUME 3.5 to 7.0 ft^3 [0.10 to 0.20 m^3]							
11	Foam pad	For metal components and electrical and electronic assemblies.	.14 (5)	2	MM	24 to 27 (9.5 to 10.6)	5.0 to 6.0 (2.0 to 2.4)	.5 to .7 (.20 to .28)
	RANGE OF PROTECTED VOLUME 7 to 14 ft^3 [0.2 to 0.4 m^3]							
12	Foam pad	For metal components and electrical and electronic assemblies.		2	MM	24 to 27 (9.5 to 10.6)	24 to 26 (9.5 to 10.3)	.5 to .7 (.20 to .28)
13	Plastic sheet, thin, oval, VCI	Use in thin channels between large circuit boards, bottom or side of chassis or tool box.		2	MM	30 to 33 (12 to 13)	13 to 15 (5.0 to 6.0)	.1 to .2 (.04 to .08)
	RANGE OF PROTECTED VOLUME 700 to 1400 ft^3 [20 to 40 m^3]							
14	VCI Diffuser, rigid assembly	Use in large equipment or vehicle, control cabinets, both in operation and packaged in shrink film, bags, crates.	25 (900)	1	MM	18 to 23 (7 to 9)	10 to 13 (4 to 5)	4.8 to 5.3 (1.9 to 2.1)
15	VCI Diffuser, rigid assembly	Use in large equipment or vehicle, control cabinets, both in operation and packaged in shrink film, bags, crates.	25 (900)	2	MM	18 to 23 (7 to 9)	10 to 13 (4 to 5)	4.8 to 5.3 (1.9 to 2.1)
	RANGE OF PROTECTED VOLUME 2 to 4 ft^3 per linear foot of tape or tubing [0.2 to 0.4 m^3 per linear m]							
16	Plastic tubing, stiff	Use in ferrous pipes and tubes up to 2 inches in diameter with closed ends, also rifle and gun barrels.		2	F	290 to 320 (950 to 1050)	.6 to .7 dia (.24 to .28)	--

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:14Z
Check the source to verify that this is the current version before use.

TABLE I. Physical characteristics - Continued.

Item	Description	Application	Protection Volume m^3 (ft^3)	Protection Life (yr)	Metals Protected	Length cm (in)	Width or Diameter cm (in)	Height cm (in)
	VAPOR CORROSION INHIBITORS -- TYPE II							
	RANGE OF PROTECTED VOLUME 4 to 8 ft^3 per linear foot of tape or tubing [0.8 to 0.8 m^3 per linear m]							
17	VCI Diffuser assembly, 10 diffuser units on 1/2" plastic strap	Use in pipes and tubes up to 0.3m (1 ft) in diameter, multimetal structures, electrical wiring, contacts, electronics, cannons, missiles.		2	MM	12 to 13 (39 to 42)	2.5 to 3.3 (1.0 to 1.3)	--
	RANGE OF PROTECTED VOLUME 8 to 16 ft^3 per linear foot of tape [0.8 to 1.6 m^3 per linear m]							
18	VCI Diffuser assembly, 16 diffuser units on 1/2" plastic strap	Use in pipes and tubes up to 0.6m (2 ft) in diameter, multimetal structures, electrical wiring, contacts, electronics, cannons, missiles.		2	MM	12 to 13 (39 to 42)	2.5 to 3.3 (1.0 to 1.3)	--

Key: MM = Multi-metal; F = Ferrous; NF = Non-ferrous

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:14Z
Check the source to verify that this is the current version before use.

3. National stock numbers (NSNs). Table II provides NSNs that correspond to this CID. The list may not be indicative of all possible NSNs associated with the CID.

TABLE II. National stock numbers.

Item	Standard Package	NSN
1	1000 pieces / carton	TBD
2	1000 pieces / carton	TBD
3	1000 tablets / bottle	TBD
4	1000 pieces / carton	6850-01-362-9256
5	600 tablets / bottle	TBD
6	1000 pieces / carton	6950-01-426-3539
7	300 tablets / bottle	TBD
8	300 pieces / carton	TBD
9	300 pouches per carton	8030-01-208-1769
10	1000 tablets per bottle	TBD
11	250 pieces / carton	TBD
12	250 pieces / carton	TBD
13	100 pieces / carton	TBD
14	4 individually wrapped units per carton	TBD
15	4 individually wrapped units per carton	6850-01-348-1390
16	1 individually wrapped unit per package	TBD
17	1 individually wrapped unit per package	TBD
18	1 individually wrapped unit per package	TBD

MILITARY INTERESTS

Custodians:
Navy – SH
Air Force – 99

Review Activity:
DLA – CC

CIVIL AGENCY COORDINATING ACTIVITY:
GSA - FSS

Preparing Activity:
Navy – SH
(Project 2090-0118-002)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:14Z
Check the source to verify that this is the current version before use.