[INCH-POUND]
A-A-59493
25 August 1999
SUPERSEDING
MIL-T-40629B
3 October 1985

COMMERCIAL ITEM DESCRIPTION

TRUCK, FORK, REACHING AND TIERING, STAND UP RIDER, ELECTRIC, NON PALLET STRADDLING, SHIPBOARD

The General Services Administration has authorized the use of this Commercial Item Description as a replacement for MIL-T-40629 which is canceled.

1. SCOPE. This specification covers stand-up rider, type EE, electric powered, shipboard, reach and tiering type fork trucks.

2. CLASSIFICATION. The forklift trucks shall be of the following classifications as specified (see 7.2).

Type 1 - 4000 pound capacity, 58 inch overall height
Type 2 - 4000 pound capacity, 68 inch overall height
Type 3 - 4500 pound capacity, 58 inch overall height
Type 4 - 4500 pound capacity, 68 inch overall height
Type 5 - 5000 pound capacity, 68 inch overall height

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Naval Inventory Control Point, 5450 Carlisle Pike, P.O. Box 2020, Mechanicsburg PA 17055-0788.

AMSC N/A FSC 3930

DISTRIBUTION STATEMENT A: Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

3. SALIENT CHARACTERISTICS:

3.1 Configuration. This commercial item description covers the types of electric forklifts listed below. In addition to the requirements stated elsewhere in this CID, each type of forklift truck must be able to meet the following characteristics:

Characteristic	Type 1	Type 2	Type 3	Type 4	Type 5
CAPACITY AT 24 IN. LOAD CENTER AND TO FULL LIFT HEIGHT	4000 LBS..	4000 LBS..	4500 LBS..	4500 LBS..	5000 LBS..
MAXIMUM OVERALL HEIGHT	58 IN.	68 IN.	58 IN.	68 IN.	68 IN.
MINIMUM FREE LIFT HEIGHT	18 IN.	20 IN.	18 IN.	20 IN.	20 IN.
MAXIMUM TURNING RADIUS (OUTSIDE)	82 IN	82 IN.	82 IN.	82 IN.	88 IN.
BATTERY CAPACITY	680 AMP HR.	870 AMP HR.	680 AMP HR	870 AMP HR	870 AMP HR.
MAXIMUM TRUCK WEIGHT(NO LOAD WITH BATT.)	7200 LBS.	7200 LBS.	7200 LBS.	7200 LBS.	8800 LBS..

3.2 Safety. The forklift shall comply with ASME B56.1, UL 583 and with the Occupational Safety and Health Standards in effect at time of manufacture. The trucks shall bear the UL stamp of approval for the EE safety rating. Use of thermoplastic hoses such as SAE 517, 100R7 or 100R8 is prohibited.

3.3 Motors. All motors including traction motors shall be designed for operation on 24 volt direct current.

3.4 Battery and battery accessories. Battery capacity for truck shall be as listed in paragraph 3.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

3.5 Electrical connectors. Truck shall be equipped with standard EC mounting half connectors. The locking half mounted on the battery shall be located so that it can be actuated by the operator without leaving the compartment. Locking half connector including mounting hardware shall be fastened to the battery with bolts and not welded so that connector and hardware can be removed and reinstalled.

3.6. Lubricants. The truck shall operate using only those lubricants listed in MIL-HDBK-267.

3.7 Structure. The frame and related structure shall be capable of withstanding 300 per cent overload without permanent deformation.

3.8 Forks. The forks and fork carrier shall conform to ANSI B56.11.4 or may be of the shaft type. Fork dimensions shall be 40 inches long, 4.125 inches wide, maximum and 2.125 inches thick, maximum. Fork spacing, measured between the outer edges of the forks, shall be 28 inches minimum spread and 16.5 inches maximum together. With no load on the forks, the operator shall be able to see at least one fork tip at all lift heights and fork positions.

3.9 Fork position. Forks when not centered during lowering operation shall stop between 13 inches and 9 inches(top of level forks to deck) at all reach positions from zero to maximum, at any amount of sideshift, right and left and any amount of load from zero to rated. Latter dimensions shall be adjustable from 14 inches to 9 inches. The lifting surfaces of the forks shall measure 3 inches plus minus .25 inches from the deck in the lowest fork position. Adjustment shall be provided to change this dimension from 4 inches to 2 inches plus minus .25 inches. With the forks level, centered, between the base legs, and at the lowest position, clearance between the deck and the bottom of the entire reach mechanism, shall be 1 inch minimum at all reach distances from zero to maximum and with any amount of load on the forks from zero to rated.

3.10 Load centering system. The truck shall be equipped with a load centering system which shall prevent the fork carriage from being lowered below the base legs unless the fork carriage is centered. The system also shall prevent side shift when the forks are below the base legs. The system shall include a green light mounted on the panel which shall indicate when the forks are centered.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

The load centering system shall function with the forks in any reach position from full retracted to fully extended.

3.11 Base legs. Overall height of base legs shall not exceed 6 inches (152 mm) when truck is empty, and overall width of the base legs shall not exceed the maximum allowable width of the truck. Base leg plates shall protect the top and sides of the load wheels.

3.12 Reach mechanism. The reach mechanism shall be a pantograph type and a sliding mast is not acceptable. It shall permit extension of the forks or fork assembly to a point where the front vertical face of the forks measures from 0 to .50 inch in front of the forward edge of the load wheels or base legs to permit handling of loads at deck level that are off center laterally or would otherwise conflict with the base legs or load wheels. With the forks level, centered, between the base legs, and at the lowest position, clearance between the deck and the bottom of the entire reach mechanism, shall be 1 inch minimum at all reach distances from zero to maximum and with any amount of load on the forks from zero to rated. Bottom of the reach mechanism shall be chamfered 45 degrees by .25 inches to .50 inches, front and rear lowest edges. Clearance and chamfer is required to prevent the base of the reach mechanism from contacting and bending shipboard elevator ramps during unloading/loading operations. Positive means shall be provided to prevent the rollers from leaving the reach track, such as a bar welded across the top of the track. Reach mechanism shall be strong enough to withstand accidental damage when side shifting the forks.

3.13 Wheels. There shall be two single steer/drive wheels and four load wheels two in each base leg. Wheels, when equipped with new tires, shall clear any part of the truck structure and mast structure by at least .25 inch under all conditions of operation.

3.14 Tires. The tires shall conform to sizes and loadings as listed in the Tire and Rim Association (T&RA) Handbook and shall be static discharge type conforming to UL 583 type "EX". The drive tires shall have a minimum thickness of 2.13 inches. Tire size for drive wheels shall be not less than 10 inches outside diameter by 6 inches face. Each drive tire shall provide a minimum of 15 square inches of tire to deck contact area. The load wheels shall be not less than 5 inches diameter by 3.5 inches face

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

3.15 Steering. Power steering shall be provided. Steering shall be accomplished by a horizontal hand steering wheel. A steering lever or tiller is unacceptable.

3.16 Service brakes. The service brakes shall be of the hydraulic activated and mechanically released type. Brakes shall be designed to release in case of failure of the system, brakes shall not fail in the "on" mode. Brake lining shall be of the non-asbestos type.

3.17 Travel disconnect. Travel disconnect system shall be provided, such that upon removal of the operator's foot from a pedal located for left foot operation on both the operator's platforms, the current to the traction motors will be interrupted and the drive wheel brakes will be applied. The control system shall be so designed that when the circuit is broken, it can be activated only by resetting the directional control(s) when the operator assumes the operating position.

3.18 Parking brake. A hand operated parking brake with locking device shall be installed.

3.19 Operator's compartment. The operator's compartment shall provide two platform levels. Distance from deck of ship to lowest platform shall be 7 inches minimum, 12 inches maximum. Distance from lowest platform to upper platform shall be 9 inches and height of operators compartment shall be 53 inches from deck of ship. Upper platform shall provide a minimum of 19.5 inches wide by 14 inches deep at controls level and a minimum of 15.5 inches wide and 14.5 inches deep at floor level, deadman brake, service brake, and parking brake assembly excepted. Lower platform shall provide a minimum depth of 11 inches. Compartment shall have three enclosed sides with unobstructed entrance from the rear. Design of compartment shall allow truck operator to stand within plan outline of truck when truck is being operated and when truck is not being operated. Means shall be provided for operator to maintain his balance when stopping suddenly while backing up, such as a vertical steel plate or a rubber pad on the side of the compartment.

3.20 Slinging and tie down provisions. Permanently affixed slinging and tie down provisions that enable the truck to be lifted in its normal travel position and to be fastened to the floor or deck of a transportation medium shall be provided. Provisions shall conform to MIL-STD-209, Classes 1 and 2 or Class 3 for type II or III equipment, excluding air transport requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

3.21 Sideshift attachment. The truck shall be equipped with a sideshift attachment. Side shifter shall provide for a minimum movement of 3 inches on each side of center with rated load.

3.21.1 Alignment marks for side shift mechanism. Provide two alignment marks on frame or side shift fork carriage and two matching marks on the mast or non-shifting main fork carriage to assist operator in aligning side shift mechanism to center position.

3.22 Master switch. A key operated master switch shall be provided such that its removal deactivates all electrical control circuits. All trucks under each contract shall be keyed identically. Two (2) keys shall be supplied with each truck.

3.23 Hour meter. An electrically operated hour meter which registers the total number of hours of operation of the traction and pump motors shall be provided.

3.24 Flood light. The truck shall be equipped with one white sealed beam, 25 watt minimum floodlamp, shock mounted in an elastometer ring housing on the left side of the mast. Directional adjustment range of this light shall be a minimum of 45 degrees above and below the horizontal plane. Horizontal adjustment range shall be a minimum of 300 degrees to illuminate front and rear areas. Adjustments shall not require use of hand tools. Adequate protection against damage, by means of position or guard, shall be provided. Light shall be mounted on a bracket which can be rotated to eliminate interference with the battery cover.

3.25 Warning device. The truck shall be equipped with an operator controlled warning device (e.g. horn).

3.26 Battery protector. Each truck shall be equipped with a battery protector to protect the battery from a dangerously low state of charge.

3.27 Wheel Position Indicator. Truck shall have a wheel position indicator showing the position of at least one of the steerable drive wheels and visible to the operator in operating position.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

3.28 Fork carriage indicator. Truck shall be equipped with a green indicator light which glows green when the fork carriage is centered and it is safe to lower the forks to their lowest position (between the base legs) without any interference of the forks or carriage parts with any part of the truck. The light shall be installed on the panel in front of the operator where it is in sight of the operator at all times.

3.29 Lifting speed. Minimum lifting speed over the entire distance from the ground to maximum fork height shall be 35 feet per minute empty and 30 feet per minute carrying rated load.

3.30 Lowering speed. The minimum lowering speed unloaded, from maximum fork height to ground shall be 80 feet minute.

3.31 Extension and retraction time. Trucks shall be capable of fully extending and retracting the forks, with rated load on forks, in not less than 2.5 seconds nor more than 5 seconds maximum.

3.32 Reach. The minimum reach shall be 19.125 inches.

3.33 Speed. While carrying rated capacity on a level deck, trucks shall be capable of attaining a travel speed of 4 to 4.5 miles per hour in forward and reverse directions.

3.34 Slope ascension, forward direction. Trucks with and without rated load shall be capable of ascending straight up an 18 percent slope, in the forward direction.

3.35 Fork tilt. When carrying rated load, truck forks shall provide forward tilt of 2 degrees, plus or minus 0.5 degree and 4 degrees, minimum rearward tilt, plus or minus 0.5 degree.

3.36 Lift height. The minimum fork height when bearing rated capacity load, measured from the ground to the load carrying surface of the forks and with a 24 inch load center, shall be not less than 68 inches.

3.37 Extended height. The maximum height of the forklift with the mast in its fully extended position shall be 96 inches.

3.38 Overall length. The maximum truck overall length shall be 105 inches.

3.39 Overall width. The maximum truck overall width shall be 42.5 inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

3.40 Underclearance. The truck with rated load shall have sufficient underclearance to permit safe operation from one horizontal plane to another without scraping or dragging, using a slope of 18 percent. Underclearance beneath the mast assembly, when in a true vertical position with rated load in retracted position shall be not less than 2.75 inches. Underclearance shall be not less than 2.75 inches under the entire truck, except the space under the truck can be 1.75 inches minimum for a distance of 10 inches back from the rear load wheel and 10 inches in front of the drive wheel, both sides. Both distances are measured from the center lines of the wheel axles.

3.41 Lift assembly drift. The lift assembly shall be capable of holding the rated load at maximum height and extension with not more than 1.75 inches of vertical and extension drift and not more than 1 degree of rotational drift from the vertical for a minimum of than 10 minutes.

3.42 Sideshift interference. No parts of the truck including mast assembly, forks, or related structures shall show any damage, permanent deformation, or failure if the mast is lowered with the forks fully side shifted left or right or if the forks are side shifted left or right when the forks are below the load arms of the truck.

3.43 Stability. The truck carrying rated load shall have longitudinal stacking stability on a 4 percent slope, longitudinal traveling stability on an 18 percent slope, lateral stacking stability on a 6 percent slope, lateral traveling stability on a 27 percent slope, rearward stacking stability on an 18 percent slope, rearward traveling stability on a 30 percent slope and static stability on a 46.5 percent slope.

3.44 Acceleration. From a standing start, when carrying the specified rated load, the truck shall have an average acceleration rate in the forward direction such as to negotiate a distance of 22 feet in 7 seconds. There shall be not more than one second delay in the movement of the truck when the truck is accelerated.

3.45 Stopping distance. Truck, with rated load, shall be capable of stopping from either forward or rearward maximum speeds in the distance indicated in ASME B56.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

3.46 Parking brake and travel disconnect system. The parking brake and the travel disconnect system shall each be capable of retaining the truck with rated load on an 18 percent slope in both forward and reverse directions. Testing of brakes shall be accomplished only with the truck ascending specified slope in forward direction.

3.47 Resistance to saline atmosphere. All truck components shall withstand the corrosive effect of salt fog in accordance with MIL-STD-810 Method 509.2 Salt Fog without any loss of performance of the truck.

3.48 Power consumption. The truck shall be able to be cycled continuously for 6 hours with one battery only and no recharging is allowed.

3.49 HI (High-Impact) shock requirement. The truck and the battery as a component of the truck shall withstand a type A high shock as a grade A Item in accordance with MIL-S-901.

3.50 Electromagnetic interference control. Trucks shall be equipped for control of electromagnetic interference in accordance with MIL-STD-461. For radiated emissions, procedure RE102 shall be used with limits shown in Figure RE102-1 over a frequency range of 10 KHZ to 1 GHZ. For susceptibility to electric fields, procedure RS103 shall apply with a frequency range from 10 KHZ to 1 GHZ at a limit level of 10 Volts/Meter.

3.51 Rain. The truck shall be capable of performing all its normal operations after being subjected to a heavy water spray of not less than four(4) inches per hour for a period of one hour.

3.52 Reliability. Truck shall complete 2000 laps around an endurance course without failure.

3.53 Shipboard ramp traverse. Truck shall be able to negotiate shipboard door sill ramps.

3.54 Treatment and painting. All exterior surfaces of the truck shall be thoroughly cleaned, primed and painted in accordance with standard commercial practice. The finish coat shall be yellow color 13538 of FED-STD-595. Paint shall be lead free and chromate free. The mast may be painted black.

3.55 Information plates. The truck shall be equipped with the following information plates conforming to A-A-50271, composition C. Plates shall be furnished and installed by the contractor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

3.55.1 Identification plate. Each forklift shall be equipped with an identification plate that shall be in accordance with ASME B56.1 in addition to the following: truck nomenclature such as, "TRUCK, LIFT, FORK, ELECTRIC, SOLID TIRES", contract number, lifting capacity, lift height, USN registration number, shipping weight, cube dimension, name or stamp of government inspector, date shipped, technical manual stock number, high shock test date, warranty expiration date and manufacturer's name and address.

3.55.2 Shipping data plate. Each forklift shall be equipped with a shipping data plate that shall show silhouette of the forklift in transport position indicating the center of gravity and the location and capacity of the lifting and tie down attachments.

3.55.3 Instruction, warning and caution plates. Each forklift shall be equipped with instruction plates including warnings, cautions and diagrams describing any special or important procedures to be followed in assembling, operating or servicing the forklift. Commercially proven decals may be substituted for these instruction plates.

3.55.4 Side shift centering warning plate. Forklift shall be equipped with a plate in center of cross assembly facing operator at eye level having the following information:

WARNING

CENTER ALIGNMENT MARKS
BEFORE LOWERING FORKS
FORKS WILL NOT LOWER TO DECK
UNLESS GREEN LIGHT IS ON

3.55.5 Fork centering light plate. Truck shall be equipped with a plate under the light with the following information: "FORK CENTERING LIGHT, WHEN LIGHT IS ON, FORKS ARE CENTERED".

3.55.6 Wheel loading plate. Each forklift shall be equipped with a wheel loading plate to show wheel loading on each wheel when the forklift is carrying the rated load and when the forklift is unloaded.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

3.55.7 Safety designation plate. Each forklift shall be equipped with a safety designation plate to show the truck manufacturer's name, the truck's complete model number, the safety designation (Type EE), independent testing laboratory's name, independent testing laboratory's registration or index number assigned to the inspected truck, and the date and location of the independent laboratory's inspection.

3.55.8 Battery plate. Each forklift shall be equipped with a battery plate to show the battery weight, dimensions, ampere-hour capacity at a 6-hour rate, voltage, number of cells, number of plates, cable lead length and position.

3.56 Body marking. The USN number shall be indelibly stamped into the external plate of the truck body on the right side of the truck approximately 6 inches below the center of the entrance to the operator's compartment. Marking shall be in 0.25 in high block letters and numbers.

3.57 Vehicle marking. The vehicle shall be marked in black block letters, unless otherwise indicted, as follows.

3.57.1 USN registration number. The assigned USN registration number shall be painted in block numbers 1.5 inches high on each side of the truck.

3.57.2 Vehicle weight. The words, "VEHICLE WEIGHT" followed by the forklifts's empty weight shall be painted on each side of the truck in numbers 2 inches high.

3.57.3. Safe working load. Each truck shall be marked with the letters "SWL" followed by the truck's rated lifting capacity on each side of the mast in 2 inch high letters and numbers. White numbers and letters may be used when the mast is painted black.

3.57.4 Safety designation. The safety designation (EE) shall be painted on each side and the rear of the truck in accordance with UL 583 and NFPA 505.

3.57.5 Slinging and tie down. Slinging and tie down markings shall be in accordance with MIL-STD-209.

3.57.6 No rider. "No Rider" warning shall be painted in 2 inch letters on the rear of the mast.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

3.57.7 Paint. The words "Painted with lead free and chromate free paint on (MM/YY) by (Contractor Name)" shall be painted in 1/4 inch high letters on each side of the truck.

3.57.8 Brake linings. The words "Non-asbestos brake linings used. Replacements to be non-asbestos." shall be painted in 1 inch high letters on the truck.

3.57.9 Shipboard use. Each truck shall be marked with the words "SHIPBOARD USE APPROVED" in 1.5 inch high letters on each side and rear of the truck. Batteries shall be marked with the words "SHIPBOARD CERTIFIED" in a conspicuous place on the battery case in 1 inch high letters.

3.57.10 Structural testing. Each truck shall be marked with the words "STRUCTURALLY TESTED", the test date and the manufacturer's name in 1/4 inch high letters on each side of the truck.

4. REGULATORY REQUIREMENTS.

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR). However, used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the forklift.

5. QUALITY ASSURANCE PROVISIONS.

5.1 Contractor certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this Commercial Item Description and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices. Also, the item delivered is substantially the same product offered for sale in the commercial marketplace or is the same product that has been delivered to the government on a previous contract or purchase order. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

5.2 Warranty. Unless otherwise specified in the contract or purchase order, the manufacturer's standard commercial warranty shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

6. PACKAGING. Preservation, packaging , packing and marking for shipment shall be specified in the contract or order.

7. NOTES.
(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

7.1 Reference documents.

Government Documents.

Specifications, standards and handbooks. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 7.2).

SPECIFICATIONS

FEDERAL

A-A-50271 Plate, Identification

DEPARTMENT OF DEFENSE

MIL-S-901 Shock Tests, HI (High Impact) Shipboard Machinery, Equipment, and Systems, Requirements For Navy.

STANDARDS

FEDERAL

FED-STD-595 Colors.

DEPARTMENT OF DEFENSE

MIL-STD-209 Slinging Eyes and Attachments for Lifting and Tying Down Military Equipment.

MIL-STD-461 Electromagnetic Emission And Susceptibility Requirements For The Control Of Electromagnetic Interference.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

MIL-STD-810 Environmental Test Methods and Engineering Guidelines.

HANDBOOK

DEPARTMENT OF DEFENSE

MIL-HDBK-267(SH) Guide for Selection of Lubricants and Hydraulic Fluids for use in Shipboard Equipment.

(Unless otherwise indicated, copies of Federal and Military specifications, standards, and handbooks are available from DODSSP Standardization Document Order Desk, 700 Robins Ave., Philadelphia, PA 19110-5094).

7.1.2 Other Government Documents, Drawings and Publications.

DEPARTMENT OF LABOR(DOL)

29 CFR, Chapter XVII, Part 1910 - Occupational Safety and Health Standards (OSHA)

(Application for copies should be addressed to the Superintendent of Documents, U.S., Government Printing Office, Washington, D.C. 20402).

Non-Government publications. Unless otherwise specified, the issues of the document which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 7.2).

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

B56.1 Safety Standard For Powered Industrial Trucks.

B56.11.4 Forks and Fork Carriers for Powered Industrial Trucks.

(Application for copies should be addressed to: American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017-22392).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

J517 - Hydraulic Hose.

(Application for copies should be addressed to: Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096-0001).

UNDERWRITERS LABORATORIES, INC. (UL)

UL 583 Standard for Electric-Battery-Powered Industrial Trucks

(Application for copies should be addressed to: Underwriters' Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062)

THE TIRE AND RIM ASSOCIATION, INC. (T&RA)

Tire and Rim Association Yearbook

(Application for copies should be addressed to the Tire and Rim Association Inc., 175 Montrose West Ave., Suite 150, Copley, OH 44321).

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

NFPA 505 Fire Safety Standard for Powered Industrial Trucks Including Type, Designation, Area of Use, Conversions, Maintenance and Operation.

(Application for copies should be addressed to: National Fire Protection Association, 1 Batterymarch Park, P.O. Box 9101, Quincy, MA 02269-9101.)

7.2 Ordering data. Acquisition documents shall specify the following:

(a) Title, number and date of this commercial item description.

(b) Type required. (See 3.1)

(c) Issue of the DODISS cited in the solicitation and if required, the specific issue of individual documents referenced.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

(d) When a government first article inspection is required, location where user test is to be conducted and required government clearances.

(e) When a technical manual verification review is required, location where review is to be conducted and required government clearances.

7.3 Technical Manuals. The requirements for technical manuals should be considered when this commercial item description is applied on a contract. If technical manuals are required, military specifications and standards that have been cleared and listed in DOD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL) must be listed on a separate Contract Data Requirements List (DD Form 1423), which is included as an exhibit to the contract. The technical manuals must be acquired under separate contract line item in the contract.

7.3.1 Technical manual verification review. When a government technical manual verification is required (see 7.2), the government will conduct the review as specified herein.

7.3.1.1 Technical manual verification review. The technical manual verification review will be conducted by the government to validate that the truck's final technical manual accurately reflects the truck configuration, general information, operating instructions, safety rating, preventative maintenance, repair and overhaul, illustrated parts breakdown and parts list index. The truck will be operated only to the extent required by the technical manual to ensure that each section of the manual is accurate. Repair and overhaul operations will not be conducted, but will be reviewed for clarity. The illustrated parts breakdown and parts list index will be reviewed to the extent possible without major disassembly of the truck. The manual review shall be conducted after successful completion of first article inspection. The truck shall be available for review for a period of fourteen consecutive calendar days. Government review will be conducted in accordance with instructions in the contract or purchase order. In the event the technical manual does not accurately reflect the truck, a written list of discrepancies will be included in the prefinal technical manual review comments.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

7.3.1.2 Delivery. The contractor shall deliver one preproduction truck to the Naval facility specified herein (see 7.2). The cost of transportation to and from the test site shall be borne by the contractor. The contractor shall provide notification of truck shipment to the contracting officer and the Naval facility a minimum of 20 days prior to shipment.

7.3.1.3 Contractor personnel. When requested by the contractor and approved by the government, contractor's personnel may witness the review. When required (see 7.2), government clearance for contractor personnel will be provided. The cost of transportation and billeting contractor personnel shall be borne by the contractor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

Custodian:

Navy - SA

Review Activities:

Navy - SH

Preparing Activity:

Navy - SA

Project No. 3930-0709

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7, and send to preparing activity.

3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	**1. DOCUMENT NUMBER** A-A-59493	**2. DOCUMENT DATE (YYYYMMDD)** 19990825

3. DOCUMENT TITLE **TRUCK, FORK, REACHING AND TIERING, STAND UP RIDER, ELECTRIC, NON PALLET STRADDLING, SHIPBOARD**

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON *(if applicable)*	**7.DATE SUBMITTED** (YYYYMMDD)

8. PREPARING ACTIVITY

a. NAME NAVAL INVENTORY CONTROL POINT CODE 1041	b. TELEPHONE *Include Area Code)* (1) Commercial (717) 605-4024 (2) AUTOVON 430-4024
c. ADDRESS *(Include Zip Code)* 5450 CARLISLE PIKE, P.O. BOX 2020 MECHANICSBURG, PA 17055-0788	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** Defense Standardization Program Office (DLSC-LM) 8725 John J. Kingman road, Suite 2533, Ft. Belvoir, VA 22060-2533 Telephone (703) 767-6888 AUTOVON 427-6888

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:16Z
Check the source to verify that this is the current version before use.