MILITARY SPECIFICATION

COMPRESSOR UNITS: DIESEL-ENGINE-DRIVEN, HIGH PRESSURE

This specification is approved for use by the Naval Facilities Engineering Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers wheel-mounted, diesel-engine-driven, air compressors, with a maximum capacity of 750 cubic feet per minute (cfm), nominal, at 250 pounds per square inch gage (psig).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

WW-C-633 - Couplings, Hose, (Half), Pneumatic, Universal Type.

MILITARY

MIL-V-173 - Varnish, Moisture-and Fungus-Resistant (For Treatment of Communications, Electronic, and Associated Equipment).

MIL-C-3600 - Compressors, Rotary, Power-Driven; and Compressors, Reciprocating Power-Driven; Air and Gas (Except Oxygen and Refrigerant), Packaging of.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 4310

Source: https://assist.dla.mil -- Downloaded: 20260-20T22:19Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-209 - Slinging and Tiedown Provisions for Lifting and Tying Down Military Equipment.
MS51336 - Lunette-Coupler, Drawbar, Ring.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other Government documents, drawings, and publications. The following other Government documents form a part of this specification to the extent specified herein.

DEPARTMENT OF TRANSPORTATION (DoT)

Federal Motor Vehicle Safety Standards and Regulations.

(Application for copies of DoT should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

2.4 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DODISS and the supplement thereto, if applicable.

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Boiler and Pressure Vessel Code, Section VIII - Pressure Vessels.
Power Test Code, PTC-9 - Displacement Compressors, Vacuum Pumps and Blowers.

(Application for copies should be addressed to the American Society of Mechanical Engineers, P.O. Box 3199, Grand Central Station, New York, NY 10163.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)

Code of Federal Regulations, Title 40, Part 204 Subpart B - Noise Emission Standards for Construction Equipment.

(Application for copies should be addressed to the Public Affairs Office, Environmental Protection Agency, Rockville, MD 20852.)

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE Handbook.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:19Z
Check the source to verify that this is the currentversion before use.

TIRE AND RIM ASSOCIATION, INC.

T&RA Yearbook.

(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 West Market Street, Akron, OH 44313.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Description. The compressor unit shall consist of a diesel engine, air compressor, receiver, air pressure regulating system, lubricating and cooling systems, safety controls, steel housing, and the piping, instruments, gages, and other accessories specified herein all assembled and mounted on a wheel-mounted undercarriage.

3.2 First article. When specified (see 6.2), the contractor shall furnish one complete compressor for first article inspection and approval (see 4.2.1 and 6.5).

3.3 Standard commercial product. Each compressor unit shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the compressor unit being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs, or brochures, and represents the latest production model.

3.3.1 Federal Motor Vehicle Safety Standards. When specified (see 6.2), wheeled undercarriages and furnished accessories shall comply with all applicable Federal Motor Vehicle Safety Standards (FMVSS) in effect on the date of manufacture.

3.4 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification unless otherwise specified.

3.5 Identical items. All compressor units furnished under any specific contract shall be physically and mechanically identical. This requirement includes parts, assemblies, components, and accessories. No deviations will be acceptable without written approval of the contracting officer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:19Z
Check the source to verify that this is the current version before use.

3.6 Performance. The compressor unit shall be capable of compressing and delivering not less than the nominal volume of free air, 750 cfm, at a receiver pressure of 250 psig under the following atmospheric conditions:

a. 14.696 pounds per square inch absolute (sea level).
b. 60° Fahrenheit (F).
c. Zero humidity.

Under the conditions specified, the air discharge temperature shall not exceed 250°F. The compressor shall be capable of operating satisfactorily when tilted 15° longitudinally or transversely from a level position.

3.6.1 Regulation. Regulation of compressor output shall be accomplished by a stepless, pneumatic control system. The system shall be adjustable within limits established by the manufacturer and shall be set to automatically maintain a nominal discharge pressure of 250 psig when the compressor is operating at full rated capacity. The system shall also provide for automatic regulation of compressor output from zero to 100 percent of rated capacity. Primary regulation shall be affected by the proportional and automatic reduction of engine speed within the range of full-rated-capacity speed to a speed not less than the engine manufacturer's recommended idle speed. Supplemental control may be accomplished by the proportional and automatic actuation of a compressor inlet unloader valve.

3.6.2 Environmental conditions. The compressor shall be capable of starting and operating under the following atmospheric conditions:

a. Plus 120°F to -25°F at sea level (29,92 inches of mercury).
b. Plus 102°F to -25°F at an elevation of 5,000 feet (24.89 inches of mercury).

3.6.3 Safety shutdown. The compressor shall be equipped with a safety shutdown system designed to automatically stop the engine under any of the following conditions:

a. Compressor discharge air temperature in excess of safe limit established by the manufacturer but in no case exceeding 250°F.
b. Engine cooling water temperature in excess of the manufacturer's established limit.
c. Engine lubricating oil pressure below minimum manufacturer's established limit.

When specified (see 6.2), the engine shall also be equipped with an overspeed trip to automatically stop the engine in the event the engine speed exceeds the lesser of either the maximum speed recommended by the engine manufacturer or the maximum speed recommended for the compressor. The overspeed trip shall operate independently from the regular speed control system and shall require manual reset.

3.6.4 Sound level. The exterior sound level produced by the compressor unit shall not exceed the noise limits established by the EPA in effect on the date of manufacture.

3.7 Engine. The compressor unit shall be driven by a liquid- or air-cooled diesel engine of a size and type used or recommended for use by the compressor manufacturer on standard commercial compressor units. The engine,

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:19Z
Check the source to verify that this is the current version before use.

at full-rated compressor output shall have an intermittent horsepower rating sufficient to properly and adequately operate the compressor and all connected auxiliaries at the speed required to develop rated compressor capacity under the atmospheric conditions specified in 3.6. Instruments and gages specified in 3.7.1 shall be of the type recommended by the manufacturer. All engine accessories supplied commercially as standard equipment shall be furnished. The engine shall be equipped with an electrical starting system rated either at 12 or 24 volts in accordance with the standard voltage for the engine being furnished. The diesel engine shall be capable of starting within 5 minutes and shall be ready for full-load operation within 15 minutes under any of the environmental conditions specified in 3.6.2. The fuel tank shall be sized for continuous operation at rated compressor output of at least 8 hours. The diesel engine shall start in any temperature above -20°F. Starting aids may be either electric glow plug or ether primer. When an ether priming system is required, it shall be the measured shot type, with storage capacity of not less than 12 fluid ounces. An enbloc design engine compressor unit is not excluded from this specification.

3.7.1 Instruments and controls. The following engine instruments and controls, as a minimum, shall be furnished:

a. Control, starter button.
b. Control, shutoff.
c. Control, manual engine warm-up.
d. Gage, lubricating oil pressure.
e. Gage, engine water temperature, or engine temperature.
f. Ammeter or battery charging indicator.
g. Safety controls (see 3.6.3).
h. Priming aid controls (see 3.8).
i. Hour meter.

All instruments shall be mounted on a panel or panels located near the operating controls and shall be visible to the operator. The instrument panel(s) shall be furnished with illumination for night operation. The engine hour meter shall have a totalizing mechanism capable of registering not less than 9,999.9 hours of engine operating time.

3.8 Storage battery(s). The manufacturer's standard commercial storage battery(s) normally furnished to make a complete electrical system shall be furnished dry charged and moisture sealed. Electrolyte shall not be furnished. W e pecified (see 6.2), a wet charged battery(s) shall be furnished. The wet charged battery(s) shall be filled with electrolyte and fully charged. Electrolyte shall have a specific gravity of 1.265 ± 0.010 at 80°F.

3.9 Air cleaners. Air cleaners shall be of the two-stage dry-type design wherein the first stage provides centrifugal separation and the second stage provides impingement filtration with use of a suitable filter medium. When handling dust concentrations of 0.025 grams per cubic foot, the air cleaners shall be capable of operating not less than 8 hours without exceeding an air restriction which could adversely affect the rated output of the compressor. When located outside the compressor housing, air intake shall be fitted with a rain cap and screen. Connections of components associated with the air cleaner installation shall be water- and gas-tight. The cleaner shall have an indicator that shows when the cartridge is ready for replacement.

Source: https://assist.dla.mil -- Downloaded: 20260-20T22:19Z
Check the source to verify that this is the current version before use.

3.10 Compressor. Unless otherwise specified (see 6.2), the compressor shall be either rotary, screw, or reciprocating type.

3.11 Receiver. The air receiver shall be designed, constructed, and stamped for a pressure of not less than 300 psig, in accordance with the ASME Boiler and Pressure Vessel Code, Section VIII - Pressure Vessels. The receiver shall be equipped with a pressure gage and drain valve and shall be protected against excessive pressure by the manufacturer's standard relief valve. The receiver discharge system shall include a manual blowdown valve and an automatic blowdown valve designed to blow the complete air system down to atmospheric pressure when the engine stops. When a pressure in excess of 10 psig must be maintained in the receiver to insure adequate circulation of compressor oil or elimination of carryover, the air discharge piping shall include a minimum pressure valve or device set to maintain a predetermined minimum back-pressure on the compressor on the compressor oil system.

3.12 Manifold and service outlets. The air receiver discharge line shall be equipped with an air service manifold having individually controlled service outlets with standard universal type pneumatic hose couplings. The air service manifolds shall be fitted with not less than four 3/4-inch outlets and two 1-1/2-inch outlets with globe valves. All 3/4-inch outlets shall be equipped with the manufacturer's standard lever-type air cocks. When specified (see 6.2), lever-handle, plug-type air cocks and couplings conforming to WW-C-633, type II or III shall be provided. When specified (see 6.2), the compressor unit shall be equipped with a check valve installed in the air line between the receiver and the manifold outlets to prevent reverse flow of air into the receiver during blowdown.

3.13 Housing. A suitable housing shall be provided to enclose the engine, compressor, and instrument panel(s). Steel housing and steel panels shall be not less than 0.0598 inch (U.S. revised standard gage No. 16) thick. Supporting members and braces shall be furnished as required. The housing shall be sufficiently rigid to support a 300-pound load applied to any single 1-square-foot area on the top of the housing. The housing shall include hinged access openings to the engine, compressor, and instrument panel(s). Access panel(s) shall be equipped with devices to hold the panel(s) in an open position and clamps or latches to retain the panel(s) in the closed position.

3.14 Mounting. The complete compressor unit shall be securely mounted on a wheel-mounted undercarriage equipped with parking brakes. The undercarriage shall be of the four-wheel type with drawbar, drawbar lunette-coupler, and automotive type steering or tandem axle, as specified (see 6.2). Drawbar couplers shall conform to MS51336. All units shall be equipped with springs having components with a rated capacity at least equal to the loads imposed on each member, measured at the ground, with compressor loaded to capacity. When suspension capacity is rated at spring pads, unsprung weight shall be deducted. Two safety chains shall be furnished on each unit. The units shall be designed for towing over graded gravel roads at speeds up to 20 mph. Tires shall be of rated capacity at least equal to the load imposed on each tire, measured at each wheel at the ground with trailer loaded to rated gross vehicle weight. Tires shall not drag on fenders when making turns. Unless a particular type and size is specified in the contract (see 6.2), tires shall be standard passenger car tires having a ply rating and size recommended in the T&RA Yearbook for the gross weight of the unit. The parking brake shall be capable of holding the unit in a stationary position on a 15 percent grade.

Source: https://assist.dla.mil -- Downloaded: 202640-20T22:19Z
Check the source to verify that this is the currenversion before use.

3.15 Lubrication. The equipment shall be serviced with grease and oils of types and grades recommended by the manufacturer. Lubrication fittings shall conform to SAE J534 and shall be located in accessible protected positions. A bright red circle shall be painted around each lubricating point. The equipment shall be designed to operate efficiently and satisfactorily when lubricating equipment, 1,000 pounds per square inch and higher, will damage grease seals or other parts, a suitable warning plate shall be affixed to the unit in a conspicuous location. The equipment shall be tagged to indicate the temperature range and grades of lubricants used.

3.16 Cleaning, treatment, and painting. Unless otherwise specified (see 6.2), surfaces normally painted in good commercial practice shall be cleaned, treated, and painted as specified herein. The color of the finish coat shall be as specified (see 6.2). Surfaces to be painted shall be cleaned and dried to insure that they are free from contaminants, such as oil, grease, welding slag and spatter, loose mill scale, water, dirt, corrosion product, or any other contaminating substances. As soon as practicable after cleaning, and before any corrosion product or other contamination can result, the surfaces shall be prepared or treated to insure the adhesion of the coating system. The painting shall consist of at least one coat of primer and one finish coat. The primer shall be applied to a clean, dry surface as soon as practicable after cleaning and treating. Painting shall be with manufacturer's current materials according to manufacturer's current processes and the total dry film thickness shall be not less than 1.5 mils over the entire surface. The paint shall be free from runs, sags, orange peel, or other defects.

3.17 Lifting and tying down attachments. When specified (see 6.2), the equipment shall be equipped with lifting and tying down attachments. Lifting and tying down attachments shall conform to type II or type III of MIL-STD-209. Attachments shall be indicated by a transportation plate. Transportation plates shall be inscribed with a diagram showing the lifting attachments and lifting slings, the capacity of each attachments, and the required length and size of each sling cable. A silhouette of the item furnished showing the center of gravity shall be provided on the transportation plate. Tying down attachments may be identified by stenciling or other suitable marking. Tying down marking shall clearly indicate that the attachments are intended for the tie down of the equipment on the carrier when shipped.

3.18 Fungus resistance. When specified (see 6.2), electrical components and circuit elements, including terminal and circuit connections, shall be coated with varnish conforming to MIL-V-173, except that:

a. Components and elements inherently inert to fungi or in hermetically sealed enclosures need not be coated.
b. Current-carrying contact surfaces, such as relay contact points, shall not be coated.

3.19 Identification plate. An identification plate will be furnished by the contracting officer for each compressor unit. The contractor shall stamp all necessary data in the blank spaces of the plate provided for that purpose, and securely affix a plate to each compressor unit in a conspicuous place with brass screws or bolts not less that 1/8 inch in diameter. The applicable nomenclature contained in the contract item description shall be placed in the top blank.

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:19Z
Check the source to verify that this is the current version before use.

3.20 Instruction plates. The compressor unit shall be equipped with instruction plates suitably located, describing any special or important procedures to be followed in operating and servicing the equipment. Plates shall be of a material which will last and remain legible for the life of the equipment, and shall be securely affixed thereto with nonferrous screws or bolts of not less than 1/8-inch diameter.

3.21 Workmanship.

3.21.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

3.21.2 Bolted connections. Bolt holes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.21.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.21.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

3.21.5 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or any other defect which reduces the castings ability to perform its intended function.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:19Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. The first article inspection shall be performed on one complete compressor unit when a first article is required (see 3.2, 6.2, and 6.5). This inspection shall include the examination of 4.3 and the tests of 4.4.1, 4.4.2, and 4.4.4. The first article may be either a first production item or a standard production item from the supplier's current inventory provided the item meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining items to be furnished under the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.3, the test of 4.4.3, and the packaging inspection of 4.5.

4.3 Examination. Each compressor unit shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.4 Tests. Prior to the tests specified herein which require the compressor(s) be operated, the unit(s) shall be serviced with oils and greases recommended by the manufacturer for use in the ambient temperature at the test location. Batteries used for test purposes shall be supplied by the manufacturer in lieu o the batteries to be shipped with the unit.

4.4.1 Performance test. The compressor shall be tested to determine capacity and power consumption in accordance with the rules, procedures, and instrumentation specified in the ASME PTC-9. The duration of the test shall be sufficient to record all data required under Report of Test of PTC-9, but in no case shall the test duration be less than 1 hour. Test results shall be corrected to the atmospheric conditions specified in 3.6. Prior to the actual performance test, preliminary tests shall be run, as required, to verify that the compressor and associated system are in suitable condition, that speed controls have been properly adjusted, and that gages and instruments are functioning properly. Following the successful completion of the performance test, the compressor shall be operated for a period of not less than 30 minutes in each of the four tilted positions specified in 3.6. Inability of the compressor to meet the performance requirements of this specification or to operate satisfactorily in any of the four tilted positions shall be cause for rejection.

4.4.2 Functional test. The compressor shall be operated continuously for a period of not less than 8 hours during which time a log shall be maintained of the capacity, discharge pressure, operating speed, and temperature of compressed air at the receiver discharge outlet. For a 1-hour period during

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:19Z
Check the source to verify that this is the current version before use.

the test, the air discharge valve shall be alternately opened and closed so as to operate the compressor through the complete loading cycle (from zero to full rated capacity to zero capacity) not less than once every 5 minutes. The compressor shall operate at zero capacity for not more than 1 minute between cycles. Cycling operation shall be observed to determine if, when the air discharge valve is closed, the engine speed reduces from full-rated-capacity speed to a speed within the idling range recommended by the engine manufacturer. Failure of the compressor to meet the performance requirements of 3.6, 3.6.1, and 3.7, or malfunction or failure of any parts, components, or controls shall be cause for rejection.

4.4.3 Operational test. Each compressor, excluding first article samples, shall be tested for a period of not less than 60 minutes to verify satisfactory operation of the compressor and all controls. During the test all necessary adjustments in controls shall be made as required to insure that performance requirements relating to compressor output and regulation and engine speeds will be met.

4.4.4 Mobility test. The wheel-mounted compressor shall be towed over graded gravel roads for a distance of not less than 25 miles at speeds up to 20 miles per hour (mph). When graded gravel roads are not readily available for mobility tests, paved highways in a condition similar to gravel roads will be acceptable for test purposes subject to the approval of the contracting officer or his authorized representative. After successful completion of the road test, the compressor shall be towed on off-road cross-country terrain for 10 miles at average speeds of approximately 5 mph. Off-road terrain is defined as open fields, ungraded roadways, and generally uneven terrain normally encountered at construction sites where compressors are used. During the mobility test, the unit shall be checked for steering capability and the parking brake shall be operated to verify that the brake will hold the unit on a 15 percent grade.

4.5 Packaging inspection. The inspection of the preservation, packing, and marking shall be in accordance with the requirements of section 4 of MIL-C-3600. The inspection shall consist of the quality conformance inspection; and, when specified (see 6.2), a preproduction pack shall be furnished for examination and test within the time frame required (see 6.2).

5. PACKAGING

5.1 Preservation, packing, and marking. Preservation, packing, and marking shall be in accordance with the requirements of MIL-C-3600 with the level of preservation and the level of packing as specified (see 6.2).

6. NOTES

6.1 Intended use. The air compressors are intended as portable sources of compressed air. Each compressor is a self-contained unit readily movable and suitable for field service at construction sites.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of the specification.
b. When a first article is required for inspection and approval (see 3.2, 4.2.1 and 6.5).
c. When wheeled undercarriages shall comply with FMVSS (see 3.3.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:19Z
Check the source to verify that this is the current version before use.

d. When an engine overspeed device is required (see 3.6.3).
e. When a wet charged battery shall be furnished (see 3.8).
f. Type of compressor, if different (see 3.10).
g. When lever-handle, plug-type airlocks and couplings conforming to WW-C-633 are required (see 3.12).
h. When a check valve in discharge air line is required (see 3.12).
i. Whether the units shall be equipped with automotive type steering or tandem-axle; size and type of tires required (see 3.14).
j. Color required (see 3.16).
k. When slinging eyes and tying down devices are required (see 3.17).
l. When fungus treatment is required (see 3.18).
m. When a preproduction pack inspection is required, and time frame required for submittal (see 4.5).
n. Level of preservation and level of packing required (see 5.1).

6.3 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423 and invokes the provisions of paragraph 7-104.9(n) of the Defense Acquisition Regulations (DAR), the data requirements will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the Contract Data Requirements List (DD Form 1423) incorporated into the contract. When the provisions of DAR 7-104.9(n) are not invoked, the data shall be delivered in accordance with the contract requirements.

6.4 Standard lubricants. When requested by the manufacturer, the contracting officer should obtain through established channels, a list of standard military lubricants applicable to the equipment covered herein. This information is contained in the Department of Defense Section of the Federal Supply Catalog, 9100-IL.

6.5 First article. When a first article inspection is required, the item will be tested and should be a first production item or it may be a standard production item from the contractor's current inventory as specified in 4.2.1. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, test, and approval of the documents first article.

Custodian:

Navy - YD

Preparing activity:

Navy - YD

Project No. 4310-N089

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:19Z
Check the source to verify that this is the current version before use.