INCH-POUND


MIL-DTL-29210/2A
1 April 2020
SUPERSEDING
MIL-DTL-29210/2
21 June 2010

DETAIL SPECIFICATION SHEET

HOSE ASSEMBLY, IRON, BRASS, AND CRES CONNECTORS, RUBBER, METAL LINED, WIRE REINFORCED, 1.250, 1.500, AND 2.000 INCH HOSE, 250 PSIG, SATURATED STEAM SERVICE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-29210.



NOTE: .750 inch (19.05 mm) hose clamp may be a single type U-Bolt design.

FIGURE 1. Hose assembly configuration.

AMSC N/A

FSC 4720

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:16Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Hose assemblies described herein shall be manufactured with BOSS male stem fittings or male stem and female spud as specified herein and hose in accordance with MIL-DTL-29210, metal lined.

The end fittings with the special stem design should be equal to end fittings with special stem design available from Dixon Valve and Coupling Company, https://www.dixonvalve.com. The male fitting should be “Easy Boss Style GM-28” and the female fitting should be either “Easy Boss Style GB-28C” using copper insert in the female spud or “Easy Boss Style GM-28” using polymer insert in the female spud.

Patent notice. The end fittings are covered by the following patent: U.S. patent number 4,603,888; expires September 18, 1999. The Government does not have a royalty-free license.

Hose fittings shall be of the long shank interlocking clamp type or U-type as applicable, having fingers or lugs on each half of the clamp to grip the collar on the stem, see figures 1 and 2. The fittings shall prevent the stem shank from being pulled forward in relation to the clamp. As applicable each clamp half shall interlock with the other half.




FIGURE 1. Male end fitting assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:16Z
Check the source to verify that this is the current version before use.




FIGURE 2. Female end fitting assembly.

Coupling components shall consist of a serrated stem with a raised continuous collar, a swivel nut and spud (for female section). Coupling components shall also consist of a two-part interlocking clamp type or U-type as applicable, clamp with two bolts for the .75-inch (19.05 mm) size hose and four bolts for the larger size hoses.

The seating surface of the female stem shall be round to fit the beveled copper insert or polymer insert in the female spud, as specified. There shall be no sharp edges on the nipples or the clamps to cause damage to the tube or cover. When assembled, there shall be provisions for additional take-up of clamps in service.

The male and female stems shall be designed with rib type right hand spirals at the end of the stem to screw into the stainless steel liners providing positive gripping and retention. The pitch of the rib type spirals shall be.312-inch (7.92 mm) for the 1.5-inch (38.10 mm) and 2-inch (50.80 mm) hose fittings and .25-inch (6.35 mm) for the .75-inch (19.05 mm), 1-inch (25.40 mm), and 1.25-inch (31.75 mm) hose fittings.

The spiral on the male and female stems shall be of sufficient length to ensure that part of the metal liner is always under the clamp which provides additional gripping and retention when the clamps are torqued over the hose.

Female threads on spud and male connections shall be American Standard Taper Pipe (NPT) meeting the requirements of FED-STD-H28. The female threads on the swivel shall be American Standard Straight Pipe (NPSM).

Hose shall be in accordance with MIL-DTL-29210.

All hose assemblies shall be subjected to the individual inspections as specified in MIL-DTL-29210.

Hose assembly working pressure 250 psi (1.7 MPa) at 406°F (208°C).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:16Z
Check the source to verify that this is the current version before use.

Hose ID designators shall be as specified in table I.

TABLE I. Hose size code number. 1/ 2/

Hose size code number	Hose size ID inches (mm)
125	1.250 (31.75)
150	1.500 (38.10)
200	2.000 (50.80)

1/ Dimensions are in inches.
2/ Metric equivalents are given for information only.

Hose reinforcement wires shall be in accordance with MIL-DTL-29210. Designators shall be as specified in table II.

TABLE II. Reinforcement wire.

Code	Material
B	Brass plated high tensile carbon steel
S	Corrosion resistant steel (CRES)
Z	Zinc-plated high tensile carbon steel wire

Hose assembly configurations shall be as specified on figure 1.

Material for male stem, see table II for material designators:

Malleable iron in accordance with ASTM A47/A47M, grade 32510, or ductile iron in accordance with ASTM A536, grade 60-40-18 or grade 65-45-12, and shall be protected with a corrosion-resisting coating to withstand 90 hours of salt spray testing in accordance with ASTM B117. Gray iron castings in accordance with ASTM A48/A48M shall not be acceptable.

Brass in accordance with ASTM B61 or alloys C92200 or C90300 in accordance with ASTM B271/B271M, ASTM B505/B505M or ASTM B584.

Corrosion resistant steel (CRES) alloy 316 in accordance with SAE-AMS-5653.

TABLE III. Stem material designators.

Material designator	Material
M	Malleable iron
B	Brass
S	CRES

Nipple: The nipple shall be a “BOSS” Male Stem, see table IV for size designators.

Threads shall be NPT in accordance with ASME B1.20.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:16Z
Check the source to verify that this is the current version before use.

TABLE IV. Male stem hose and thread sizes. 1/ 2/

Male stem size designator	Male stem hose size inch (mm)	Thread size NPT
-20-20	1.250 (31.75)	1 ¼ - 11.5
-24-24	1.500 (38.10)	1 ½ - 11.5
-32-32	2.000 (50.80)	2 - 11.5

1/ Dimensions are in inches.
2/ Metric equivalents are given for information only.

TABLE V. Male and female stem hose and thread sizes. 1/ 2/

Male/Female stem size designator	Male stem hose size inch (mm)	Thread size NPTM		Female stems hose size inch (mm)	Thread size NPTF
-20-20F	1.250 (31.75)	1 ¼ - 11.5		1.250 (31.75)	1 ¼ - 11.5
-24-24F	1.500 (38.10)	1 ½ - 11.5		1.500 (38.10)	1 ½ - 11.5
-32-32F	2.000 (50.80)	2 - 11.5		2.000 (50.80)	2 - 11.5


1/ Dimensions are in inches.
2/ Metric equivalents are given for information only.

U-Bolt:

Casting, if used, for U-bolt shall be malleable iron in accordance with ASTM A47/A47M, grade 32510.

The U-bolt bolts shall be factory set at the manufactures torque value.

Hose assembly length. The hose assembly length is calculated as specified on figure 2.




NOTES:
1. Lengths of hose “L” are represented by feet (25, 50, 75, and 100).
2. Hose length tolerance shall be in accordance with MIL-DTL-29210.
3. Figure is for illustration purposes only and is not meant to restrict designs.

FIGURE 2. Hose assembly dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:16Z
Check the source to verify that this is the current version before use.

Part or Identifying Number (PIN) example:



M29210/2-25125S-20-20S indicates - Hose assembly 25 feet long, 1.250 inch hose ID, CRES male fittings with CRES reinforcement wires, both hose stems are for 1.250 inch hose with 1.250 inch NPT threads.

Intended use: Temporary services from docks or barges to ships 250 psi, saturated steam service at a temperature of up to 406°F (208°C).

Referenced documents. In addition to MIL-DTL-29210, this document references the following:

FED-STD-H28	ASTM B117
ASME B1.20.1	ASTM B271/B271M
ASTM A47/A47M	ASTM B505/B505M
ASTM A48/A48M	ASTM B584
ASTM A536	SAE-AMS-5653
ASTM B61	

CONCLUDING MATERIAL

Custodians:
Army - AT
Navy - SH
Air Force - 71
DLA - CC

Preparing activity:
DLA - CC

(Project 4720-2020-005)

Review activities:
Navy - MC, SA
Air Force - 11

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:16Z
Check the source to verify that this is the current version before use.