MILITARY SPECIFICATION

SWEEPER, STREET VACUUM, SELF PROPELLED, DED, 4 CUBIC YARD EFFECTIVE MINIMUM CAPACITY

This specification is approved for use by the Naval Facilities Engineering Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a self propelled type vacuum pickup street sweeper.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATION

FEDERAL

W-B-131 - Battery, Storage, Vehicular, Ignition Lighting, and Starting.

STANDARDS

FEDERAL

FED-STD-595 - Colors.
FED-STD-297 - Rustproofing of Wheeled Vehicles.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 3825

Source: https://assist.dla.mil -- Downloaded: 202640-20T22:11Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

(Copies of military specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other Government documents, drawings, and publications. The following other Government documents form a part of this specification to the extent specified herein.

DEPARTMENT OF LABOR (DoL)
OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

Occupational Safety and Health Standards.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

DEPARTMENT OF TRANSPORTATION (DoT)

Federal Motor Vehicle Safety Standards and Regulations.
Federal Motor Carrier Safety Regulations.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

CODE OF FEDERAL REGULATIONS (CFR)

Title 40, Environmental Protection

Part 86 - Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines: Certification and Test Procedures.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

2.2.1 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE Handbook.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

Source: https://assist.dla.mil -- Downloaded: 20260-20T22:11Z
Check the source to verify that this is the current version before use.

STATE OF CALIFORNIA

California Vehicle Code.

(Application for copies should be addressed to the Department of Motor Vehicles, 2570 24th Street, Sacramento, CA 95809.)

TIRE AND RIM ASSOCIATION, INC. (TRA)

TRA Yearbook.

(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 West Market Street, Akron, OH 44313.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Description. The sweeper shall be a commercial product of the manufacturer's latest design and shall meet the requirements specified herein. The sweeper shall consist essentially of a short-conventional cab, cab-over-engine tilt type, or single-man cab, diesel-engine-driven self propelled vehicle. Mounted equipment shall include, an enclosed hopper body, diesel auxiliary engine if required, brooms, vacuum pickup system, and dust supression water system capable of operating efficiently from 35 degrees (°) to 120° Fahrenheit (F).

3.2 Standard commercial product. The sweeper shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the sweeper being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs, or brochures, and represents the latest production model.

3.3 First article. When specified (see 6.2), the contractor shall furnish a complete sweeper for first article inspection and approval (see 4.2.1 and 6.4).

3.4 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:11Z
Check the source to verify that this is the current version before use.

without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification unless otherwise specified.

3.5 Safety. All rotating or reciprocating parts that are of such nature or so located as to be a hazard to operating or maintenance personnel shall be enclosed or properly guarded in accordance with OSHA 1910.219.

3.6 Interchangeability. All units of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to insure interchangeability of component parts, assemblies, accessories, and spare parts.

3.6.1 System of measurement. The dimensions used in this specification are not intended to preclude the use of the metric system of measurement in the fabrication and production of the material, individual parts, and the finished product, provided form, fit, and function requirements are satisfied.

3.7 DoT Federal Motor Vehicle Safety Standards. The vehicle shall comply with all applicable Motor Vehicle Safety Standards in effect on date of manufacture.

3.8 Air pollution control. Sweeper vehicles shall comply with the CFR regulations governing Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines in effect on the date of manufacture. In addition, sweeper vehicles destined for California shall comply with State of California regulations governing air pollution control in effect on the date of manufacture.

3.9 Sound level. The exterior sound level produced by the vehicle shall not exceed the noise limits established by the CFR. The interior sound level shall be in accordance with DoT Federal Motor Carrier Safety Regulations, section 393.94 and shall not exceed 90 decibals on the "A" scale.

3.10 Performance.

3.10.1 Sweeper vehicle performance. The fully equipped vehicle loaded to specified rated gross vehicle weight (gvw) shall perform the following:

a. Maintain a maximum speed of not less than 45 miles per hour (mph) on a dry, level, paved roadway.
b. Service brakes bringing the sweeper to a stop within a braking distance of 40 feet from a speed of 20 mph on a dry smooth level surface free from loose material.
c. There shall be no evidence of body distortion, water leakage, tire and body contact, malfunction of components, irregular chassis noise, vibration or sway when subjected to a road test of 10 miles over paved roadway at not less than 45 mph.

Source: https://assist.dla.mil -- Downloaded: 20260-20T22:11Z
Check the source to verify that this is the current version before use.

3.10.2 Sweeper performance. While traveling at not less than 5 mph demonstrate the following performance:

a. Pick up and retain in a single pass not less than 80 percent of general trash, as listed in Table I, spread uniformly over an area 65 inches wide by 20 feet long.

Table I. General trash item and quantity.

ITEM	QUANTITY
8 1/2 X 11 paper sheet	12
Plastic cups 6 to 8 ounce (oz) (6 styrofoam and 6 clear plastic)	12
Soft drink cups (waxed paper 12 oz)	12
Newspapers folded in 3rds secured with rubber band	4
Nails box 8d (2-1/2 inches)	12
Washers (1/2 inch O.D.)	12
Stones 2 inch nominal	12
Nuts 1/4 machine	12
Total Quantity Equals 100 Percent	

b. Pick up and retain in a single pass not less than 90 percent (by weight) a 50 pound (lb) mixture of half sand and pea gravel spread uniformly over an area 65 inches wide by 20 feet long.

c. With not less than 4 cubic yards of trash in the hopper, the dust supression system shall effectively retain 98 percent of all particles 50 microns and larger.

d. Operate continuously in the sweeping mode for not less than 2 hours using all sweeping systems, i.e. vacuum, water spray, gutter brooms, etc. In addition, the hopper body shall be dumped at least twice.

3.11 Vehicle construction.

3.11.1 Chassis. Chassis shall be a short conventional cab-, cab-over-engine, or single man cab. If cab-over-engine is furnished, the chassis shall be furnished with tilt cab and reinforced frame.

3.11.2 Gross vehicle weight. The gvw shall be rated not less than 24,000 lbs.

3.11.3 Engine. The vehicle shall be equipped with a liquid cooled, compression ignition, two or four stroke cycle diesel engine, with not less than six cylinders, having horsepower (hp), torque, and speed characteristics to satisfactorily perform all sweeping and travel requirements.

3.11.3.1 Oil filter. A full flow oil filter shall be furnished.

3.11.3.2 Governor. Engine governor shall be furnished and set and sealed to limit engine to manufacturer's maximum recommended operating speed.

3.11.4 Fuel system. Fuel systems shall conform to DoT Federal Motor Carrier Safety Regulations, section 393.65. Fuel tank shall have sufficient capacity for 5 hours of normal sweeping operation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:11Z
Check the source to verify that this is the current version before use.

3.11.5 Air cleaner. A dry type engine intake air cleaner shall be furnished, and provided with a restrictor indicator gage in full and constant view of the driver operator.

3.11.6 Electrical system. The electrical system shall be 12 volt (V). Alternator shall have a minimum rated capacity of not less than 50 amperes (A). All lights, reflectors, and wiring shall conform to DoT Federal Motor Carrier Safety Regulations.

3.11.7 Battery. The vehicle shall be equipped with a 12V battery. The total reserve capacity rating shall be not less than 110 minutes. The total cold cranking rate at 0°F shall be not less than 450A. Reserve capacity ratings and cold cranking ratings shall be measured in accordance with SAE J537. Batteries shall be of the maintenance-free type, having the maintenance-free characteristics listed in W-B-131. The battery shall not be located in the cab.

3.11.8 Steering. Vehicle shall be equipped with full power hydraulic steering. If full width cab is provided it shall be equipped with dual controls for both left and right steering.

3.11.9 Transmission. Each sweeper shall be equipped with an automatic transmission having not less than 4 forward and one reverse speeds. If a hydrostatic drive system is provided it shall be furnished with traction motor(s) and capable of attaining required speeds.

3.11.10 Brakes. Each sweeper shall be equipped with either full air or power assisted hydraulic service brakes. If air brakes are provided a minimum 7-1/4 cubic feet per minute capacity compressor and air storage reservoir(s) of not less than 2000 cubic inches is required. A hand operated positive-locking parking brake independent of the service brakes is required.

3.11.11 Suspension. Each sweeper shall be equipped with suspension system having components with a rated capacity at least equal to the loads imposed on each member, measured at the ground, with sweeper loaded to rated gvw. When suspension capacity is rated at the spring pads, unsprung weight shall be deducted. Shock absorbers of the heavy-duty, double-acting, hydraulic type shall be mounted on the front axle.

3.11.12 Axles. Front and rear axles shall be manufacturer's standard. Axle ratings shall be at least equal to the load imposed on each axle, measured at the ground, with sweeper loaded to rated gvw.

3.11.13 Wheels, rims, tires, and tubes. Chassis shall be equipped with spare tire assemblies when different sizes utilized. Rims and tire rating shall conform to TRA recommendations. Wheels and rims shall be of the 10 lug disk type, tires shall have highway type thread design. Tires shall have rated capacity at least equal to the load imposed on each tire, measured at each wheel at the ground, with sweeper loaded to rated gvw.

3.11.14 Windshield washers and wipers. If a full width cab is provided the cab shall be equipped with dual windshield washers and dual windshield wipers. Windshield wipers shall be multispeed type and operated by either vacuum booster, air, or electric motor(s).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:11Z
Check the source to verify that this is the current version before use.

3.11.15 Cab heater and defroster. Heater shall be manufacturer's standard liquid coolant operated type, meeting the requirements of DoT Federal Motor Carrier Safety Regulations, section 393.77, as applicable. Defroster shall keep not less than 75 percent of windshield area clear at an ambient temperature of -25°F and shall be provided with air regulating control. Heater and defroster controls shall be mounted on the instrument panel.

3.11.16 Vehicle warning light. A vehicle warning light shall be provided and mounted at point of attachment on vehicle centerline in a position affording 360° visibility. The warning light shall be operated by means of a separate switch, with a red indicating light, located on instrument panel and marked to indicate function of switch. The warning light shall have a minimum of 33,000 candle power and a minimum flash rate exceeding 80 flashes per minute. The lamps shall be amber in color.

3.12 Accessories and equipment. Sweeper equipment shall be complete with all accessories furnished as standard equipment by the manufacturer. The following minimum equipment shall be furnished:

a. Outside rearview and combination (flat and convex) mirrors, west coast type, mounted on each side of cab or body as applicable.
b. Key-operated ignition switch.
c. Ammeter or charging indicator.
d. Fuel gage.
e. Oil pressure gage or indicator.
f. Water temperature gage or indicator.
g. Speedometer with recording odometer.
h. Engine hour meter (recording 9999.9 hours).
i. Dual sun visors. (If single man cab is provided a single sun visor is acceptable.)
j. Driver's compartment ventilator other than window.
k. Horn.
l. Tachometer.

3.13 Back up alarm. When specified (see 6.2), the vehicle shall be provided with an audible pulsating signaling device (electric or mechanical) to caution personnel when the vehicle is in reverse gear operation.

3.14 Vacuum sweeping components.

3.14.1 Sweeper engine. If the vacuum sweeper is powered by an independent auxiliary engine it shall be a heavy-duty type diesel, liquid-cooled engine having hp, torque, and speed characteristics to satisfactorily meet all sweeping requirements. The engine shall have not less than 212 cubic inches displacement. The engine shall comply with all applicable CFR regulations. The engine shall be furnished complete with oil filter and electrical system, but not limited to, the following accessories:

a. Key-operated ignition switch.
b. Ammeter or charging indicator.
c. Oil pressure gage or indicator.
d. Fuel gage.
e. Water temperature gage or indicator.
f. Engine hour meter recording 9999.9 hours.

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:11Z
Check the source to verify that this is the current version before use.

g. Tachometer.
h. Battery same as in 3.11.7.
i. Fuel tank(s) with sufficient capacity for 8 hours operation, or fuel furnished from chassis fuel tank having sufficient capacity for 8 hours operation is acceptable.
j. Governor.
k. Air cleaner with precleaner and restriction gage mounted in cab in full view of the operator.

3.14.2 Body. The body construction shall be all weld heavy-gage steel plate. The hopper shall have a vacuum chamber of not less than 6 cubic yards (cu yd) with an effective capacity of not less than 4 cy yd. Hydraulically actuated means shall be provided to dump the contents of the body. The discharge door shall be opened hydraulically and latched mechanically or hydraulically for safety. The actuating mechanism for unlatching and opening the rear discharge door shall be positioned so that the operator can observe the dump area when discharging the load. A single flood light at rear of the dump door shall be furnished.

3.14.3 Brooms and pickup system. The main broom, when furnished, and each side broom shall be raised and lowered independently.

3.14.3.1 Main (extension) brooms. The pickup system shall be either rotating broom and vacuum, air blast and vacuum, or just vacuum. The sweeping and pickup system shall be suspended under the vehicle between the front and rear axles and shall be raised and lowered hydraulically or pneumatically from within the operators cab. The sweeping system width shall be not less than 68 inches. When a main broom is incorporated, it shall be not less than 48 inches long and 12 inches in diameter. Raising and lowering the broom shall be hydraulically or pneumatically controlled from the operator's position. Broom core shall be steel, reversible, and replaceable with polypropylene broom filaments.

3.14.3.2 Side (gutter) brushes. Two side brushes shall be vertical digger type, located forward of vacuum nozzle, and operated from control panel in cab. Side brushes shall be raised, lowered, and suspended either pneumatically, hydraulically, or by automatic torque sensing valves. Each side brush shall be separately hydraulic motor driven. The mounting shall provide for flexibility of the brush to resist front impact and sideward impact damage to the brush mounting or drive mechanism. The side brush mounting system shall be adjustable to meet varying curb angles. Side brush segments shall be of the quick detachable, or bolt on, type with a sweeping diameter of 20 inches or greater. The gutter brooms shall be furnished with an adjustable flood light.

3.14.4 Vacuum nozzles(s). The vacuum pickup nozzle(s) shall have not less than 125 square inch area, attached to hopper by a flexible hose of 6 inches in diameter or greater. Means for nozzle adjustment relative to the roadway shall be provided. Raising and lowering operations shall be controlled with switches located on the operator's control panel.

3.14.5 Dust spray system. A high pressure low volume water dust spray system shall be furnished to supress dust. The system shall include a pump, not less than 170 gallon reservoir manufactured from corrosion-resistant

Source: https://assist.dla.mil -- Downloaded: 20260-20T22:11Z
Check the source to verify that this is the current version before use.

materials, valves, strainer, relief valve, hoses and spray nozzles located to cover the sweeping path ahead of the vacuum nozzle and brooms. The pump shall be controlled from a switch located on the operators panel with a low water level switch incorporated in the reservoir which will shut down the pump to prevent operation without water.

3.14.6 Wandering hose. Wandering suction hose shall be manufacturer's standard commercial product with a minimum diameter of not less than 6 inches. Collection nozzle for the hose shall be steel or aluminum construction. Hose shall be secured to the body during travel. Hose shall be of sufficient length to allow pickup of debris at a point not less than 8 feet from the rear of the vehicle. When specified (see 6.2), sufficient hose extension pieces shall be provided to pick up debris at a point 30 feet from the perimeter of the vehicle.

3.14.7 Exhaust (suction) fan. The exhaust (suction) fan shall be operated at a fixed speed, independent of vehicle speed. The exhaust fan shall have the capacity to satisfactorily meet all sweeping requirements of 3.10.2 and shall be separated from the engine compartment to protect the engine from dust.

3.14.8 Separator. Separation of the dirts and refuse from the air stream will be accomplished within the body. The separator shall be designed so that it will not plug with normally encountered dirt and trash and shall be designed so that particulate emissions shall not exceed the requirements of 3.10(c).

3.14.9 Operating controls. The sweeper operating controls shall be mounted inside the cab and within easy reach of the driver position. The control shall include the following:

a. Pickup nozzle control.
b. Gutter broom controls.
c. Dust spray system low-water warning light on controls.
d. Gutter broom and rear dump door light controls.

3.15 Cleaning, treatment, and painting. Surfaces normally painted in good commercial practice shall be cleaned, treated, and painted as specified herein. Color of the finish coat shall be yellow No. 13538 conforming to FED-STD-595. Surfaces to be painted shall be cleaned and dried to insure that they are free from contaminants such as oil, grease, welding slag and spatter, loose mill scale, water, dirt, corrosion product, or any other contaminating substances. As soon as practicable after cleaning, and before any corrosion product or other contamination can result, the surfaces shall be prepared or treated to insure the adhesion of the coating system. The painting shall consist of at least one coat of primer and one finish coat. The primer shall be applied to a clean, dry surface as soon as practicable after cleaning and treating. Painting shall be with manufacturer's current materials according to manufacturer's current processes and the total dry film thickness shall be not less than 2.5 mils over the entire surface. The paint shall be free from runs, sags, orange peel, or other defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:11Z
Check the source to verify that this is the current version before use.

3.16 Lubrication. Lubrication means shall be provided for all moving parts requiring lubrication. Hydraulic lubrication fitting shall be in accordance with SAE J543. Pressure lubrication fittings shall not be used where normal lubricating pressure may damage grease seals or other parts. The unit shall be lubricated prior to delivery.

3.17 Radio noise supressors. When specified (see 6.2), the sweeper chassis shall be equipped with radio noise supressors conforming to SAE J552. Electromagnetic radiation from the sweeper chassis shall be within the limits of SAE J551.

3.18 Rustproofing. The vehicle shall be rustproofed in accordance with FED-STD-297.

3.19 Instruction plates. The vacuum sweeper shall be equipped with instruction plates suitably located, describing any special or important procedures to be followed in operating and servicing the equipment. Plates shall be of a material which will last and remain legible for the life of the equipment. Plates shall be securely affixed to the equipment with nonferrous screws or bolts of not less than 1/8-inch diameter.

3.20 Identification plate. The contracting officer will furnish to the Government inspector the required identification plates. The contractor will be required to stamp the necessary data in the blank spaces thereon and securely affix said plates in a conspicuous place on each unit, assembly or subassembly, and parts as directed by the Government inspector. Nonferrous screws, rivets, or bolts of not less than 1/8-inch in diameter shall be used to affix the plates.

3.21 Servicing and adjusting. Prior to acceptance of the vehicle by the Government inspector, contractor shall service and adjust each vehicle for operational use including at least the following: Focusing of lights; adjustment of the engine, electrical and brake system; filling and charging of battery; alinement of front wheels; inflation of all tires; complete lubrication of chassis, engine, and running gear, with grades of lubricants recommended for the ambient air temperature at the delivery point; servicing of cooling system with a solution of ethylene glycol and water in equal parts by volume and servicing of windshield washer reservoir with water and appropriate additives, including servicing all components of the sweeper system.

3.22 Technical manuals. The contractor shall provide technical manual(s) conforming to the Data Item Description(s) listed on the Contract Data Requirements List (CDRL) (DD Form 1423).

3.23 Workmanship.

3.23.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:11Z
Check the source to verify that this is the current version before use.

3.23.2 Bolted connections. Boltholes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.23.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.23.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

3.23.5 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or any other defect which reduces the castings ability to perform its intended function.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. The first article inspection shall be performed on one complete sweeper when a first article is required (see 3.3 and 6.2). This inspection shall include the examination of 4.4 and the tests of 4.5.1. The first article may be either a first production item or a standard production item from the supplier's current inventory provided the

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:11Z
Check the source to verify that this is the currentversion before use.

item meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining items to be furnished under the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.4, the tests of 4.5.2, and the packaging inspection of 4.6. The product unit test shall be performed on the sample selected in accordance with 4.3.

4.3 Sampling. Sampling and inspection procedures shall be in accordance with MIL-STD-105. The unit of product shall be one complete sweeper. All sweepers offered for delivery at one time shall be considered a lot for the purpose of inspection. The quality conformance inspection shall be performed on one unit selected from the lot at random. If an inspection lot is rejected, the contractor may rework it to correct the defects, or screen out the defective units, and resubmit for a complete reinspection. Resubmitted lots shall be reinspected using tightened inspection. If the rejected lot was screened, reinspection shall be limited to the defect causing rejection. If the lot was reprocessed, reinspection shall be performed for all defects. Rejected lots shall be separated from new lots, and shall be clearly identified as reinspected lots.

4.4 Examination. Each sweeper shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.5 Tests.

4.5.1 First article tests.

4.5.1.1 Performance tests. The sweeper shall be tested for the performance requirements of 3.10.1 and 3.10.2. When tested to conform to 3.10.2(c), the manufacturer upon approval of the contracting officer may furnish a certification (see 6.3), in lieu of the test that the sweeper meets the requirements together with a list of the dust supression devices installed. The list shall be sufficiently detailed to allow visual determination that the devices are installed. Failure of the sweeper to meet any of the requirements shall be cause for rejection.

4.5.1.2 Radio noise supression. When specified in 3.17, electromagnetic radiation shall be measured in accordance with SAE J551. When supressed to conform to 3.17, the manufacturer upon approval of the contracting officer may furnish a certification (see 6.3), in lieu of the test that the sweeper meets the requirements, together with a list of the supression devices installed. The list shall be sufficiently detailed to allow visual determination that the devices are installed.

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:11Z
Check the source to verify that this is the currentversion before use.

4.5.2 Production unit test. The sweeper shall be operated a sufficient period of time to satisfy the sweeper vehicle requirements of 3.10.1(c) and the normal street sweeping requirements of 3.10.2(d). The contractor shall be responsible for correcting defects disclosed during operation and for taking action to prevent reccurence of such defects in subsequently furnished vehicles.

4.6 Packaging inspection. The vehicle shall be inspected to verify conformance to the requirements of section 5.

5. PACKAGING

5.1 Vehicle processing. The equipment shall be preserved and packaged in accordance with the contractor's standard practice. The equipment shall be lubricated for operational service as required in the operator's manual.

6. NOTES

6.1 Intended use. The intended use of the vacuum sweeper is to clean streets, clean clogged street drains, leaf pickup, clean raised areas, clean areas between parked cars, and other inaccessible spots on military bases.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.
b. When first article is required (see 3.3 and 4.2.1).
c. When back up alarm is required (see 3.13).
d. When hose extension pieces are required (see 3.14.6).
e. When radio noise supression is required (see 3.17).

6.3 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, CDRL and invokes the provisions of paragraph 52.227-7031 of the Federal Acquisition Regulations (FAR), the data requirements will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL (DD Form 1423) incorporated into the contract. When the provisions of FAR 52.227-7031 are not invoked, the data shall be delivered in accordance with the contract requirements.

6.4 First article. When a first article inspection is required, the item will be tested and should be a first production item or it may be a standard production item from the contractor's current inventory as specified in 4.2.1. The first article should consist of one unit. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

Preparing Activty:

Navy - YD

(Project 3825-N170)

☆ U.S. GOVERNMENT PRINTING OFFICE: 1988—505-038/20898

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:11Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-S-29201A(YD)	SWEEPER, STREET VACUUM, SELF-PROPELLED, DED, 4 CUBIC YARD EFFECTIVE MINIMUM CAPACITY

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*:
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:11Z
Check the source to verify that this is the current version before use.