MIL-S-29215A(YD)
23 February 1987
SUPERSEDING
MIL-S-29215(YD)
12 April 1982

MILITARY SPECIFICATION

SEMITRAILER, BULK CEMENT HAULER, COMMERCIAL

This specification is approved for use by the Naval Facilities Engineering Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a commercial semitrailer type cargo hauler for hauling and discharging bulk cement and other bulk products.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Standards. The following standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

STANDARDS

FEDERAL

FED-STD-297 - Rustproofing of Commercial (Nontactical) Vehicles.
FED-STD-595 - Colors.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 2330

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:18Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-STD-209 - Slinging and Tiedown Provisions for Lifting and Tying Down Military Equipment.
MIL-STD-281 - Automobiles, Trucks, Truck-Tractors and Trailer Dollies; Preservation and Packaging of.
MIL-STD-1223 - Administrative Wheeled Vehicles Treatment, Painting, Rustproofing, Undercoating, Identification Marking, Data Plates and Warranty Notice Standards.
MS75021 - Connector, Receptacle, Electrical - 12 Contact, Intervehicular, 28 Volt, Waterproof.

2.1.2 Other Government documents. The following other Government documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DEPARTMENT OF TRANSPORTATION (DoT)

Federal Motor Vehicle Safety Standards and Regulations.
Federal Motor Carrier Safety Regulations.

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

(Copies of standards and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of the documents not listed in the DODISS shall be the issue of the non-Government documents which is current on the date of the solicitation.

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE Handbook.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:18Z
Check the source to verify that this is the current version before use.

TIRE AND RIM ASSOCIATION, INC. (TRA)

TRA Yearbook.

(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 West Market Street, Akron, OH 44313.)

(Non-Government standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The semitrailer shall consist of a tandem axle suspension system, pressure vessel type body, pneumatic discharge system with all necessary lines, controls and valves, walkways, ladders, fenders, landing gear, lights and wiring, and all other components and accessories to make a complete serviceable unit.

3.2 First production vehicle. When specified (see 6.1.1), the contractor shall furnish a semitrailer for first production vehicle inspection (see 4.2.1 and 6.3).

3.3 Standard commercial product. The semitrailer shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the semitrailer being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs, or brochures, and represents the latest production model.

3.4 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:18Z
Check the source to verify that this is the current version before use.

reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification unless otherwise specified.

3.5 Interchangeability. All units of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to insure interchangeability of component parts, assemblies, accessories, and spare parts.

3.6 General design.

3.6.1 DoT Federal Motor Vehicle Safety Standards. The semitrailer shall comply with DoT Federal Motor Vehicle Safety Standards in effect at the time of manufacture.

3.6.2 Net weight. The net weight of the fully equipped semitrailer shall be the minimum practicable for the service intended.

3.6.3 Gross vehicle weight (gvw). The gvw shall consist of the net weight and the payload, as specified in 3.6.4, evenly distributed within the load area.

3.6.4 Volume and payload. The body shall have a minimum total volume of not less than $25M^3$, and shall be capable of handling dry flowable commodities having densities from 240 to 2,400 kilograms per cubic meter (kg/m^3). The payload shall not exceed 15,422 kg on the semitrailer tandem axle, 15,422 kg on the tractor tandem axle and 4,536 kg on a tractor front axle.

3.6.5 Ratings. Vehicle ratings shall be the manufacturer's published ratings. Component and vehicle ratings shall not be raised to meet the requirements of this specification.

3.7 Performance. The semitrailer, fully equipped and loaded with a payload up to the maximum axle capacity (see 3.6.4), shall be capable of being towed at speeds as great as 32 kilometers per hour (kmph) over unimproved roads (see 6.4), and over reasonably hard uneven terrain; and being towed at speeds as great as 80 kmph over improved roads.

3.7.1 Turning ability. The semitrailer shall be capable of assuming a 90 degree (°) angle to the coupled towing vheicle without cramping, or damage to the semitrailer or the towing vehicle.

3.7.2 Tracking ability. The semitrailer shall conform to the tracking requirements of DoT Federal Motor Carrier Safety Regulations, section 393.70.

3.7.3 Brake performance. The semitrailer service braking system and parking brake system shall comply with the performance requirements of DoT Federal Motor Vehicle Safety Regulations, section 393.52.

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:18Z
Check the source to verify that this is the currentversion before use.

3.8 Chassis frame and body structure. The semitrailer chassis frame and body shall be electrically welded, steel, aluminum or combination steel and aluminum, general constructed, integral unit. The rated payload (see 3.6.4), and the sprung weight of the semitrailer shall not impose a fiber stress greater than 50 percent of the yield strength of the materials used when the semitrailer is operating under mobile conditions specified in 3.7. The chassis main frame members shall extend the full length of the body and shall be combined with sufficient number of crossmembers to ensure stabilty.

3.8.1 Body (pressure) vessel. The body design, construction, and configuration shall be the manufacturer's standard commercial pressure vessel type used for transporting and discharging bulk cement and other pulverized materials such as powdered lime. The body shall have not less than two hoppers (pods) with two or more 508 millimeters (mm) minimum diameter full opening type manholes with airtight covers equipped with hold downs and safety latch. Body reinforcing rings, buttresses, supports and braces may be internally or externally located. When body internal reinforcements are provided, they shall not trap or restrict the flow of the commodity in a manner that would prevent complete vessel unloading. Body sides and ends shall be shaped, tapered, or cylindrical for quick thorough cleanout. The body shall be an airtight pressure vessel and shall be capable of withstanding a test pressure of at least 1-1/2 times the manufacturer's standard operating discharge pressure.

3.8.2 Pneumatic discharge system. Unless otherwise specified (see 6.1.1), the semitrailer body shall be equipped with a combination pneumatic-gravity discharge system. Each hopper (pod) shall have an individual unloading valve with air inlet connection and a pneumatic product discharge outlet manifold. Gravity discharge shall be accomplished by swinging open the valve lower housing to provide not less than 406 mm diameter discharge opening or by similar means. The pneumatic discharge system shall be complete, including all necessary controls, check and relief valves, lines and hoses, and connections to the external air supply.

3.8.3 Suspension system. The semitrailer shall be furnished with the manufacturer's standard suspension system. Each component of the suspension system shall have a rated capacity at least equal to the load imposed, measured at the ground, when the semitrailer is loaded with its specified payload (see 3.6.4). Clearances shall preclude interference between wheels and any other part of the semitrailer under the operating conditions specified herein.

3.8.4 Axle. Axle ratings shall be at least equal to the load imposed on each axle, measured at the ground, when the semitrailer is loaded with the applicable rated payload. The wheel bearings and axle spindles shall be oil lubricated. The oil viscosity shall be in accordance with the manufacturer's recommendations. The hubcaps shall have a window for visual determination of oil level. Provision for venting or other method of withstanding internal pressure buildup, and for replenishing the oil supply, shall incorporated. The hubs shall be fitted with seals.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:18Z
Check the source to verify that this is the current version before use.

3.8.5 Wheels, rims, tires, and tubes.

3.8.5.1 Wheels, rims, and tires. Semitrailer shall be equipped with dual wheels on each axle. When specified (see 6.1.1), disk type wheels shall be furnished. The rim and tire ratings shall conform to TRA recommendations for the type and size tires furnished. Tire and rim sizes shall be the same for all wheels on the semitrailer. Tires shall be tube or tubeless type with highway tread. Tires shall be of rated capacity at least equal to the load imposed on each tire, measured at each wheel at the ground, when the semitrailer is loaded with the applicable rated payload.

3.8.5.2 Tire carrier. One tire carrier shall be provided and installed in an accessible location. Means shall be provided for securing the tire within the carrier to prevent accidental loss.

3.8.5.3 Inner tubes. When tube-type tires are furnished, inner tubes shall be of heavy-duty type, and shall be of proper size for the tires furnished. Tire flaps shall be provided in accordance with TRA recommendations.

3.8.5.4 Spare wheel. Unless otherwise specified (see 6.1.1), a spare wheel or rim shall be mounted on the tire carrier.

3.8.5.5 Spare tire. When specified (see 6.1.1), an inflated spare tire shall be mounted on the spare wheel or rim specified in 3.8.6.4. The spare tire shall be of the same size and tread design and of the same ply rating as tires installed on the semitrailer.

3.8.6 Brakes. Brakes shall be of the full air type and shall conform to DoT Federal Motor Carrier Safety Regulations, sections 393.45 through 393.47, and as specified herein. The braking system shall include manual or automatic slack adjusters, piping, hose connections, gladhands conforming to SAE J318, spring loaded dust covers or dummy glad hands equipped with security chains, and all other components required for a complete air-brake system. Air-hose fittings and location shall comply with SAE J702. The braking system shall be installed in a manner which provides road clearance for travel over uneven terrain and protection against damage caused by objects striking components. No part of the braking system shall extend below the bottom of wheel rims.

3.8.6.1 Parking brakes. Spring or air diaphragm mechanical lock-type parking brakes shall be furnished. The parking brakes shall be automatically applied upon disconnection of the emergency air line and under emergency braking conditions. The parking brakes shall remain in the applied condition with no additional application and despite the depletion of all air pressure. Parking brakes shall conform to DoT Federal Motor Carrier Safety Regulations, section 393.41.

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:18Z
Check the source to verify that this is the currentversion before use.

3.8.7 Upper fifth wheel plate. The upper fifth wheel plate shall be designed for coupling to a full oscillating and fore and aft rocking type fifth wheel, and shall be of sufficient size to cover a fifth wheel 914 mm in diameter, and shall conform to DoT Federal Motor Carrier Safety Regulations, section 393.70(b). The kingpin shall fabricated of heat treated alloy steel and shall conform to SAE J700. The forward end of the upper fifth wheel plate or skid plate shall have a turned up lip for ease of loading and for body protection.

3.8.8 Lighting. Unless otherwise specified (see 6.1.1), the electrical lighting system shall be 12-volt (V) potential. The lighting system shall conform to DoT Federal Motor Carrier Safety Regulations, sections 393.14, 393.20, 393.22, 393.23, 393.25 through 393.29, 393.32, and 393.33. All lights and reflectors shall be protected from operational hazards by mounting in recessed or otherwise guarded locations. Lights and reflectors shall not be mounted on vertical surfaces of the rub rails or semitrailer bumpers. The front of the semitrailer shall be equipped with a receptacle conforming to SAE J560, with the conductors connected and color coded as specified therein. The receptacle shall be located in accordance with SAE J702. All electrical wiring shall conform to SAE J555.

3.8.8.1 Receptacle system 24V. When specified (see 6.1.1), the semitrailer shall be equipped with one 12-contact receptacle with cover and one 7-contact receptacle with cover installed at the front of the semitrailer. The 12-contact receptacle shall conform to MS75021, part No. MS75021-1. The 7-contact receptacle shall conform to SAE J560 round socket for jumper cable. The 12-contact receptacle shall be provided with resistance for each circuit to reduce the voltage of a tactical military design towing vehicle from 24V to 12V. The 7-contact socket shall be wired in accordance with SAE J560 to supply 12V directly to the semitrailer circuits. The 24V, 12-contact receptacle shall be connected through the necessary resistors into the 12V trailer circuits as follows:

A - Do not connect.
B - Connect to circuit No. 3.
C - Do not connect.
D - Connect to circuit No. 1.
E - Connect to circuits No. 2 and 6.
F - Do not connect.
H - Do not connect.
J - Connect to circuit No. 5.
K - Connect to circuit No. 7.
L - Do not connect.
M - Do not connect.
N - Do not connect.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:18Z
Check the source to verify that this is the current version before use.

Circuits B and J on tactical truck-tractors are combination stop and turn indicator circuits. The normal 12V turn signal lights will function both as turn signals and stoplights and the normal 12V stoplights will not be in operation when the semitrailer is connected to a towing vehicle with a 24V power supply. Because of this condition, the No. 4 on a stoplight circuit is not connected to the 24V, 12-contact receptacle.

3.8.9 Landing gear. Semitrailer shall have two vertical lift, telescopic, nonrotating landing legs, with two speed gears and a handcrank on the curb side. Landing legs shall be equipped with steel wheels or self-leveling skid pads. Supports for the crank extension shafts and clips for holding cranks, when folded, shall be provided. The landing gear shall withstand, without deformation, the combined static and dynamic forces due to proportion of gross weight sustained and the forces resulting from impact during coupling and uncoupling operations. When placed in travel position, the landing gear legs shall remain positively locked. The landing gear shall have a range of adjustment to vary the height of the upper fifth wheel from 1193 mm to not less than 1320 mm from the ground. With the semitrailer coupled to a towing tractor and in level position, the clearance under the fully retracted landing gear shall exceed the semitrailer ground clearance, but shall in no case be less than 297 mm.

3.8.10 Rear end protection. Semitrailer rear end protection shall be in accordance with DoT Federal Motor Carrier Safety Regulations, section 393.86.

3.8.10.1 Dock bumper. A dock bumper, extending not less than 38 mm beyond the rear of the semitrailer, shall be furnished. The dock bumper shall be the full width of the trailer.

3.8.11 Rear wheel splash and stone throw protection. Rear wheels shall have mud flaps at rear. Splash and stone throw protection shall be in accordance with SAE J682.

3.8.2 Fenders. Steel or aluminum fenders shall be provided over the semitrailer wheels.

3.8.13 Walkway. A walkway shall be provided on top of the body. The walkway shall have a non-slip, safety surface such as abrasive type paint or tape.

3.8.14 Ladder. A sturdy steel or aluminum ladder for access to the top of the body shall be provided.

3.8.15 Hose carrier. Manufacturer's standard type hose carrier shall be provided.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:18Z
Check the source to verify that this is the current version before use.

3.9 Lifting and tying down attachments. When specified (see 6.1.1), the semitrailer shall be provided with lifting and tying down attachments conforming to MIL-STD-209, type III. Attachments shall be designed for lifting and tying down the unloaded semitrailer. The attachments shall be identified by stenciling or other comparable marking on the semitrailer. The marking shall clearly indicate the purpose of the attachment.

3.10 Lubrication. Lubrication means shall be provided for all parts of the semitrailer normally requiring lubrication. Where the use of high lubricating pressure will damage grease seals or other parts, fittings with pressure release shall be used.

3.11 Treatment, painting, identification marking, and data plates. Treatment, painting, identification marking, and data plates shall be in accordance with MIL-STD-1223, as specified for the Navy, except the exterior color shall be green No. 14064 of FED-STD-595.

3.12 Rustproofing. When specified (see 6.1.1), the vehicle shall be rustproofed in accordance with FED-STD-297.

3.13 Servicing and adjusting. Prior to acceptance of the semitrailer by the Government, the contractor shall service and adjust the semitrailer for immediate operational use as required in the operator's manual. The servicing and adjusting shall include at least the following:

a. Inflation of all tires.
b. Adjustment of brakes.
c. Proper functioning of all lighting and electrical systems.
d. Complete lubrication with grades of lubricants recommended for ambient temperature at the delivery point.

The semitrailer shall be conspicuously tagged to identify the lubricants and their temperature range.

3.14 Identification plate. An identification plate will be furnished by the contracting officer for each semitrailer. The contractor shall stamp all necessary data in the blank spaces of the plate provided for that purpose, and securely affix a plate to each semitrailer in a conspicuous place with nonferrous screws, rivets, or bolts not less than 3 mm in diameter. The applicable nomenclature contained in the contract item description shall be placed in the top blank.

3.15 Workmanship.

3.15.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:18Z
Check the source to verify that this is the current version before use.

3.15.2 Bolted connections. Boltholes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.15.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.15.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

3.15.5 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or any other defect which reduces the castings ability to perform its intended function.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:18Z
Check the source to verify that this is the current version before use.

4.2.1 First production vehicle inspection. The first production vehicle inspection shall be performed on one semitrailer when a first production vehicle is required (see 3.2 and 6.1.1). This inspection shall include the examination of 4.3 and the tests of 4.4. The production vehicle may be either a first production item or a standard production item from the supplier's current inventory provided the semitrailer meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining semitrailers to be furnished under the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.3, the tests of 4.4, and the packaging inspection of 4.6. This inspection shall be performed in accordance with 4.3.

4.3 Examination. Each semitrailer shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.4 First production vehicle tests. When a first production vehicle is required, it shall be subject to the tests specified in 4.4.1 through 4.4.6. Failure to pass any phase of the required tests shall be cause for the Government to refuse acceptance of all semitrailers until corrective action has been taken.

4.4.1 Vehicle weight. Semitrailer shall be weighed to determine net weight and distribution of net weight on fifth wheel and axle(s). The imposed loading on the fifth wheel and axle shall be computed using the net weight and the payload. Calculated imposed loads on fifth wheel and axle(s) shall be utilized to ascertain that the suspension, axle(s), and tires furnished are of adequate capacity to meet contract requirements, and to determine conformance to 3.6.

4.4.2 Road test. Road test shall consist of coupling the semitrailer loaded with rated payload to a truck-tractor. The tractor combination shall be driven a distance of not less than 32 km under the conditions specified in 3.7. At least 20 percent of the distance shall be over hard uneven terrain. At least five sudden stops shall be made from a speed not less than 32 kmph. Service brakes and parking brake shall be checked for conformance to 3.7.3. Tracking ability shall be observed to verify conformance to 3.7.2. After test, the semitrailer shall be examined for evidence of misalinement, binding, or other malfunction.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:18Z
Check the source to verify that this is the current version before use.

4.4.3 Turning ability test. A truck-tractor shall be coupled to the semitrailer and driven through turns up to 90° right and left to determine conformance to 3.7.1.

4.4.4 Landing gear test. Upon completion of the road test, function of landing gear shall be tested to verify conformance to 3.8.10.

4.4.5 Pressure tests. Pressurize the body to the manufacturer's recommended discharge pressure for 30 minutes. Monitor a pressure gage for any drop in pressure and check for leaks around manholes, valves, and lines as necessary. Increase the pressure 1-1/2 times the discharge pressure for 5 minutes. Examine body for any damage and check for any equipment malfunction. The pressure test may be conducted with or without payload.

4.4.6 Discharge system test. With the system under pressure, operate all valves and controls not less than 10 times to determine the system is functioning properly. Check gravity system for conformance to 3.8.2.

4.5 Production semitrailer tests. The contractor's testing system shall, as a minimum, ensure that the semitrailer is capable of meeting the performance requirements specified herein.

4.6 Packaging inspection. The preservation and packaging of the semitrailers shall be inspected to verify conformance to the requirements of section 5.

5. PACKAGING

5.1 Vehicle processing. The equipment shall be preserved and packaged in accordance with the contractor's standard practice. When specified (see 6.1.1), equipment shall be preserved, packaged, and marked in accordance with the mobile requirements of MIL-STD-281 with the level of preservation and packaging as specified (see 6.1.1).

6. NOTES

6.1 Ordering data.

6.1.1 Acquisition requriements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. When first production vehicle is required for inspection (see 3.2, 4.2.1, and 6.3).
c. When a pneumatic discharge system is required (see 3.8.2)
d. When disk-type wheels are required (see 3.8.5.1).
e. When spare wheel is not required (see 3.8.5.4).
f. When spare tire is required (see 3.8.5.5).
g. When lighting system shall be other than as specified (see 3.8.8).

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:18Z
Check the source to verify that this is the current version before use.

h. When 24V receptacle system is required (see 3.8.8.1).
i. When lifting and tying down attachments are required (see 3.9).
j. When rustproofing is required (see 3.12).
k. When MIL-STD-281 is required and level of preservation and packaging required (see 5.1).

6.2 Data requirements. When this specification is used in an acquisition and data are required to be delivered, the data requirements shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved Contract Data Requirements List (CDRL), incorporated into the contract. When the provisions of DOD FAR Supplement, Part 27, Sub-Part 27.410-6 (DD Form 1423) are invoked and the DD Form 1423 is not used, the data shall be delivered by the contract or in accordance with the contract or purchase order requirements.

6.3 First production vehicle. When a first production vehicle inspection is required, the vehicle shall be tested and should be a first production vehicle or a standard vehicle from the contractor's current inventory. The contracting officer should include specific instructions in the contract regarding arrangements for examination, test, and approval of the first production vehicle (see 3.2 and 4.2.1).

6.4 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

6.5 Definitions.

6.5.1 Improved road. An improved road is a smooth, hard surfaced road, such as a concrete or asphalt paved highway.

6.5.2 Unimproved road. An unimproved road is an unpaved, unstabilized road with an undulating surface having occasional chuckholes and exposed rocks.

6.6 Subject term (key word) listing.

Body, pressure vessel type, trailer mounted
Cement, hauler
Semitrailer, tandem axle
Trailer, cement
Transportation, bulk material

Custodian:
Navy - YD

Preparing activity:
Navy - YD

(Project 2330-N931)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:18Z
Check the source to verify that this is the current version before use.