MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, ELECTROLYTIC (NONSOLID ELECTROLYTE), TANTALUM, (NONPOLARIZED, HIGH ETCHED FOIL), 85°C (VOLTAGE DERATED TO 125°C), ESTABLISHED RELIABILITY, STYLE CLR73

This amendment forms a part of Military Specification Sheet MIL-C-39006/17A, dated 30 January 1976, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Following preamble note, add:

* FAILURE RATE LEVEL 'L' INACTIVE FOR DESIGN AFTER 27 May 1976 *

* CASE SIZES E3, E4, and E5 INACTIVE FOR DESIGN AFTER 27 May 1976 *

* CASE SIZE E1 INACTIVE FOR DESIGN AFTER 20 Oct 1978 *

* CASE SIZE E2 INACTIVE FOR DESIGN AFTER 12 May 1980 *

FIGURE 1 (dimension table), C Max, Case size G2,: Delete "1.406 (35.71)" and substitute "1.469 (37.31)".

FIGURE 1 (dimension table): Add G1 case size

G1	.688 (17.48)	.188 (4.78)	.219 (5.56)	1.188 (30.18)	

PAGE 3

* TABLE I, following part no. M39006/17-: Add "1/".

* TABLE I, part number column: Add "-" following numbers 2036 through 2174 to denote optional random vibration part numbers.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:16Z
Check the source to verify that this is the current version before use.

* TABLE I: Add the new G1 case size units

Rated voltage (85°C)	Cap.	Cap. tolerance	DC leakage (max) 25°C	85°C	125°C	Derated voltage (125°C)	Surge voltage (85°C)	Impedance (max)	Case size	Part no. M39006/17- 1/ Failure rate level (%/1,000 hr) L (2.0)	M (1.0)	P (0.1)	R (0.01)	S (0.001)
15	20.0	+75,-15	5	24	16	10	17.2	185	G1	2000	2035-	2070-	2105-	2140-
25	10.0	+75,-15	4	20	12	15	28.8	370	G1	2005	2040-	2075-	2110-	2145-
30	8.0	+75,-15	3	19	12	20	34.5	455	G1	2010	2045-	2080-	2115-	2150-
50	3.5	+50,-15	3	14	9	30	57.5	1060	G1	2015	2050-	2085-	2120-	2155-
75	2.0	+50,-15	2	12	8	50	86.2	1850	G1	2020	2055-	2090-	2125-	2160-
100	1.4	+30,-15	2	11	7	65	115.0	2700	G1	2025	2060-	2095-	2130-	2165-
150	0.75	+30,-15	2	9	6	100	172.0	5000	G1	2030	2065-	2100-	2135-	2170-

* Following Table I: Add "1/ Dash number for failure rate level M, P, R, and S parts will include the letter 'H' to indicate the optional random vibration requirement or '-' will be deleted."

PAGE 4

* Following vibration requirement, add new Random vibration requirement:
"Random vibration (when applicable): Method 214 of MIL-STD-202, test condition II-E (18.7 g)."

Temperature cycling: Delete "Temperature cycling: Method 102 of MIL-STD-202, condition D" and substitute "Thermal shock: Method 107 of MIL-STD-202, condition A."

PAGE 5

Life at 85°C: Delete "240-hr (group B)" requirement in its entirety; also delete "10,000-hr (group C)" and substitute "10,000-hr (group B)".

Vacuum life: Delete "DF" requirement and substitute "DF — 20% (≤50 V) or 15% (>50 V) (max)."

Add the following new requirement under "Life at 125°C":

"10,000-hr (group B):

DCL (125°C)	-	125% (max) of table I value.
DCL (25°C)	-	See table I.
ΔCap.	-	Within ±50% of initial measurement for E1, E2, and G1 cases; within ±25% of initial measurement for all other cases.
DF	-	80% (<30 V) or 60% (>30 V) (max) for E1, E2, and G1 cases; 40% (≤30 V) or 30% (>30 V) (max) for all other cases.
DWV	-	2,000 Vdc, min.
IR	-	100 megohms, min."

NOTE: The margins of this amendment are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:16Z
Check the source to verify that this is the current version before use.

Custodians:
Army - ER
Navy - EC
Air Force - 11

Review activities:
Army - AR
Air Force - 17, 85, 99
DLA - ES

User activities:
Navy - AS, MC, OS
Air Force - 19

Agent:
DLA-ES

Preparing activity:
Navy - EC

(Project 5910-1404-6)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:16Z
Check the source to verify that this is the current version before use.